# University of Nebraska - Lincoln Digital Commons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

11-27-1957

Test 626: Ford 850-L

Tractor Test & Power Museum University of Nebraska, jsteele4@unl.edu

Follow this and additional works at: http://digitalcommons.unl.edu/tractormuseumlit



Part of the Applied Mechanics Commons

Museum, Tractor Test & Power, "Test 626: Ford 850-L" (1957). Nebraska Tractor Tests. Paper 18. http://digitalcommons.unl.edu/tractormuseumlit/18

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST NO. 626

Department of Agricultural Engineering Dates of test: June 24, 1957 to July 12, 1957 Manufacturer: FORD MOTOR COMPANY, BIRMINGHAM, MICHIGAN Manufacturer's rating: Not rated

BELT HORSEPOWER TESTS

Нр	Crank shaft speed rpm	Fuel Consumption				Temp. Deg. F.				Barometer		
		Gal per h	r	Hp-hr per gal		per -hr	Cooling	1	Air vet ulb	Air dry bulb	inches of mercury	
	1	TEST B	-100	% MA	XIMU	M LOA	D-TV	VO H	OURS			
39.55	2200	5.00	08	7.90	0.5	38	179		65	71	28	.662
0	TES	T C-	OPERA	ATING	MAX	MUM	LOAD	-ON	E HO	UR		9 11
38.22	2200	4.62	24	8.27	0.5	514	184		73	81	28	.833
11,16	William Inc.	T	EST D	-RAT	ED LO	DAD-	ONE I	HOUR				111
35.50	2199	4.40	7	8.06	0.5	28	179		73	80	28	.845
TEST	E-VAR	YING I	LOAD	-TWO	OHOU	JRS (2	20 minu	ite ru	ns; las	t line a	average	:)
35.49	2199	4.41	2	8.04	0.5	28	177		72	79		
1.52	2364	1.962		0.77	5.4	87	141	1 43	72	78	l	
18.72	2308	3.155		5.93	0.7	16	144	44 72		79	1 2	
37.15	2053	4.49	6	8.26	0.5	14	174		72	78	1 22	
9.54	2351	2.54	18	3.74	3.74   1.135		143	72		78		
27.43	2265	3.86	51	7.10	0.598		165 73		73	79	****	
21.64	2256	3.40	06	6.35   0.669		669	157	i u	72		28.830	
	HIPOHII	TEST	' L—(	OPERA	TING	MAXI	MUM 7	ORQ	UE			
of rate	d rpm (en	gine)	100	95	90	85	80	75	70	65	60	56
of rated-speed torque		100	103	105	108	110	112	112	111	109	109	

DRAWBAR HORSEPOWER TESTS

Нр	Draw	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels	Fue	Tem	Temp. Deg. F.				
	bar pull lbs				Gal per hr	Hp-hr per gal	Lb per hp-hr	Cool- ing med	Air wet bulb	Air dry bulb	Barometer inches of mercury
		TES	T H—F	ATED	LOAD-	TEN H	OURS-	3rd Gea	ar		
28.26	2329	4.55	1997	4.67	3.720	7.60	0.559	187	77	91	28.888
		-11-11-11	TE	ST F—1	00% M	AXIMUN	I LOAD			111	en bas
35.16	2947	4.47	2001	6.44	3rd g	ear		189	75	84	28.790
15/21	COL III	THE R. P. LEWIS CO., LANSING	TEST (	G—OPE	RATING	MAXI	MUM LC	AD	100		
26.99	5170	1.96	1997	13.34	1st ge	ear (prt	t-thrtl)	173	75	84	28.790
34.09	3880	3.29	2000	8.48	2nd g	ear		186	73	83	28.810
34.32	2871	4.48	2000	6.22	3rd g	ear		185	73	83	28.810
34.21	2032	6.31	2000	4.48	4th g	ear		185	73	83	28.810
32.23	1053	11.48	2002	2.34	5th g	ear		172	74	86	29.035
			TEST	—OPEF	RATING	MAXIN	IUM LO	AD			
27.73	2507	4.15	1999	14.39	3rd ge	ar (prt-	thrtl)	186	75	89	29.015
			TEST I	K—OPF	RATING	MAXI	MUM LC	OAD			
21,90	2128	3.86	2000	12.91	3rd ge	ar (prt-	thrtl)	171	73	89	28.720

FORD 850-L (LPG)

FUEL, OIL, WATER and TIME Fuel Commercial Propane Weight per gallon 4.25 lb Oil SAE 20-20W To motor 1.174 gal Drained from motor 0.877 gal Water used 0.285 gal Total time motor was operated 46½ hours.

CHASSIS TYPE Standard Serial No. 850-L127727
Tread width rear 52" to 76" front 52" to 80"
Wheel base 74.5" Hydraulic control system direct
engine drive Advertised speeds mph first 2.30 second 3.66 third 4.87 fourth 6.72 fifth 11.96 reverse
3.93 Belt pulley diam. 9" Face 6½" rpm 1279
Belt speed 3015 fpm Belt flat Length 71' Width 6"
Thickness 0.215" Maximum slip 0.87% Clutch
single plate dry disc operated by foot pedal Seat
pressed steel cushioned by rubber in torsion Brakes
internal expanding shoes operated by two foot pedals
located on right hand side of tractor Equalized by
foot action Power take-off conventional type Steering aided by hydraulic power steering.

ENGINE Make Ford LPG Type 4 cylinder vertical Serial No. 850-L127727 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and stroke 3.90" x 3.60" Rated rpm belt 2200 drawbar 2000 Compression ratio 8.0 to 1 Displacement 172 cu. in. Valve Port diameter Inlet 1.46" Exhaust 1.26" Governor variable speed centrifugal Carburetor size 1" Ignition system battery Starting system 6 volt battery Air cleaner oil washed wire mesh Muffler was used Oil filter full flow with replaceable paper element Cooling medium temperature control thermostat.

**REPAIRS AND ADJUSTMENTS** No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectivly. Tests C, D, E, G, H, J, K and L were made with an operating setting of the carburetor (selected by the manufacturer) of 97.0% of maximum belt horsepower.

TIRES, WHEELS AND WEIGHT

	Tests F, G, & H	Test J	Test K	
Rear wheels Type	Pressed steel	Pressed steel	Pressed steel	
Liquid ballast	383 lb each	None	None	
Added cast iron	1080 lb each	None	None	
Rear tires No. and size	Two 12-28	Two 12-28	Two 10-28	
Ply	4	4	4	
Air pressure	14 lb	14 lb	12 lb	
Front wheels Type	Pressed steel	Pressed steel	Pressed steel	
Liquid ballast	69 lb each	None	None	
Added cast iron	104 lb each	None	None	
Front tires No. and size	Two 6.00-16	Two 6.00-16	Two 6.00-16	
Ply	4	4	4	
Air pressure	28 lb	28 lb	28 lb	
Height of drawbar	23 inches	24 inches	21 inches	
Static weight Rear end	4856 lb	1930 lb	1850 lb	
Front end	1665 lb	1320 lb	1314 lb	
Total weight as tested with operator	6696 lb	3425 lb	3339 lb	

HORSEPOWER SUMMA	RY	
	Drawbar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and		
29.92" Hg)	37.37	41.72
2. Observed maximum horsepowe (tests F and B)	r 35.16	39.55
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (ASA)	d d	
and SAE ratings)	28.03	35.46
We, the undersigned, certify that the correct report of official Tractor Test		ue and
L. F. LARSEN Engineer-in-Charge		
L. W. HURL G. W. STEIN		

J. J. SULEK Board of Tractor Test Engineers

## EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissable include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

#### BELT HORSEPOWER TESTS

TEST B: The throttle valve is wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel econonmy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. This more practical carburetor setting is used in all later tests except test F. The throttle valve is wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors which have an altogether different fuel system.

TEST D: The throttle control lever is set so that the governor will maintain rated engine speed when rated load is applied. Rated load is 85% of 100% maximum, as obtained in test B, corrected to standard conditions.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

### TEST E:

Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads, of 20 minutes each; rated load, no load, ½ rated load, maximum load at wide open throttle valve, ¼ and ¾ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

TEST L: This torque test is run with wide open throttle. Loads are applied to reduce engine speed in approximately ten 5% increments. Rated speed equals 100%. The corresponding dynamometer torque is recorded as a per cent of torque at rated speed.

## DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instru-

ment in the test car. When rubber tires are used, all tests are made on the concrete test course. All crawler type tractors are tested on a dirt test course which is maintained by grading, sprinkling and rolling so that it remains very nearly the same throughout the season. The same tires, wheels and weights are used for all tests except J and K.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in this test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 16%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated load the throttle control lever is set to maintain rated engine speed. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: Similar to test J except that the smallest tires and lighest wheels offered by the manufacturer are used.

