## University of Nebraska - Lincoln Digital Commons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1950

## Test 442: Cockshutt 40

Nebraksa Tractor Test Laboratory Submitted by Larsen Museum University of Nebraska-Lincoln

Follow this and additional works at: http://digitalcommons.unl.edu/tractormuseumlit



Part of the Applied Mechanics Commons

Submitted by Larsen Museum, Nebraksa Tractor Test Laboratory, "Test 442: Cockshutt 40" (1950). Nebraska Tractor Tests. Paper 140. http://digitalcommons.unl.edu/tractormuseumlit/140

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Department of Agricultural Engineering
Dates of test: June 12 to June 17, 1950.
Manufacturer: COCKSHUTT PLOW CO. LTD.,
BRANTFORD, ONTARIO, CANADA
Manufacturer's rating: Not rated.

The Experiment Station University of Nebraska College of Agriculture W. V. Lambert, Director, Lincoln, Nebraska

BELT	HORSEPOWER	TESTS

Нр		ank	Fuel Consumption		Water	Temp Deg F			Barometer	
	shaft speed rpm	eed	Gal per hour	Hp-hr per gal	Lb per hp-hour	used gal per hour	Cooling med	Air		in Hg
		TE	ST B—1	00% MA	XIMUM LO	DAD—TW	O HOU	RS		
43.30	1 10	550	4.537	9.544	0.637	0.00	182	1 74		28.793
		TEST	C-OPE	RATING	MAXIMU	M LOAD-	ONE H	OUR		
41.44	1 10	550	3.658	11.33	0.537	0.00	196	80		28.830
			TE	ST D—R	ATED LOA	D-ONE	HOUR	-		
38.68	1 16	550	3.545	10.91	0.557	0.00	196	85	1	28.830
					O HOURS	1	-		100	ALCOHOLD AND ADDRESS OF THE PARTY OF THE PAR
38.72		551	3.548	10.91	0.557	1	198	87	-	
1.84		744	1.540	1.19	5.087		156	85	-	
20.41		734	2.492	8.19	0.742		178	87	-	
39.14		76	3.484	11.23	0.541		203	89	-	
10.19		728	1.890	5.39	1.128		174	89	-	
29.62		582	3.020	9.81	0.620		190	90	1	
23.32	1 16	686	2.662	8.76	0.694	0.00	183	88		28.830
			DR	AWBAR	HORSEPOV	WER TEST	ГS			
11113	Draw	Speed	Crank	Slip	Fuel Cons	sumption	Water	Temp	Deg F	1_
Нр	bar pull lb	miles per hr	shaft speed rpm	of drive wheels	Gal Hp per per hour ga		gal per hour	Cool- ing med	Air	Barometer in Hg
	-	T7	EST F		IAXIMUM I					
37.85	2748	5.16		4.55		t Recorded		176	78	28.755
57105	27 10	3.10	TEST C	-	ATING MA		LOAD	170	1 / 0	1 20.755
20.42	5538	1.38	1651	16.96		t Recorded		162	74	28.940
31.14	4494	2.60	1649	7.82	"	"		164	70	28.935
34.58	3632	3.57	1654	6.55	"	"		189	91	28.770
34.58	2514	5.16	1652	4.48	"	"		189	91	28.770
29.40	1762	6.26	1650	3.12	"	"		164	75	28.940
24.68	759	12.19	1653	1.49	"	"		161	74	28.940
		TEST	H-RA	TED LO	DAD-TEN	HOURS-	-4th GE	AR		
30.36	2187	5.21	1651	3.53	3.124   9.7	72   0.625	0.00	185	89	28.782
		TEST	' I-OPE	RATING	MAXIMU	M LOAD-	4th GE	AR	-	
-11										
32.92	2422	5.10	1649	3.79	Not	t Recorded		171	77	28.975
32.92	2422		1649	3.79	Not G MAXIMU	t Recorded			77	28.975

FUEL, OIL and TIME Gasoline octane No ASTM 76 Research 82 (rating taken from oil company's typical inspection data); weight per gallon 6.079 lb Oil SAE 30; to motor 2.209 gal; drained from motor 0.954 gal Total time motor was operated 49 hours.

CHASSIS Type standard Serial No 40-1042 Tread width rear 61¾" and 78¾" front 53¾" and 59" Wheel Base 86 9/16" Hydraulic control system direct engine drive Advertised speeds mph first 1.6 second 2.7 third 3.7 fourth 5.25 fifth 6.25 sixth 12.00 reverse 2.2 and 5 Belt pulley diam 12" face 8½" rpm 997 Belt speed 3131 fpm Clutch dry disk clutch for transmission and wet multiple disk clutch for power take-off Seat spring cushion with padded backrest Brakes combination external and internal shoe operated by two foot pedals Equalized by locking brakes together Power take-off "LIVE" power take-off with independent clutch.

ENGINE Make Buda Type 6 cylinder vertical Serial No 332620 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and Stroke 3 7/16" x 4\%" Rated rpm 1650 Compression ratio 6.18-1 Displacement 230 cu in Port Diameter Valves inlet 1\%" exhaust 1\%" Governor variable speed centrifugal Carburetor Size 1\%" Ignition System 6 volt battery Air Cleaner oil washed wire mesh Muffler used Oil Filter replaceable paper element Cooling medium temperature control thermostat.

REPAIRS AND ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J and K were made with an operating setting of the carburetor (selected by the manufacturer) of 96.1% of maximum belt horsepower.

## TIRES, WHEELS and WEIGHT

	Tests F, G & H	Test J	Test K	
Rear wheels Type	Pressed steel	Pressed steel	Pressed steel	
Liquid ballast	333 lb each	None	None	
Added cast iron	1200 lb each	None	None	
Rear tires No. and size	Two 13-38	Two 13-38	Two 12-38	
Ply	6	16	14	
Air pressure	14 lb	12 lb	12 lb	
Front wheels Type	Cast iron	Cast iron	Cast iron	
Liquid ballast	None	None	None	
Added cast iron	None	None	None	
Front tires No. and size	Two 7.50-16	Two 7.50-16	Two 6.00-16	
Ply	4	4	4	
Air pressure	28 lb	28 lb	28 lb	
Height of drawbar	16½ inches	18 inches	17½ inches	
Static weight Rear end	6428 lb	3362 lb	3312 lb	
Front end	1758 lb	1758 lb	1712 lb	
Total weight as tested with operator	8371 lb	5305 lb	5209 lb	

## HORSEPOWER SUMMARY

	Draw- bar	Belt
<ol> <li>Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg)</li> </ol>	40.06	45.59
2. Observed maximum horsepower (tests F and B)	37.85	43.30
<ol> <li>Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (form-</li> </ol>	X.	
erly ASAE and SAE ratings)	30.05	38.75

We, the undersigned, certify that this is a true and correct report of official tractor test No. 442.

L. F. Larsen Engineer in Charge

C. W. Smith
L. W. Hurlbut
F. D. Yung
Board of Tractor
Test Engineers