

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 1950

Test 442: Cockshutt 40

Nebraska Tractor Test Laboratory Submitted by Larsen Museum
University of Nebraska-Lincoln

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Submitted by Larsen Museum, Nebraska Tractor Test Laboratory, "Test 442: Cockshutt 40" (1950). *Nebraska Tractor Tests*. 140.
<http://digitalcommons.unl.edu/tractormuseumlit/140>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Department of Agricultural Engineering
 Dates of test: June 12 to June 17, 1950.
 Manufacturer: COCKSHUTT PLOW CO. LTD.,
 BRANTFORD, ONTARIO, CANADA
 Manufacturer's rating: Not rated.

The Experiment Station
 University of Nebraska College of Agriculture
 W. V. Lambert, Director, Lincoln, Nebraska

NEBRASKA TRACTOR TEST NO. 442

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer in Hg
		Gal per hour	Hp-hr per gal	Lb per hp-hour		Cooling med	Air	
TEST B—100% MAXIMUM LOAD—TWO HOURS								
43.30	1650	4.537	9.544	0.637	0.00	182	74	28.793
TEST C—OPERATING MAXIMUM LOAD—ONE HOUR								
41.44	1650	3.658	11.33	0.537	0.00	196	80	28.830
TEST D—RATED LOAD—ONE HOUR								
38.68	1650	3.545	10.91	0.557	0.00	196	85	28.830
TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average)								
38.72	1651	3.548	10.91	0.557	...	198	87
1.84	1744	1.540	1.19	5.087	...	156	85
20.41	1734	2.492	8.19	0.742	...	178	87
39.14	1576	3.484	11.23	0.541	...	203	89
10.19	1728	1.890	5.39	1.128	...	174	89
29.62	1682	3.020	9.81	0.620	...	190	90
23.32	1686	2.662	8.76	0.694	0.00	183	88	28.830

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lb	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer in Hg
					Gal per hour	Hp-hr per gal	Lb per hp-hr		Cooling med	Air	
TEST F—100% MAXIMUM LOAD—4th GEAR											
37.85	2748	5.16	1655	4.55	Not Recorded			176	78	28.755	
TEST G—OPERATING MAXIMUM LOAD											
20.42	5538	1.38	1651	16.96	Not Recorded			162	74	28.940	
31.14	4494	2.60	1649	7.82	" "			164	70	28.935	
34.58	3632	3.57	1654	6.55	" "			189	91	28.770	
34.58	2514	5.16	1652	4.48	" "			189	91	28.770	
29.40	1762	6.26	1650	3.12	" "			164	75	28.940	
24.68	759	12.19	1653	1.49	" "			161	74	28.940	
TEST H—RATED LOAD—TEN HOURS—4th GEAR											
30.36	2187	5.21	1651	3.53	3.124	9.72	0.625	0.00	185	89	28.782
TEST J—OPERATING MAXIMUM LOAD—4th GEAR											
32.92	2422	5.10	1649	3.79	Not Recorded			171	77	28.975	
TEST K—OPERATING MAXIMUM LOAD—4th GEAR											
31.71	2451	4.86	1650	9.96	Not Recorded			174	79	28.975	

TIRES, WHEELS and WEIGHT

	Tests F, G & H	Test J	Test K
Rear wheels			
Type	Pressed steel	Pressed steel	Pressed steel
Liquid ballast	333 lb each	None	None
Added cast iron	1200 lb each	None	None
Rear tires			
No. and size	Two 13-38	Two 13-38	Two 12-38
Ply	6	6	4
Air pressure	14 lb	12 lb	12 lb
Front wheels			
Type	Cast iron	Cast iron	Cast iron
Liquid ballast	None	None	None
Added cast iron	None	None	None
Front tires			
No. and size	Two 7.50-16	Two 7.50-16	Two 6.00-16
Ply	4	4	4
Air pressure	28 lb	28 lb	28 lb
Height of drawbar	16½ inches	18 inches	17½ inches
Static weight			
Rear end	6428 lb	3362 lb	3312 lb
Front end	1758 lb	1758 lb	1712 lb
Total weight as tested with operator	8371 lb	5305 lb	5209 lb

FUEL, OIL and TIME Gasoline octane No ASTM 76 Research 82 (rating taken from oil company's typical inspection data); weight per gallon 6.079 lb Oil SAE 30; to motor 2.209 gal; drained from motor 0.954 gal Total time motor was operated 49 hours.

CHASSIS Type standard Serial No 40-1042 Tread width rear 61¼" and 78¾" front 53¾" and 59" Wheel Base 86 9/16" Hydraulic control system direct engine drive Advertised speeds mph first 1.6 second 2.7 third 3.7 fourth 5.25 fifth 6.25 sixth 12.00 reverse 2.2 and 5 Belt pulley diam 12" face 8½" rpm 997 Belt speed 3131 fpm Clutch dry disk clutch for transmission and wet multiple disk clutch for power take-off Seat spring cushion with padded backrest Brakes combination external and internal shoe operated by two foot pedals Equalized by locking brakes together Power take-off "LIVE" power take-off with independent clutch.

ENGINE Make Buda Type 6 cylinder vertical Serial No 332620 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and Stroke 3 7/16" x 4 1/8" Rated rpm 1650 Compression ratio 6.18-1 Displacement 230 cu in Port Diameter Valves inlet 1 1/8" exhaust 1 1/8" Governor variable speed centrifugal Carburetor Size 1 1/8" Ignition System 6 volt battery Air Cleaner oil washed wire mesh Muffler used Oil Filter replaceable paper element Cooling medium temperature control thermostat.

REPAIRS AND ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J and K were made with an operating setting of the carburetor (selected by the manufacturer) of 96.1% of maximum belt horsepower.

HORSEPOWER SUMMARY

	Draw-bar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg)	40.06	45.59
2. Observed maximum horsepower (tests F and B)	37.85	43.30
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings)	30.05	38.75

We, the undersigned, certify that this is a true and correct report of official tractor test No. 442.

L. F. Larsen
 Engineer in Charge

C. W. Smith
 L. W. Hurlbut
 F. D. Yung
 Board of Tractor
 Test Engineers