

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

January 2004

## Test 2204: Case IH MXU135 Diesel

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

---

"Test 2204: Case IH MXU135 Diesel" (2004). *Nebraska Tractor Tests*. 236.  
<http://digitalcommons.unl.edu/tractormuseumlit/236>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2204—NEBRASKA SUMMARY 496

## CASE IH MXU135 DIESEL

### 16 SPEED

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1037 rpm)</b>					
114.5 (85.4)	2199	7.19 (27.22)	0.443 (0.269)	15.93 (3.14)	
<b>Standard Power Take-off Speed (1000 rpm)</b>					
120.1 (89.6)	2120	7.21 (27.29)	0.424 (0.258)	16.65 (3.28)	
<b>Maximum Power (2 hours)</b>					
127.4 (95.0)	1900	7.17 (27.13)	0.397 (0.241)	17.77 (3.50)	

VARYING POWER AND FUEL CONSUMPTION					
114.5 (85.4)	2199	7.19 (27.22)	0.443 (0.269)	15.93 (3.14)	Air temperature
100.0 (74.6)	2257	6.58 (24.92)	0.464 (0.282)	15.19 (2.99)	73°F (23°C)
76.4 (57.0)	2298	5.49 (20.78)	0.507 (0.308)	13.92 (2.74)	Relative humidity
51.6 (38.5)	2326	4.41 (16.68)	0.602 (0.366)	11.72 (2.31)	56%
26.0 (19.4)	2358	3.28 (12.42)	0.888 (0.540)	7.94 (1.57)	Barometer
--	2372	2.31 (8.74)	--	--	29.8" Hg (101.0 kPa)

Maximum Torque - 408.2 lb.-ft. (553.4 Nm) at 1398 rpm  
 Maximum Torque Rise - 49.1%  
 Torque rise at 1800 engine rpm - 34%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged)

##### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—7th (1C) Gear</b>									
94.4 (70.4)	8275 (36.8)	4.28 (6.88)	2199	4.5	0.523 (0.318)	13.50 (2.66)	180 (82)	66 (19)	30.1 (101.9)
<b>75% of Pull at Maximum Power—7th (1C) Gear</b>									
74.0 (55.2)	6205 (27.6)	4.47 (7.20)	2279	3.5	0.581 (0.353)	12.14 (2.39)	180 (82)	66 (19)	30.1 (101.9)
<b>50% of Pull at Maximum Power—7th (1C) Gear</b>									
50.7 (37.8)	4145 (18.4)	4.58 (7.37)	2310	2.8	0.702 (0.427)	10.05 (1.98)	180 (82)	66 (19)	30.1 (101.9)
<b>75% of Pull at Reduced Engine Speed—8th (3B) Gear</b>									
74.3 (55.4)	6215 (27.6)	4.48 (7.21)	2020	3.6	0.551 (0.335)	12.79 (2.52)	178 (81)	72 (22)	30.1 (101.9)
<b>50% of Pull at Reduced Engine Speed—8th (3B) Gear</b>									
50.7 (37.8)	4135 (18.4)	4.60 (7.40)	2052	2.5	0.604 (0.368)	11.67 (2.30)	178 (81)	72 (22)	30.1 (101.9)

**Location of test:** Silsoe Research Institute, Wrest Park, Silsoe, MK45 4HS, United Kingdom

**Dates of test:** June to August, 2004.

**Manufacturer:** CNH U.K. Ltd., Basildon, Essex, SS14 3AD, England

**FUEL and OIL:** Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.847 Fuel weight 7.04 lbs/gal (0.8453 kg/l) Oil SAE 10W30 API service classification CH-4 Transmission and hydraulic lubricant MAT 3525 fluid Front axle lubricant MAT 3525 fluid

**ENGINE:** Make CNH Diesel Type six cylinder vertical with turbocharger and air to air intercooler Serial No. 00066631 Crankshaft lengthwise Rated engine speed 2200 Bore and stroke 4.094" x 5.196" (104.0 mm x 132.0 mm) Compression ratio 17.0 to 1 Displacement 410 cu in (6728 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements and aspirator Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler vertical Cooling medium temperature control thermostat and variable speed fan

**CHASSIS:** Type front wheel assist Serial No. 209584 Tread width rear 68.1" (1730 mm) to 83.9" (2130 mm) front 64.2" (1630 mm) to 81.9" (2080 mm) Wheelbase 104.4" (2652 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio with partial (4) range operator controlled powershift Nominal travel speeds mph (km/h) first 1.42 (2.28) second 1.73 (2.78) third 2.11 (3.40) fourth 2.58 (4.15) fifth 3.32 (5.35) sixth 4.06 (6.53) seventh 4.39 (7.07) eighth 4.96 (7.98) ninth 5.36 (8.63) tenth 6.06 (9.75) eleventh 6.56 (10.56) twelfth 8.02 (12.90) thirteenth 10.32 (16.60) fourteenth 12.60 (20.28) fifteenth 15.41 (24.80) sixteenth 18.83 (30.30) reverse 1.40 (2.25), 1.71 (2.75), 2.09 (3.37), 2.55 (4.10), 3.28 (5.28), 4.01 (6.45), 4.34 (6.98), 4.90 (7.89), 5.30 (8.53), 5.99 (9.64), 6.48 (10.43), 7.92 (12.75), 10.20 (16.41), 12.46 (20.05), 15.23 (24.51), 18.60 (29.94) Clutch multiple wet disc electro-hydraulically operated by foot pedal Brakes wet disc hydraulically operated by two foot pedals that can be locked together Steering hydrostatic Power take-off 540 rpm at 1969 engine rpm or 1000 rpm at 2120 engine rpm Unladen tractor mass 12020 lb (5452 kg)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Engaged)**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. <sup>o</sup> F(°C) cool- ing med	Temp. <sup>o</sup> F(°C) Air dry bulb	Barom. inch Hg (kPa)	
3rd(3A) Gear									
62.6 (46.7)	11755 (52.3)	2.00 (3.21)	2292	10.9	0.637 (0.388)	11.07 (2.18)	181 (83)	70 (21)	30.1 (101.9)
4th(4A) Gear									
73.9 (55.1)	11400 (50.7)	2.43 (3.91)	2277	10.8	0.577 (0.351)	12.23 (2.41)	181 (83)	70 (21)	30.1 (101.9)
5th(1B) Gear									
92.7 (69.1)	11285 (50.2)	3.08 (4.95)	2203	9.2	0.538 (0.327)	13.11 (2.58)	180 (82)	70 (21)	30.1 (101.9)
6th(2B) Gear									
103.7 (77.3)	11175 (49.7)	3.48 (5.60)	2034	8.9	0.483 (0.294)	14.62 (2.88)	178 (81)	70 (21)	30.1 (101.9)
7th(1C) Gear									
104.3 (77.8)	10880 (48.4)	3.60 (5.79)	1902	7.0	0.486 (0.295)	14.53 (2.86)	178 (81)	66 (19)	30.1 (101.9)
8th(3B) Gear									
104.6 (78.0)	9420 (41.9)	4.16 (6.70)	1911	5.2	0.471 (0.286)	14.99 (2.95)	176 (80)	68 (20)	30.1 (101.9)
9th(2C) Gear									
106.6 (79.5)	8900 (39.6)	4.49 (7.23)	1900	4.7	0.459 (0.279)	15.38 (3.03)	178 (81)	68 (20)	30.1 (101.9)
10th(4B) Gear									
106.2 (79.2)	7710 (34.3)	5.17 (8.31)	1920	4.3	0.479 (0.291)	14.72 (2.90)	176 (80)	72 (22)	30.1 (101.9)
11th(3C) Gear									
104.2 (77.7)	6955 (30.9)	5.62 (9.04)	1921	3.8	0.493 (0.300)	14.31 (2.82)	178 (81)	68 (20)	30.1 (101.9)
12th(4C) Gear									
102.7 (76.6)	5590 (24.9)	6.89 (11.09)	1915	3.2	0.506 (0.308)	13.95 (2.75)	176 (80)	68 (20)	30.1 (101.9)
13th(1D) Gear									
102.9 (76.7)	4310 (19.2)	8.95 (14.41)	1923	2.7	0.498 (0.303)	14.16 (2.79)	176 (80)	68 (20)	30.1 (101.9)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments.

**NOTE:** The test results on this Summary were obtained from tests carried out on the New Holland TS135A Diesel.

**NOTE:** The manufacturer's claim of 115 PTO hp (85.8 kW) was met during the standard PTO speed test.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claims of: 26.5 gpm (100 lpm) remote hydraulic flow nor 3 point lift capacity of 12185 lbs (5527 kg). The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2204** Nebraska Summary 496, December 15, 2005.

Leonard L. Bashford  
 Director

M.F. Kocher  
 V.I. Adamchuk  
 J.A. Smith  
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 7th (1C) gear	72.0	73.0
Bystander	--	--

**TIRES AND WEIGHT**

**Rear tires** - No., size, ply & psi (kPa)  
**Front tires** - No., size, ply & psi (kPa)  
**Height of Drawbar**  
**Static Weight with operator** - Rear  
 - Front  
 - Total

**Tested Without Ballast**

Two 600/65R38; \*\*, 10 (70)  
 Two 480/65R28; \*\*, 10 (70)  
 20.3 in (515 mm)  
 7445 lb (3378 kg)  
 4740 lb (2149 kg)  
 12185 lb (5527 kg)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Disengaged)**  
**FUEL CONSUMPTION CHARACTERISTICS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp. <sup>o</sup> F (°C)	Barom.	
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	cool- ing med	Air dry bulb (kPa)	
<b>Maximum Power—7th(1C)Gear</b>									
91.3 (68.1)	8345 (37.1)	4.10 (6.60)	2200	7.0	0.547 (0.333)	12.89 (2.54)	178 (81)	70 (21)	30.1 (101.8)
<b>75% of Pull at Maximum Power—7th(1C)Gear</b>									
73.4 (54.7)	6250 (27.8)	4.40 (7.08)	2282	3.6	0.591 (0.360)	11.93 (2.35)	180 (82)	70 (21)	30.1 (101.9)
<b>50% of Pull at Maximum Power—7th(1C)Gear</b>									
50.5 (37.7)	4190 (18.6)	4.52 (7.27)	2312	2.4	0.713 (0.433)	9.90 (1.95)	180 (82)	68 (20)	30.1 (101.9)
<b>75% of Pull at Reduced Engine Speed—8th(3B) Gear</b>									
73.5 (54.8)	6250 (27.8)	4.41 (7.09)	2028	4.0	0.511 (0.311)	13.81 (2.72)	176 (80)	73 (23)	30.1 (101.8)
<b>50% of Pull at Reduced Engine Speed—8th(3B) Gear</b>									
50.6 (37.7)	4190 (18.6)	4.53 (7.29)	2055	2.7	0.586 (0.357)	12.03 (2.37)	178 (81)	73 (23)	30.1 (101.8)
<b>MAXIMUM POWER IN SELECTED GEARS</b>									
1st(1A) Gear									
30.0 (22.4)	8565 (38.1)	1.32 (2.12)	2342	12.8	0.915 (0.557)	7.71 (1.52)	181 (83)	75 (24)	30.1 (101.8)
2nd(2A) Gear									
36.2 (27.0)	8510 (37.9)	1.60 (2.57)	2331	13.0	0.817 (0.497)	8.63 (1.70)	183 (84)	73 (23)	30.1 (101.8)
3rd(3A) Gear									
44.5 (33.2)	8475 (37.7)	1.97 (3.17)	2316	11.6	0.755 (0.459)	9.34 (1.84)	183 (84)	75 (24)	30.1 (101.8)
4th(4A) Gear									
54.2 (40.4)	8475 (37.7)	2.40 (3.86)	2304	11.5	0.685 (0.416)	10.30 (2.03)	179 (82)	73 (23)	30.1 (101.8)
5th(1B) Gear									
69.1 (51.5)	8420 (37.5)	3.08 (4.95)	2282	11.0	0.639 (0.389)	11.03 (2.17)	181 (83)	73 (23)	30.1 (101.8)
6th(2B) Gear									
83.0 (61.9)	8375 (37.3)	3.72 (5.98)	2237	10.1	0.594 (0.361)	11.88 (2.34)	181 (83)	73 (23)	30.0 (101.7)
7th(1C) Gear									
91.3 (68.1)	8345 (37.1)	4.10 (6.60)	2200	7.0	0.547 (0.333)	12.89 (2.54)	178 (81)	70 (21)	30.1 (101.8)
8th(3B) Gear									
97.1 (72.4)	8275 (36.8)	4.40 (7.08)	2079	6.5	0.517 (0.314)	13.65 (2.69)	178 (81)	68 (20)	30.1 (101.9)
9th(2C) Gear									
101.8 (75.9)	8210 (36.5)	4.65 (7.48)	2034	6.6	0.487 (0.296)	14.48 (2.85)	178 (81)	68 (20)	30.1 (101.8)
10th(4B) Gear									
104.9 (78.2)	7870 (35.0)	5.00 (8.05)	1916	5.6	0.492 (0.299)	14.33 (2.82)	178 (81)	72 (22)	30.1 (101.9)
11th(3C) Gear									
103.9 (77.5)	7170 (31.9)	5.44 (8.75)	1911	4.8	0.476 (0.289)	14.82 (2.92)	176 (80)	73 (23)	30.1 (101.8)
12th(4C) Gear									
105.8 (78.9)	5875 (26.1)	6.75 (10.87)	1913	3.4	0.484 (0.295)	14.57 (2.87)	178 (81)	70 (21)	30.1 (101.9)
13th(1D) Gear									
106.5 (79.4)	4570 (20.3)	8.74 (14.06)	1907	2.6	0.465 (0.283)	15.18 (2.99)	176 (80)	68 (20)	30.1 (101.9)

This vehicle is equipped with an electronically controlled engine Power management system that monitors and boosts engine power output in certain circumstances. This is achieved by electronically changing the characteristics of the engine power-speed curve. The engine Power management function ("boosted" power level) becomes active in the higher transmission gears (13th and above) and for road transport applications. The system is also activated when power transfer through the PTO exceeds a preset level (and forward speed exceeds 0.5 km/h), for mobile PTO driven implement applications. An override system is provided to enable PTO operations at the "boosted" power level while the vehicle is stationary for test purposes. The results of of this PTO output test are presented below.

### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1037 rpm)</b>					
141.5 (105.5)	2199	8.53 (32.29)	0.425 (0.259)	16.59 (3.27)	
<b>Standard Power Take-off Speed - (1001 rpm)</b>					
145.2 (108.3)	2122	8.53 (32.28)	0.414 (0.252)	17.02 (3.35)	
<b>Maximum Power (2 hours)</b>					
151.5 (113.0)	1900	8.32 (31.48)	0.387 (0.235)	18.22 (3.59)	

### VARYING POWER AND FUEL CONSUMPTION

141.5 (105.5)	2199	8.53 (32.29)	0.425 (0.259)	16.59 (3.27)	Air temperature
122.7 (91.5)	2241	7.42 (28.09)	0.427 (0.259)	16.54 (3.26)	73°F (23°C)
93.6 (69.8)	2278	6.46 (24.45)	0.487 (0.296)	14.48 (2.85)	Relative humidity
63.3 (47.2)	2312	5.05 (19.12)	0.563 (0.342)	12.54 (2.47)	55%
32.2 (24.0)	2352	3.68 (13.92)	0.806 (0.490)	8.75 (1.72)	Barometer
--	2372	2.40 (9.08)	--	--	30.3"Hg (101.7kPa)

Maximum Torque 436.5 lb.-ft. (591.8 Nm) at 1703 rpm  
 Maximum Torque Rise - 29.1%  
 Torque rise at 1750 rpm - 28%

### THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: No

Maximum Force Exerted Through Whole Range: 9530 lbs (42.4 kN)

i) Opening pressure of relief valve:

NA NA

	<u>one outlet set</u>	<u>two outlet sets combined</u>
Sustained pressure at compensator cutoff:	3105 psi (214 bar)	3105 psi (214 bar)

ii) Pump delivery rate at minimum pressure: 24.2 GPM(91.5 l/min) 26.2 GPM(99.0 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 23.6 GPM(89.4 l/min) 25.0 GPM(94.5 l/min)

Delivery pressure: 2540 psi (175 bar) 2610 psi (180 bar)

Power: 35.0 HP (26.1 kW) 38.0 HP (28.3 kW)

### THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi.(bar)	3105 (214)				
Location:	lift cylinder				
Hydraulic oil temperature: °F (°C)	150 (65)				
Location:	hydraulic sump				
Category:	II				
Quick attach:	none				
<b>SAE Static Test</b> —System pressure 2685 psi (185 Bar) (two 90 mm external cylinders)					
Hitch point distance to ground level in.(mm)	7.7 (195)	15.6 (395)	23.0 (585)	30.3 (770)	36.2 (920)
Lift force on frame lb	14500	13510	12970	12455	11240
" " " " " " (kN)	(64.5)	(60.1)	(57.7)	(55.4)	(50.0)

### HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	29.9	760	30.3	770
B	12.2	310	12.2	310
C	15.6	395	15.6	395
D	14.6	370	14.6	370
E	8.2	208	10.8	275
F	9.3	235	9.3	235
G	32.3	820	32.3	820
H	1.1	28	1.1	28
I	17.9	455	16.9	430
J	23.0	585	23.0	585
K	19.8	502	22.8	580
L	46.5	1180	46.5	1180
M	24.6	625	24.6	625
N	39.8	1012	39.8	1012
O	7.7	195	7.7	195
P	47.0	1195	42.0	1068
Q	35.4	900	33.1	840
R	32.3	820	35.0	888

