

January 2004

## Test 2118: New Holland TM140 Diesel

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

---

"Test 2118: New Holland TM140 Diesel" (2004). *Nebraska Tractor Tests*. 284.  
<http://digitalcommons.unl.edu/tractormuseumlit/284>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2118—NEBRASKA SUMMARY 432

## NEW HOLLAND TM140 DIESEL

### 18 SPEED

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1038 rpm)</b>					
119.7 (89.3)	2201	7.81 (29.58)	0.458 (0.279)	15.33 (3.02)	
<b>Standard Power Take-off Speed (1000 rpm)</b>					
120.8 (90.1)	2121	7.67 (29.05)	0.446 (0.271)	15.74 (3.10)	
<b>Maximum Power (2 hours)</b>					
121.1 (90.3)	2061	7.54 (28.54)	0.437 (0.266)	16.04 (3.16)	

#### VARYING POWER AND FUEL CONSUMPTION

119.7 (89.3)	2201	7.81 (29.58)	0.458 (0.279)	15.33 (3.02)	Air temperature
107.5 (80.2)	2324	7.50 (28.40)	0.490 (0.298)	14.31 (2.82)	69°F (21°C)
81.5 (60.7)	2345	6.28 (23.78)	0.541 (0.329)	12.97 (2.55)	Relative humidity
54.4 (40.6)	2350	5.00 (18.93)	0.644 (0.392)	10.90 (2.15)	34%
27.4 (20.4)	2368	3.67 (13.90)	0.943 (0.574)	7.44 (1.47)	Barometer
--	2382	2.43 (9.19)	--	--	30.2" Hg (102.2 kPa)

Maximum Torque - 419.4 lb.-ft. (568.6 Nm) at 1350 rpm  
 Maximum Torque Rise - 51.3%  
 Torque rise at 1800 engine rpm - 22%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged)

#### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F (°C) cool- ing med	Barom. inch Hg (kPa)
<b>Maximum Power—9th(3B) Gear</b>							
101.2 (75.5)	7485 (33.3)	5.07 (8.16)	2199	3.3	0.541 (0.329)	9.97 (2.55)	198 (92)
<b>75% of Pull at Maximum Power—9th(3B) Gear</b>							
81.1 (60.5)	5630 (25.1)	5.40 (8.69)	2325	2.6	0.593 (0.361)	11.83 (2.33)	201 (94)
<b>50% of Pull at Maximum Power—9th(3B) Gear</b>							
54.8 (40.9)	3755 (16.7)	5.47 (8.81)	2341	1.9	0.704 (0.428)	9.97 (1.96)	201 (94)
<b>75% of Pull at Reduced Engine Speed—10th(4B) Gear</b>							
81.1 (60.5)	5645 (25.1)	5.39 (8.68)	1933	2.6	0.524 (0.319)	13.40 (2.64)	203 (95)
<b>50% of Pull at Reduced Engine Speed—10th(4B) Gear</b>							
54.7 (40.8)	3750 (16.7)	5.47 (8.81)	1946	1.9	0.600 (0.365)	11.70 (2.31)	199 (93)

**Location of Test:** Silsoe Research Institute, Wrest Park, Silsoe, MK45 4HS, United Kingdom

**Dates of Test:** December 2002 to January 2004.

**Manufacturer:** CNH U.K. Ltd., Basildon, Essex, SS14 3AD, England

**FUEL and OIL:** Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.843 Fuel weight 7.02 lbs/gal (0.8413 kg/l) Oil SAE 10W30 API service classification CG-4 Transmission and hydraulic lubricant New Holland 134D fluid Front axle lubricant New Holland 134D fluid

**ENGINE:** Make CNH Diesel Type six cylinder vertical with turbocharger and air to air intercooler Serial No. 957504 Crankshaft lengthwise Rated engine speed 2200 Bore and stroke 4.40" x 5.00" (111.8 mm x 127.0 mm) Compression ratio 17.0 to 1 Displacement 456 cu in (7480 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements and aspirator Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler underhood Exhaust vertical Cooling medium temperature control thermostat and variable speed fan

**CHASSIS:** Type front wheel assist Serial No. 170899B Tread width rear 60.2" (1530 mm) to 87.8" (2230 mm) front 61.4" (1560 mm) to 89.0" (2260 mm) Wheelbase 107.2" (2723 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio with partial (6) range operator controlled powershift Nominal travel speeds mph (km/h) first 1.53 (2.46) second 1.84 (2.96) third 2.21 (3.56) fourth 2.66 (4.28) fifth 3.19 (5.14) sixth 3.55 (5.72) seventh 3.85 (6.19) eighth 4.28 (6.88) ninth 5.14 (8.27) tenth 6.18 (9.94) eleventh 7.43 (11.96) twelfth 8.94 (14.38) thirteenth 10.09 (16.24) fourteenth 12.13 (19.52) fifteenth 14.58 (23.46) sixteenth 17.52 (28.20) seventeenth 21.08 (33.93) eighteenth 25.35 (40.80) reverse 2.98 (4.80), 3.59 (5.78), 4.31 (6.94), 5.19 (8.35), 6.24 (10.05), 7.51 (12.08) Clutch multiple wet disc electro-hydraulically operated by foot pedal Brakes wet disc hydraulically operated by two foot pedals that can be locked together Steering hydrostatic Power take-off 540 rpm at 1969 engine rpm or 1000 rpm at 2120 engine rpm Unladen tractor mass 12935 lb (5868 kg)

## DRAWBAR PERFORMANCE

### (Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. <sup>o</sup> F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
1st(1A) Gear									
52.6 (39.2)	13895 (61.8)	1.42 (2.28)	2342	14.7	0.777 (0.473)	9.04 (1.78)	190 (88)	57 (14)	30.2 (102.2)
2nd(2A) Gear									
63.2 (47.1)	13760 (61.2)	1.72 (2.77)	2342	13.9	0.712 (0.433)	9.86 (1.94)	196 (91)	59 (15)	30.2 (102.2)
3rd(3A) Gear									
76.4 (57.0)	13545 (60.2)	2.11 (3.40)	2326	11.4	0.621 (0.378)	11.31 (2.23)	194 (90)	55 (13)	30.2 (102.2)
4th(4A) Gear									
90.5 (67.5)	13420 (59.7)	2.53 (4.07)	2290	10.5	0.598 (0.364)	11.73 (2.31)	192 (89)	55 (13)	30.2 (102.2)
5th(5A) Gear									
99.0 (73.8)	12725 (56.6)	2.92 (4.70)	2143	8.2	0.548 (0.333)	12.81 (2.52)	199 (93)	55 (13)	30.2 (102.2)
6th(1B) Gear									
100.7 (75.1)	11870 (52.8)	3.18 (5.12)	2060	6.4	0.534 (0.325)	13.15 (2.59)	198 (92)	55 (13)	30.2 (102.2)
7th(6A) Gear									
101.1 (75.4)	10880 (48.4)	3.48 (5.61)	2065	5.4	0.518 (0.315)	13.55 (2.67)	196 (91)	55 (13)	30.2 (102.2)
8th(2B) Gear									
102.6 (76.5)	9845 (43.8)	3.91 (6.29)	2063	4.6	0.512 (0.311)	13.72 (2.70)	198 (92)	50 (10)	30.1 (101.9)
9th(3B) Gear									
102.7 (76.6)	8125 (36.1)	4.74 (7.63)	2062	3.6	0.518 (0.315)	13.55 (2.67)	198 (92)	50 (10)	30.1 (101.9)
10th(4B) Gear									
102.3 (76.3)	6700 (29.8)	5.73 (9.22)	2059	2.9	0.520 (0.316)	13.50 (2.66)	199 (93)	52 (11)	30.1 (101.9)
11th(5B) Gear									
101.7 (75.8)	5515 (24.5)	6.92 (11.13)	2055	2.4	0.520 (0.316)	13.50 (2.66)	190 (88)	52 (11)	30.1 (101.9)
12th(6B) Gear									
98.0 (73.1)	4385 (19.5)	8.38 (13.48)	2064	2.1	0.522 (0.317)	13.45 (2.65)	199 (93)	61 (16)	30.1 (101.9)
13th(1C) Gear									
99.8 (74.4)	3950 (17.6)	9.47 (15.24)	2061	1.9	0.532 (0.324)	13.20 (2.60)	203 (95)	63 (17)	30.1 (101.9)

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 8th (2B) gear	75.0	75.0
Bystander	--	--

### TIRES AND WEIGHT

**Rear tires** - No., size, ply & psi (kPa)

**Front tires** - No., size, ply & psi (kPa)

**Height of Drawbar**

**Static Weight with operator**- Rear

- Front

- Total

### Tested Without Ballast

Two 20.8R38; \*\*,13 (90)

Two 16.9R28; \*\*,13 (90)

21.5 in (545 mm)

8080 lb (3665 kg)

5020 lb (2278 kg)

13100 lb (5943 kg)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The standard capacity 3 point lift claim of 9755 lbs (4425 kg) was not tested for verification. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2118** Nebraska Summary 432, September 17, 2004.

Leonard L. Bashford  
Director

M.F. Kocher  
V.I. Adamchuk  
W.P. Campbell  
Board of Tractor Test Engineers

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Disengaged)**  
**FUEL CONSUMPTION CHARACTERISTICS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—9th (3B) Gear</b>									
99.1 (73.9)	7510 (33.4)	4.95 (7.97)	2198	4.5	0.547 (0.333)	12.84 (2.53)	196 (91)	53 (11)	29.8 (101.0)
<b>75% of Pull at Maximum Power—9th (3B) Gear</b>									
79.8 (59.5)	5620 (25.0)	5.32 (8.57)	2330	3.1	0.604 (0.367)	11.62 (2.29)	199 (93)	50 (10)	29.8 (101.0)
<b>50% of Pull at Maximum Power—9th (3B) Gear</b>									
54.2 (40.4)	3755 (16.7)	5.41 (8.70)	2345	2.2	0.735 (0.447)	9.55 (1.88)	198 (92)	50 (10)	29.8 (101.0)
<b>75% of Pull at Reduced Engine Speed—10th (4B) Gear</b>									
79.5 (59.3)	5610 (25.0)	5.31 (8.55)	1935	3.1	0.538 (0.328)	13.05 (2.57)	194 (90)	54 (12)	29.8 (100.8)
<b>50% of Pull at Reduced Engine Speed—10th (4B) Gear</b>									
54.0 (40.3)	3755 (16.7)	5.40 (8.69)	1948	2.2	0.612 (0.372)	11.47 (2.26)	194 (90)	54 (12)	29.8 (100.8)
<b>MAXIMUM POWER IN SELECTED GEARS</b>									
1st(1A) Gear									
42.0 (31.3)	11105 (49.4)	1.42 (2.28)	2349	14.2	0.828 (0.504)	8.48 (1.67)	194 (90)	55 (13)	29.8 (100.8)
2nd(2A) Gear									
49.9 (37.2)	10880 (48.4)	1.72 (2.77)	2345	13.2	0.780 (0.474)	9.00 (1.77)	194 (90)	54 (12)	29.8 (100.8)
3rd(3A) Gear									
60.2 (44.9)	10905 (48.5)	2.07 (3.33)	2343	12.9	0.702 (0.427)	10.00 (1.97)	193 (89)	54 (12)	29.8 (100.8)
4th(4A) Gear									
71.5 (53.3)	10580 (47.1)	2.54 (4.08)	2335	11.1	0.662 (0.403)	10.61 (2.09)	194 (90)	54 (12)	29.8 (100.8)
5th(5A) Gear									
84.8 (63.2)	10465 (46.6)	3.04 (4.89)	2321	10.9	0.641 (0.390)	10.97 (2.16)	195 (91)	55 (13)	29.8 (100.8)
6th(1B) Gear									
92.9 (69.3)	10110 (45.0)	3.45 (5.55)	2293	7.8	0.584 (0.355)	12.03 (2.37)	195 (91)	50 (10)	29.8 (100.9)
7th(6A) Gear									
96.2 (71.7)	10025 (44.6)	3.60 (5.79)	2192	7.1	0.560 (0.341)	12.54 (2.47)	194 (90)	53 (12)	29.7 (100.5)
8th(2B) Gear									
99.4 (74.1)	9520 (42.3)	3.91 (6.30)	2135	6.6	0.539 (0.328)	13.03 (2.57)	195 (91)	50 (10)	29.8 (100.9)
9th(3B) Gear									
101.8 (75.9)	8275 (36.8)	4.61 (7.42)	2057	4.9	0.515 (0.313)	13.62 (2.68)	201 (94)	53 (12)	29.7 (100.7)
10th(4B) Gear									
101.1 (75.4)	6745 (30.0)	5.62 (9.05)	2062	3.7	0.522 (0.318)	13.44 (2.65)	197 (92)	50 (10)	29.8 (101.0)
11th(5B) Gear									
101.1 (75.4)	5585 (24.8)	6.79 (10.93)	2054	3.0	0.528 (0.321)	13.30 (2.62)	196 (91)	50 (10)	29.8 (101.0)
12th(6B) Gear									
98.8 (73.7)	4500 (20.0)	8.23 (13.24)	2056	2.5	0.530 (0.322)	13.25 (2.61)	197 (92)	53 (12)	29.8 (101.0)
13th(1C) Gear									
101.6 (75.8)	4090 (18.2)	9.32 (15.00)	2060	2.3	0.518 (0.315)	13.55 (2.67)	199 (93)	55 (13)	29.8 (101.0)

### THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum Force Exerted

Through Whole Range: 7485 lbs (33.3 kN) (one boost cylinder)  
9015 lbs (40.1 kN) (two boost cylinders)

- i) Opening pressure of relief valve: NA
- Sustained pressure of the open relief valve: 2960 psi (204 bar)
- ii) Pump delivery rate at minimum pressure: 32.1 GPM (121.5 l/min)
- iii) Pump delivery rate at maximum
  - hydraulic power: 29.3 GPM (110.8 l/min)
  - Delivery pressure: 2395 psi (165 bar)
  - Power: 40.9 HP (30.5 kW)

### THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi.(bar)	2960 (204)
Location:	lift cylinder
Hydraulic oil temperature: °F (°C)	150 (65)
Location:	hydraulic sump
Category:	II
Quick attach:	none

#### SAE Static Test—System pressure 2610 psi (180 Bar) (one boost cylinder)

Hitch point distance to ground level in. (mm)	8.0 (203)	15.7 (400)	22.4 (570)	29.7 (755)	37.0 (940)
Lift force on frame lb	13490	14075	14095	13890	12295
" " " " " " (kN)	(60.0)	(62.6)	(62.7)	(61.8)	(54.7)

#### SAE Static Test—System pressure 2610 psi (180 Bar) (two boost cylinders)

Hitch point distance to ground level in. (mm)	9.5 (240)	15.4 (390)	23.8 (605)	31.5 (800)	39.6 (1005)
Lift force on frame lb	16525	17285	17760	17420	16545
" " " " " " (kN)	(73.5)	(76.9)	(79.0)	(77.5)	(73.6)

### HITCH DIMENSIONS AS TESTED—NO LOAD (2 boost cylinders)

	OECD test		SAE test	
	inch	mm	inch	mm
A	29.7	754	29.9	760
B	9.1	230	9.1	230
C	15.6	395	15.6	395
D	14.3	363	14.3	363
E	8.2	208	10.8	275
F	9.8	250	9.8	250
G	33.6	855	33.6	855
H	0.7	17	0.7	17
I	17.9	455	16.9	430
J	23.8	605	23.8	605
K	17.1	435	19.8	504
L	47.0	1194	47.0	1194
M	23.3	592	23.3	592
N	38.3	974	38.3	974
O	7.8	198	9.4	240
P	47.8	1215	43.9	1115
Q	36.3	923	35.0	890
R	29.5	750	31.0	787

