

*Tractor Test and Power Museum, The Lester F. Larsen*

*UNL Larsen Tractor Museum Archives*

---

University of Nebraska - Lincoln

Year 1970

---

Test 1047: International Farmall 1026  
Hydrostatic Diesel (Also International  
1026 Hydrostatic Diesel)

Tractor Museum  
University of Nebraska-Lincoln, [TractorMuseumArchives@unl.edu](mailto:TractorMuseumArchives@unl.edu)

# NEBRASKA TRACTOR TEST 1047-INTERNATIONAL FARMALL 1026

## HYDROSTATIC DIESEL

### (ALSO INTERNATIONAL 1026 HYDROSTATIC DIESEL)

#### POWER TAKE-OFF PERFORMANCE

Hp	Crankshaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>								
<b>Rated Engine Speed—Two Hours (PTO Speed—1159 rpm)</b>								
112.45	2400	7.865	0.485	14.30	190	65	75	28.983
<b>Standard Power Take-off Speed (1000 rpm)—One Hour</b>								
110.71	2071	7.107	0.445	15.58	192	66	75	28.885
<b>VARYING POWER AND FUEL CONSUMPTION—TWO HOURS</b>								
100.34	2523	7.610	0.526	13.19	186	65	75	.....
0.00	2645	3.200	.....	.....	166	65	75	.....
51.61	2595	5.500	0.739	9.38	178	65	75	.....
114.47	2400	7.961	0.482	14.38	189	65	75	.....
26.19	2618	4.398	1.165	5.955	173	65	75	.....
76.61	2563	6.577	0.596	11.65	180	65	75	.....
Av 61.54	2557	5.874	0.662	10.48	179	65	75	28.900

#### DRAWBAR PERFORMANCE

Hp	Draw-bar pull lbs	Speed miles per hr	Crankshaft speed rpm	Slip of drivers %	Fuel Consumption		Hp-hr per gal	Temp Degrees F			Barometer inches of Mercury	
					Gal per hr	Lb per hp-hr		Cooling med	Air wet bulb	Air dry bulb		
<b>VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST</b>												
<b>Maximum Available Power—Two Hours—Speed Setting—5.4 MPH Hi Range</b>												
80.24	5605	5.37	2402	5.71	7.824	0.676	10.26	189	73	78	28.655	
<b>75% of Pull at Maximum Power—Ten Hours—Speed Setting—5.4 MPH Hi Range</b>												
70.67	4351	6.09	2529	3.91	7.356	0.722	9.61	181	67	77	29.050	
<b>50% of Pull at Maximum Power—Two Hours—Speed Setting—5.4 MPH Hi Range</b>												
51.33	2945	6.54	2562	2.72	6.137	0.830	8.36	180	75	91	28.680	
<b>MAXIMUM POWER WITH BALLAST</b>												
79.42	9583	3.11	2396	10.91	The infinitely variable drive control		Lo Range	180	71	82	28.740	
80.52	7536	4.01	2399	7.89	variable		Lo Range	185	71	81	28.740	
80.95	6702	4.53	2403	6.88	drive control		Lo Range	184	71	83	28.740	
80.13	5960	5.04	2400	5.86	was set		Lo Range	180	71	82	28.740	
83.94	5812	5.42	2400	6.01	to give the		Hi Range	183	67	77	28.740	
84.34	4751	6.66	2403	4.73	travel speeds		Hi Range	182	68	78	28.740	
83.68	4057	7.74	2403	4.20	shown by the		Hi Range	182	68	78	28.740	
79.72	2665	11.22	2401	2.72	manufacturer		Hi Range	182	67	76	28.740	
<b>MAXIMUM PULL WITHOUT BALLAST</b>												
79.96	8717	3.44	2394	14.97	Speed—3.4 MPH		Lo Range	180	66	80	28.940	
<b>VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST</b>												
<b>Speed 5.4 MPH Hi Range</b>												
Pounds Pull				5812	5837	6440	6831	7048	7067			
Horsepower				83.94	83.66	81.38	75.39	67.30	56.00			
Crankshaft Speed rpm				2400	2394	2157	1910	1672	1437			
Miles Per Hour				5.42	5.38	4.74	4.14	3.58	2.97			
Slip of Drivers %				6.01	5.71	6.30	6.74	7.17	7.32			
<b>TIRES, BALLAST and WEIGHT</b>												
<b>Rear tires</b>				<b>With Ballast</b>				<b>Without Ballast</b>				
Ballast				—No, size, ply & psi				Two 18.4-38; 8; 20				
				—Liquid				Two 18.4-38; 8; 16				
				Cast iron				None				
								None				
								None				
<b>Front tires</b>				—No, size, ply & psi				Two 11L-15; 6; 28				
Ballast				—Liquid				Two 11L-15; 6; 28				
				Cast iron				None				
								None				
								None				
<b>Height of drawbar</b>				28 inches				28½ inches				
<b>Static weight with operator—Rear</b>				11790 lb				7960 lb				
				Front				3185 lb				
				Total				14975 lb				
								11100 lb				

#### Department of Agricultural Engineering

Dates of Test: June 3 to June 27, 1970

Manufacturer: INTERNATIONAL HARVESTER COMPANY, CHICAGO, ILLINOIS

FUEL, OIL and TIME Fuel No 2 Diesel Cetane No 50.8 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.8332 Weight per gallon 6.938 lb Oil SAE 30 API service classification MS DG DM DS To motor 3.181 gal Drained from motor 2.340 gal Transmission and final-drive lubricant IH Hy-Tran fluid Total time engine was operated 59 hours.

ENGINE Make International Diesel Type 6 cylinder vertical with turbo-charger Serial No 407T12U037197 Crankshaft mounted lengthwise Rated rpm 2400 Bore and stroke 4.321" x 4.625" Compression ratio 16 to 1 Displacement 407 cu in Cranking system 12 volt electric Lubrication pressure Air cleaner two stage dry type using replaceable pleated paper elements and automatic dust unloader Oil filter full flow with two replaceable treated paper elements Oil cooler engine coolant heat exchanger for engine oil and radiator for transmission and hydraulic oil Fuel filter one primary and one final using replaceable screw-on cartridges Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type Standard Serial No 2610130-U007534 Tread width rear 60" to 94" front 54" to 78" (and 60" to 84"—2 different axles) Wheel base 104.8" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 30.3" Vertical distance above roadway 40.3" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission infinitely variable hydrostatic using a variable displacement pump and motor. A range transmission provides Hi and Lo range Advertised speeds mph forward 0-17 Hi range; 0-7½ Lo range reverse 0-7 Hi range; 0-3 Lo range Clutch none—hydrostatic drive can be controlled by foot pedal Brakes dry disc hydraulically power actuated by two foot pedals which can be locked together with automatic equalizing Steering hydrostatic power Turning radius (on concrete surface with brake applied) right 144" left 144" (on concrete surface without brake) right 167" left 167" Turning space diameter (on concrete surface with brake applied) right 298" left 298" (on concrete surface without brake) right 344" left 344" Power take-off 539 or 1014 rpm at 2100 engine rpm.

REPAIRS and ADJUSTMENTS: During preliminary drawbar runs the Range Transmission Main Shaft Front Bearing and the Forward Drive Pressure Line were replaced.

REMARKS: All test results were determined from observed data obtained in accordance with the SAE and ASAE test code. The slower travel speeds were not run as the maximum drawbar pull was limited by the stability formula. The other travel speeds were not run as test procedure requires only eight travel speeds. During the VARYING DRAWBAR PULL VERSUS TRAVEL SPEED run the transmission warning light became illuminated at an engine speed of approximately 1200 RPM and the run was discontinued in accordance with the manufacturer's operating instructions. The Operators Manual reads: "This condition (lighting of Tellite) must be corrected before continued operation. If operating in "Hi" range, shift into "Lo" or pull back on the speed ratio control lever."

We, the undersigned, certify that this is a true and correct report of official Tractor Test 1047.

L. F. LARSEN

Engineer-in-Charge

G. W. STEINBRUEGGE

W. E. SPLINTER

D. E. LANE

Board of Tractor Test Engineers

The University of Nebraska Agricultural Experiment Station  
E. F. Frolik, Dean; H. W. Ottoson, Director; Lincoln, Nebraska