

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

5-31-1950

Test 441: McCormick-Deering WD-9

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 441: McCormick-Deering WD-9" (1950). *Nebraska Tractor Tests*. 139.
<https://digitalcommons.unl.edu/tractormuseumlit/139>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Department of Agricultural Engineering
 Dates of test: May 31 to June 7, 1950.
 Manufacturer: INTERNATIONAL HARVESTER
 COMPANY, CHICAGO, ILLINOIS
 Manufacturer's rating: Not rated.

The Experiment Station
 University of Nebraska College of Agriculture
 W. V. Lambert, Director, Lincoln, Nebraska

NEBRASKA TRACTOR TEST NO. 441

McCORMICK-DEERING WD-9

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer in Hg
		Gal per hour	Hp-hr per gal	Lb per hp-hour		Cooling med	Air	
* TESTS B and C—100% MAXIMUM LOAD—TWO HOURS								
51.27	1500	3.508	14.62	0.478	0.02	175	64	28.920
TEST D—RATED LOAD—ONE HOUR								
45.36	1501	3.153	14.39	0.486	0.02	168	62	28.920
TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average)								
45.17	1496	3.130	14.43	0.484	...	168	61
1.35	1577	1.176	1.15	6.089	...	154	60
23.67	1561	2.112	11.21	0.624	...	158	60
49.43	1457	3.357	14.72	0.475	...	170	60
11.87	1564	1.614	7.35	0.950	...	156	62
34.45	1518	2.580	13.35	0.523	...	160	60
27.66	1529	2.328	11.88	0.588	0.01	161	61	28.925

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lb	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer in Hg
					Gal per hour	Hp-hr per gal	Lb per hp-hr		Cool- ing med	Air	
TESTS F and G—100% MAXIMUM LOAD											
36.20	6727	2.02	1503	16.64	Not Recorded				169	71	28.765
43.87	5655	2.91	1504	10.85	" "				175	77	28.775
46.02	4018	4.30	1504	6.54	" "				175	73	28.775
46.83	3315	5.30	1500	5.15	" "				175	73	28.775
39.95	944	15.87	1500	1.44	" "				172	80	28.775
TEST H—RATED LOAD—TEN HOURS—3rd GEAR											
36.61	3147	4.36	1498	4.70	2.847	12.86	0.543	0.00	174	84	28.760
TEST J—OPERATING MAXIMUM LOAD—3rd GEAR											
41.34	3821	4.06	1501	13.40	Not Recorded				170	72	28.775

FUEL, OIL and TIME Diesel Fuel cetane No 47 (rating taken from oil company's typical inspection data); weight per gallon 6.988 lb Oil SAE 20; to motor 2.677 gal; drained from motor 2.188 gal Total time motor was operated 45½ hours.

CHASSIS Type standard Serial No WDCB42216-W12B Tread width rear 60" front 52" Wheel Base 83½" Hydraulic control system not available Advertised speeds mph first 2½ second 3¼ third 4¼ fourth 5½ fifth 16¼ reverse 3 Belt pulley diam 14" face 8½" rpm 707 Belt speed 2593 fpm Clutch single plate dry Seat pressed steel with canvas covered felt pad Brakes external contracting bands operated by right foot on adjacent pedals either independently or interlocked Equalized by springs when pedals are locked together Power take-off standard type.

ENGINE Make McCormick-Deering Type 4 cylinder vertical diesel Serial No WDCBM18744 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and Stroke 4.4" x 5.5" Rated rpm 1500 Compression ratio 15.7-1 Displacement 334.5 cu in Port Diameter Valves inlet 1 21/32" exhaust 1 15/32" Governor variable speed centrifugal Carburetor Size ¾" (for starting only) Ignition System magneto (for starting only) Starter 12 volt Air Cleaner oil washed wire screen Muffler used Oil Filter partial flow replaceable element Cooling medium temperature control thermostat.

REPAIRS AND ADJUSTMENTS Starting control rod bell crank seized on shaft during preliminary belt test. This was corrected and test continued.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with fuel pumps set by the manufacturer to develop approximately 51 observed belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H and J were made with the same setting.

TIRES, WHEELS and WEIGHT

	Tests F, G & H	Test J	Test K
Rear wheels			
Type	Cast iron	Cast iron	
Liquid ballast	952 lb each	None	
Added cast iron	930 lb each	None	
Rear tires			
No. and size	Two 14-34	Two 14-34	
Ply	6	6	
Air pressure	16 lb	12 lb	
Front wheels			
Type	Cast iron	Cast iron	
Liquid ballast	None	None	
Added cast iron	None	None	
Front tires			
No. and size	Two 7.50-18	Two 7.50-18	
Ply	6	6	
Air pressure	28 lb	28 lb	
Height of drawbar	19 inches	21 inches	
Static weight			
Rear end	8014 lb	4250 lb	
Front end	2786 lb	2786 lb	
Total weight as tested with operator	10,985 lb	7221 lb	

No smaller tires suggested by manufacturer.

HORSEPOWER SUMMARY

	Draw- bar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg)	48.45	53.24
2. Observed maximum horsepower (tests F and B)	46.02	51.27
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings)	36.34	45.25

We, the undersigned, certify that this is a true and correct report of official tractor test No. 441.

L. F. Larsen
 Engineer in Charge

C. W. Smith
 L. W. Hurlbut
 F. D. Yung
 Board of Tractor
 Test Engineers

