

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 2004

Nebraska Summary 477: AGCO RT120 PowrMaxx Diesel

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

"Nebraska Summary 477: AGCO RT120 PowrMaxx Diesel" (2004). *Nebraska Tractor Tests*. 153.
<https://digitalcommons.unl.edu/tractormuseumlit/153>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2235–NEBRASKA SUMMARY 477

AGCO RT 120 POWRMAXX DIESEL

CONTINUOUSLY VARIABLE TRANSMISSION

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1081 rpm)					
119.9 (89.4)	2199	8.12 (30.72)	0.473 (0.288)	14.77 (2.91)	
Maximum Power (2 hours)					
122.2 (91.1)	2150	7.96 (30.13)	0.455 (0.277)	15.34 (3.02)	
Standard Power Take-off Speed(1000 rpm)					
120.6 (89.9)	2034	7.60 (28.76)	0.440 (0.268)	15.87 (3.13)	

VARYING POWER AND FUEL CONSUMPTION					
119.9 (89.4)	2199	8.12 (30.72)	0.473 (0.288)	14.77 (2.91)	Air temperature
104.3 (77.8)	2250	7.42 (28.06)	0.497 (0.302)	14.06 (2.77)	72°F (22°C)
79.1 (59.0)	2278	6.29 (23.79)	0.556 (0.338)	12.58 (2.48)	Relative humidity
54.3 (40.5)	2335	5.13 (19.43)	0.662 (0.402)	10.57 (2.08)	72%
27.6 (20.6)	2382	3.97 (15.03)	1.004 (0.611)	6.96 (1.37)	Barometer
--	2441	2.46 (9.32)	--	--	29.4" Hg (99.4 kPa)

Maximum Torque - 408 lb.-ft. (553 Nm) at 1300 rpm
 Maximum Torque Rise - 42.5%
 Torque rise at 1800 engine rpm - 18%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle									
100.3 (74.8)	7735 (34.40)	4.86 (7.83)	2202	3.4	0.565 (0.343)	12.39 (2.44)	151 (66)	70 (21)	29.5 (99.8)
75% of Pull at Maximum Power—Turtle									
78.2 (58.3)	5780 (25.71)	5.07 (8.17)	2268	2.6	0.632 (0.384)	11.07 (2.18)	149 (65)	72 (22)	29.5 (99.7)
50% of Pull at Maximum Power—Turtle									
53.8 (40.1)	3845 (17.10)	5.25 (8.44)	2314	1.8	0.758 (0.461)	9.23 (1.82)	149 (65)	72 (22)	29.5 (99.7)
75% of Pull at Reduced Engine Speed—Turtle									
77.9 (58.1)	5785 (25.73)	5.05 (8.13)	1962	2.6	0.538 (0.328)	12.98 (2.56)	153 (67)	70 (21)	29.5 (99.7)
50% of Pull at Reduced Engine Speed—Turtle									
54.2 (40.4)	3845 (17.11)	5.29 (8.51)	2025	1.8	0.641 (0.390)	10.91 (2.15)	154 (68)	70 (20)	29.5 (99.7)

Location of tests: DLG testing station for Agricultural Machinery, Max - Eyth - Weg 1 D-64823, Gros-Umstadt, Germany

Dates of tests: April - June, 2004

Manufacturer: AGCO S.A., BP307, Avenue Blaise Pascal, 60026 Beauvais, France

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60° F (15°/15°C)** 0.839 **Fuel weight** 6.99 lbs/gal (0.8379 kg/l) **Oil SAE 10W40 API service classification** CH4 **Transmission and hydraulic lubricant** SAE10W/40 **Front axle lubricant** SAE 85W/90 gear oil

ENGINE: Make Cummins **Diesel Type** six cylinder vertical with turbocharger and air to air intercooler **Serial No.** 21600364 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.094" x 5.197" (104.0 mm x 132.0 mm) **Compression ratio** 17.5 to 1 **Displacement** 410 cu in (6728 ml) **Starting system** 12 volt **Lubrication pressure** **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and final drive oil, radiator for transmission oil **Fuel filter** one paper element **Muffler** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: Type front wheel assist **Serial No.** N119001 **Tread width** rear 69.3" (1760 mm) to 119.1" (3026 mm) front 63.4" (1610 mm) to 72.6" (1844 mm) **Wheelbase** 109.4" (2780 mm) **Hydraulic control system** direct engine drive **Transmission** AGCO CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. **Nominal travel speeds mph (km/h)** forward: Low range 0 - 17 (0 - 28), high range 0 - 25 (0 - 40) reverse: Low range 0 - 10 (0 - 16), high range 0 - 24 (0 - 38) **Clutch** a foot pedal controls the hydrostatic oil flow **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2062 engine rpm or 1000 rpm at 2033 engine rpm **Unladen tractor mass** 15055 lb (6830 kg)

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged)

MAXIMUM POWER AT SELECTED SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp.°F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
86.1 (64.2)	14235 (63.32)	2.27 (3.65)	2239	14.9	Turtle 0.638 (0.388)	10.96 (2.16)	147 (64)	72 (22)	29.4 (99.7)
96.7 (72.1)	13100 (58.28)	2.77 (4.45)	2152	9.8	Turtle 0.574 (0.349)	12.18 (2.40)	149 (65)	68 (20)	29.4 (99.7)
100.3 (74.8)	11535 (51.31)	3.26 (5.25)	2156	6.2	Turtle 0.558 (0.339)	12.54 (2.47)	147 (64)	68 (20)	29.4 (99.6)
100.3 (74.8)	10610 (47.20)	3.54 (5.70)	2156	5.1	Turtle 0.553 (0.337)	12.64 (2.49)	147 (64)	66 (19)	29.4 (99.6)
101.0 (75.3)	8940 (39.76)	4.24 (6.82)	2151	4.0	Turtle 0.556 (0.338)	12.59 (2.48)	147 (64)	66 (19)	29.4 (99.6)
101.5 (75.7)	7875 (35.02)	4.83 (7.78)	2151	3.3	Turtle 0.556 (0.338)	12.59 (2.48)	149 (65)	66 (19)	29.3 (99.2)
100.0 (74.6)	6735 (29.95)	5.57 (8.96)	2151	2.9	Turtle 0.558 (0.339)	12.54 (2.47)	151 (66)	68 (20)	29.3 (99.2)
98.8 (73.7)	5840 (25.97)	6.35 (10.22)	2150	2.5	Turtle 0.562 (0.342)	12.44 (2.45)	153 (67)	68 (20)	29.3 (99.2)
98.8 (73.7)	5255 (23.37)	7.05 (11.34)	2152	2.1	Turtle 0.562 (0.342)	12.44 (2.45)	154 (68)	68 (20)	29.3 (99.2)
97.2 (72.5)	4475 (19.90)	8.15 (13.12)	2154	1.8	Turtle 0.571 (0.347)	12.24 (2.41)	156 (69)	68 (20)	29.3 (99.2)
95.5 (71.2)	3795 (16.88)	9.44 (15.19)	2150	1.4	Turtle 0.581 (0.353)	12.04 (2.37)	156 (69)	66 (19)	29.3 (99.2)
93.4 (69.7)	3280 (14.60)	10.68 (17.18)	2154	1.1	Turtle 0.593 (0.361)	11.78 (2.32)	154 (68)	68 (20)	29.3 (99.2)
97.0 (72.3)	6235 (27.73)	5.83 (9.39)	2151	2.8	Rabbit 0.572 (0.348)	12.23 (2.41)	154 (68)	68 (20)	29.4 (99.6)
99.6 (74.3)	5845 (26.00)	6.39 (10.28)	2150	2.6	Rabbit 0.558 (0.339)	12.54 (2.47)	156 (69)	66 (19)	29.4 (99.6)
99.9 (74.5)	5135 (22.83)	7.30 (11.75)	2152	2.3	Rabbit 0.556 (0.338)	12.59 (2.48)	156 (69)	64 (18)	29.4 (99.6)
99.6 (74.3)	4605 (20.49)	8.10 (13.04)	2150	2.0	Rabbit 0.558 (0.340)	12.53 (2.47)	156 (69)	64 (18)	29.4 (99.6)
98.7 (73.6)	4050 (18.02)	9.14 (14.71)	2153	1.7	Rabbit 0.565 (0.343)	12.39 (2.44)	156 (69)	64 (18)	29.4 (99.6)
97.2 (72.5)	3635 (16.17)	10.03 (16.14)	2156	1.4	Rabbit 0.571 (0.347)	12.24 (2.41)	158 (70)	66 (19)	29.4 (99.7)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 71 dB(A) cab sound level. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2235**, Nebraska Summary 477, January 17, 2006.

Leonard L. Bashford
Director

M.F. Kocher
V.I. Adamchuk
J.A. Smith
Board of Tractor Test Engineers

DRAWBAR PERFORMANCE
(Ballasted - Front Drive Engaged)
FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp.°F cool- ing med	°C Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle									
98.2 (73.2)	6635 (29.52)	5.55 (8.93)	2204	2.5	0.572 (0.348)	12.23 (2.41)	153 (67)	81 (27)	29.4 (99.7)
75% of Pull at Maximum Power—Turtle									
76.3 (56.9)	4950 (22.02)	5.78 (9.31)	2271	1.9	0.643 (0.391)	10.87 (2.14)	156 (69)	81 (27)	29.4 (99.7)
50% of Pull at Maximum Power—Turtle									
52.6 (39.2)	3280 (14.60)	6.01 (9.67)	2314	1.2	0.767 (0.467)	9.12 (1.80)	154 (68)	81 (27)	29.4 (99.7)
75% of Pull at Reduced Engine Speed—Turtle									
76.8 (57.3)	4955 (22.03)	5.82 (9.36)	2003	1.9	0.568 (0.346)	12.31 (2.43)	153 (67)	79 (26)	29.4 (99.7)
50% of Pull at Reduced Engine Speed—Turtle									
52.5 (39.1)	3275 (14.57)	6.01 (9.67)	2040	1.1	0.662 (0.402)	10.57 (2.08)	153 (67)	77 (25)	29.4 (99.7)

TRACTOR SOUND LEVEL WITH CAB	Front wheel drive	
	Engaged dB(A)	Disengaged dB(A)
At no load at 4.7 mph (7.5 km/h)	74.0	73.0
Bystander		--

TIRES, BALLAST AND WEIGHT	With Ballast	Without Ballast
Rear Tires - No., size, ply & psi(kPa)	Four 18.4R38;**,7(50)	Two 18.4R38;**,16(110)
Ballast - Duals (total)	1325 lb (601 kg)	None
- Cast Iron (total)	None	None
Front Tires - No., size, ply & psi(kPa)	Two 14.9R28;**,12(80)	Two 14.9R28;**,12(80)
Ballast - Liquid (total)	None	None
- Cast Iron (total)	None	None
Height of Drawbar	16.9 in (430 mm)	16.9 in (430 mm)
Static Weight with operator - Rear	11355 lb (5150 kg)	10030 lb (4550 kg)
- Front	5190 lb (2355 kg)	5190 lb (2355 kg)
- Total	16545 lb (7505 kg)	15220 lb (6905 kg)

DRAWBAR PERFORMANCE
(Ballasted - Front Drive Engaged)
MAXIMUM POWER AT SELECTED SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
84.5 (63.0)	16815 (74.80)	1.88 (3.03)	2248	15.1	Turtle 0.644 (0.392)	10.86 (2.14)	151 (66)	72 (22)	29.4 (99.7)
92.9 (69.3)	15845 (70.48)	2.20 (3.54)	2149	12.1	Turtle 0.597 (0.363)	11.73 (2.31)	149 (65)	72 (22)	29.5 (99.8)
98.7 (73.6)	13020 (57.92)	2.84 (4.57)	2151	6.5	Turtle 0.563 (0.343)	12.41 (2.45)	153 (67)	75 (24)	29.5 (99.9)
97.7 (72.9)	11155 (49.63)	3.28 (5.28)	2149	4.6	Turtle 0.558 (0.340)	12.53 (2.47)	154 (68)	75 (24)	29.5 (100.0)
99.3 (74.1)	10455 (46.51)	3.56 (5.73)	2151	4.2	Turtle 0.558 (0.339)	12.54 (2.47)	154 (68)	75 (24)	29.5 (100.0)
100.7 (75.1)	9035 (40.19)	4.18 (6.72)	2151	3.2	Turtle 0.553 (0.337)	12.64 (2.49)	156 (69)	75 (24)	29.5 (100.0)
103.3 (77.0)	8075 (35.92)	4.80 (7.72)	2150	2.9	Turtle 0.542 (0.330)	12.90 (2.54)	153 (67)	68 (20)	29.5 (100.0)
102.1 (76.1)	7005 (31.16)	5.47 (8.80)	2151	2.4	Turtle 0.547 (0.333)	12.74 (2.51)	153 (67)	70 (21)	29.5 (100.0)
101.6 (75.8)	6045 (26.89)	6.31 (10.15)	2150	2.1	Turtle 0.551 (0.335)	12.69 (2.50)	156 (69)	68 (20)	29.6 (100.1)
100.2 (74.7)	5285 (23.50)	7.11 (11.45)	2151	1.7	Turtle 0.558 (0.339)	12.54 (2.47)	156 (69)	68 (20)	29.6 (100.1)
99.1 (73.9)	4595 (20.44)	8.09 (13.02)	2150	1.5	Turtle 0.565 (0.343)	12.39 (2.44)	156 (69)	70 (21)	29.6 (100.1)
97.1 (72.4)	3925 (17.46)	9.28 (14.93)	2158	1.3	Turtle 0.578 (0.351)	12.10 (2.38)	156 (69)	70 (21)	29.5 (100.0)
94.0 (70.1)	3230 (14.36)	10.92 (17.57)	2158	1.0	Turtle 0.596 (0.363)	11.73 (2.31)	158 (70)	70 (21)	29.5 (100.0)
100.2 (74.7)	6850 (28.90)	5.79 (9.31)	2150	2.4	Rabbit 0.558 (0.339)	12.54 (2.47)	154 (68)	72 (22)	29.5 (99.8)
99.8 (74.4)	5910 (26.28)	6.33 (10.19)	2150	2.0	Rabbit 0.560 (0.340)	12.49 (2.46)	154 (68)	73 (23)	29.5 (99.8)
99.0 (73.8)	5205 (23.15)	7.13 (11.48)	2151	1.8	Rabbit 0.565 (0.343)	12.39 (2.44)	154 (68)	73 (23)	29.5 (99.8)
98.7 (73.6)	4635 (20.61)	7.98 (12.85)	2150	1.6	Rabbit 0.565 (0.344)	12.38 (2.44)	154 (68)	75 (24)	29.4 (99.7)
97.1 (72.4)	3975 (17.69)	9.16 (14.74)	2153	1.3	Rabbit 0.574 (0.349)	12.18 (2.40)	158 (70)	73 (23)	29.4 (99.7)
95.0 (70.8)	3490 (15.52)	10.20 (16.43)	2155	1.1	Rabbit 0.586 (0.357)	11.93 (2.35)	158 (70)	73 (23)	29.4 (99.7)
93.7 (69.9)	3140 (13.96)	11.20 (18.02)	2150	1.0	Rabbit 0.592 (0.360)	11.80 (2.32)	160 (71)	75 (24)	29.4 (99.7)

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum force exerted

through whole range: 10915 lbs (48.55 kN) (CVT transmission)
8923 lbs (39.7 kN) (Quadrashift transmission)

- i) Opening pressure of relief valve: NA
- Sustained pressure of the open relief valve: 2900 psi (200 bar)
- ii) Pump delivery rate at minimum pressure: 33.6 GPM (127.4 l/min)
- iii) Pump delivery rate at maximum
- hydraulic power: 29.3 GPM (110.8 l/min)
- Delivery pressure: 2740 psi (189 bar)
- Power: 46.8 HP (34.9 kW)

CVT TRANSMISSION HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	29.1	740
B	14.0	355
C	13.8	351
D	11.6	295
E	5.5	140
F	9.8	250
G	32.2	820
H	2.8	70
I	17.5	445
J	22.4	570
K	26.2	665
L	45.1	1145
M	26.0	660
N	40.6	1030
O	7.9	200
P	46.5	1180
Q	36.2	920
R	29.3	745

THREE POINT HITCH PERFORMANCE QUADRASHIFT TRANSMISSION

Observed Maximum Pressure psi. (bar) 2800 (193)
Location: lift cylinder
Hydraulic oil temperature: °F (°C) 149 (65)
Location: hydraulic sump
Category: II
Quick attach: none

SAE Static Test—System pressure 2520 psi (174 Bar)

Hitch point distance to ground level in. (mm)	8.0 (203)	15.1 (384)	22.0 (559)	29.3 (744)	36.2 (919)
Lift force on frame lb	12539	11933	11629	11129	9939
" " " " " " (kN)	(55.8)	(53.1)	(51.7)	(49.5)	(44.2)

QUADRASHIFT TRANSMISSION HITCH DIMENSIONS AS TESTED—NO LOAD

	SAE TEST		OECD TEST	
	inch	mm	inch	mm
A	27.6	702	28.2	716
B	11.6	295	11.6	295
C	13.9	354	13.9	354
D	13.0	330	13.0	330
E	7.9	200	7.9	200
F	10.2	260	10.2	260
G	32.3	820	32.3	820
H	0.3	8	0.3	8
I	15.3	389	15.3	389
J	22.1	560	22.1	560
K	21.5	545	21.5	545
L	40.9	1040	40.9	1040
M	22.2	565	22.2	565
N	37.0	940	37.0	940
O	8.0	203	8.0	203
P	41.1	1043	46.1	1170
Q	36.0	914	36.0	914
R	29.4	748	29.4	748

