

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

January 2004

## Nebraska Summary 523: AGCO RT155A CVT Diesel

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Nebraska Tractor Test Lab, "Nebraska Summary 523: AGCO RT155A CVT Diesel" (2004). *Nebraska Tractor Tests*. 161.

<https://digitalcommons.unl.edu/tractormuseumlit/161>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2198—NEBRASKA SUMMARY 523

## AGCO RT 155A CVT DIESEL POWERMAXX TRANSMISSION

### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1082 rpm)</b>					
157.0 (117.1)	2201	10.17 (38.51)	0.450 (0.274)	15.43 (3.04)	
<b>Standard Power Take-off Speed(1000rpm)</b>					
166.8 (124.4)	2034	10.03 (37.96)	0.417 (0.254)	16.63 (3.28)	
<b>Maximum Power (2 hours)</b>					
168.6 (125.7)	1900	9.54 (36.11)	0.393 (0.239)	17.67 (3.48)	
<b>VARYING POWER AND FUEL CONSUMPTION</b>					
157.0 (117.1)	2201	10.17 (38.51)	0.450 (0.274)	15.43 (3.04)	Air temperature
135.6 (101.1)	2235	9.04 (34.21)	0.462 (0.282)	15.00 (2.96)	66°F (19°C)
102.4 (76.4)	2264	7.41 (28.06)	0.503 (0.306)	13.82 (2.72)	Relative humidity
69.3 (51.7)	2288	5.65 (21.37)	0.566 (0.344)	12.28 (2.42)	45%
35.1 (26.2)	2313	4.14 (15.67)	0.819 (0.498)	8.48 (1.67)	Barometer
--	2335	2.53 (9.56)	--	--	29.7" Hg (97.5 kPa)
Maximum Torque - 542 lb.-ft. (735 Nm) at 1450 rpm					
Maximum Torque Rise - 44.7%					
Torque rise at 1800 engine rpm - 30%					

### DRAWBAR PERFORMANCE

#### (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—Turtle</b>									
125.1 (93.3)	10045 (44.69)	4.67 (7.52)	2203	4.5	0.562 (0.342)	12.33 (2.43)	162 (72)	68 (20)	29.7 (100.5)
<b>75% of Pull at Maximum Power—Turtle</b>									
99.7 (74.4)	7550 (33.58)	4.95 (7.97)	2246	1.9	0.594 (0.361)	11.68 (2.30)	160 (71)	66 (19)	29.7 (100.5)
<b>50% of Pull at Maximum Power—Turtle</b>									
68.9 (51.4)	5065 (22.53)	5.10 (8.21)	2274	0.9	0.680 (0.413)	10.21 (2.01)	156 (69)	70 (21)	29.7 (100.5)
<b>75% of Pull at Reduced Engine Speed—Turtle</b>									
99.8 (74.4)	7540 (33.55)	4.96 (7.98)	1642	2.8	0.472 (0.287)	14.72 (2.90)	156 (69)	70 (21)	29.7 (100.5)
<b>50% of Pull at Reduced Engine Speed—Turtle</b>									
68.1 (50.8)	5010 (22.29)	5.10 (8.20)	1662	1.7	0.526 (0.320)	13.20 (2.60)	151 (66)	70 (21)	29.7 (100.5)

**Location of tests:** DLG testing Station for Agricultural Machinery, Max-Eyth-Weg 1 D-64823 Gross, Umstadt, Germany

**Dates of tests:** January - May, 2004

Sound tests: January 19, 2006

**Manufacturer:** AGCO S.A. BP 60307, Avenue Blaise Pascal, 60026 Beauvais, France

**FUEL and OIL:** Fuel No. 2 Diesel Specific gravity converted to 60°/60° F (15°/15°C) 0.834 Fuel weight 6.94 lbs/gal (0.8322 kg/l) Oil SAE 10W40 API service classification CF4 Transmission and hydraulic lubricant BPTerrac Tractan 9 10W/40 Frontaxle lubricant SAE 85W140 API GL-5

**ENGINE: Make** Sisu Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler **Serial No.** M20369 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.252" x 4.724" (108.0 mm x 120.0 mm) **Compression ratio** 18.5 to 1 **Displacement** 402 cu in (6596 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS: Type** front wheel assist **Serial No.** M309065 **Tread width** rear 63.1" (1604 mm) to 70.8" (1798 mm) front 67.0" (1702 mm) to 75.4" (1915 mm) **Wheelbase** 118.4" (3007 mm) **Hydraulic control system** direct engine drive **Transmission** AGCO CVT. A combination of mechanical and hydrostatic sections are electronically controlled to give the travel speeds shown. The transmission has two mechanical ranges. **Nominal travel speeds mph (km/h)** Forward: Low range 0 - 17 (0 - 28), high range 0 - 31 (0 - 50) reverse: Low range 0 - 10 (0 - 16), high range 0 - 24 (0 - 38) **Clutch** a foot pedal controls the hydrostatic oil flow **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2062 engine rpm or 1000 rpm at 2033 engine rpm **Unladen tractor mass** 15145 lb (6870 kg)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Engaged)**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
128.5 (95.8)	14795 (65.82)	3.26 (5.24)	1943	15.0	Turtle 0.531 (0.323)	13.08 (2.58)	154 (68)	61 (16)	29.7 (100.5)
134.5 (100.3)	12655 (56.30)	3.99 (6.41)	1904	9.0	Turtle 0.494 (0.301)	14.04 (2.77)	160 (71)	59 (15)	29.7 (100.5)
136.1 (101.5)	10465 (46.54)	4.88 (7.85)	1902	6.4	Turtle 0.490 (0.298)	14.16 (2.79)	156 (69)	52 (11)	29.7 (100.5)
136.2 (101.6)	9345 (41.58)	5.47 (8.80)	1900	5.7	Turtle 0.490 (0.298)	14.16 (2.79)	158 (70)	50 (10)	29.7 (100.5)
136.1 (101.5)	8315 (37.00)	6.14 (9.88)	1907	4.8	Turtle 0.490 (0.298)	14.16 (2.79)	154 (68)	52 (11)	29.7 (100.5)
133.8 (99.8)	7060 (31.40)	7.11 (11.44)	1900	4.2	Turtle 0.497 (0.303)	13.95 (2.75)	156 (69)	52 (11)	29.7 (100.5)
132.6 (98.9)	6125 (27.25)	8.12 (13.06)	1894	3.7	Turtle 0.501 (0.305)	13.86 (2.73)	158 (70)	57 (14)	29.7 (100.5)
129.9 (96.9)	5095 (22.67)	9.56 (15.38)	1902	3.7	Turtle 0.512 (0.311)	13.55 (2.67)	158 (70)	55 (13)	29.7 (100.5)
130.2 (97.1)	8950 (39.82)	5.46 (8.78)	1902	5.3	Rabbit 0.509 (0.310)	13.64 (2.69)	165 (74)	66 (19)	29.7 (100.5)
130.6 (97.4)	7855 (34.93)	6.24 (10.04)	1897	4.7	Rabbit 0.507 (0.308)	13.71 (2.70)	165 (74)	66 (19)	29.7 (100.5)
132.1 (98.5)	7230 (32.17)	6.85 (11.02)	1909	4.2	Rabbit 0.501 (0.305)	13.86 (2.73)	165 (74)	68 (20)	29.7 (100.5)
133.6 (99.6)	6595 (29.34)	7.59 (12.22)	1901	4.1	Rabbit 0.501 (0.305)	13.86 (2.73)	165 (74)	68 (20)	29.7 (100.5)
131.4 (98.0)	5455 (24.27)	9.03 (14.54)	1904	3.4	Rabbit 0.509 (0.309)	13.65 (2.69)	160 (71)	63 (17)	29.7 (100.5)

**NOTE 1:** The data on this summary was obtained from OECD report 2198 conducted on the Massey Ferguson 7495 Diesel.

**NOTE 2:** The engine of the AGCO RT155A has two different injection pump characteristics. Power boosted - for travel speeds above 9.3 mph (15.0 kmh) or above 5.0 mph (8.0 kmh) with PTO engaged. Standard for all other conditions.

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2198**, Nebraska Summary 523, May 22, 2006.

Leonard L. Bashford  
Director

M.F. Kocher  
V.I. Adamchuk  
J.A. Smith  
Board of Tractor Test Engineers

**TIRES, BALLAST AND WEIGHT**

**Rear tires** - No., size, ply & psi(kPa)

Ballast - Duals(total)  
- Liquid(none)

**Front tires** - No., size, ply & psi(kPa)

Ballast - Liquid(total)  
- Cast Iron(total)

**Height of Drawbar**

**Static Weight with operator**- Rear  
- Front  
- Total

**With Ballast**

Four 480/80R42; \*\*,6 (40)

1770 lb (803 kg)  
None

Two 380/85R30; \*\*,12 (80)

None  
None

18.9 in (480 mm)

11330 lb (5140 kg)  
5535 lb (2510 kg)  
16865 lb (7650 kg)

**Without Ballast**

Two 520/85R42; \*\*,12(80)

None  
None

Two 540/65R30; \*\*,12(80)

None  
None

21.7 in (550 mm)

9635 lb (4370 kg)  
5675 lb (2575 kg)  
15310 lb (6945 kg)

**DRAWBAR PERFORMANCE**  
**(Ballasted - Front Drive Engaged)**  
**FUEL CONSUMPTION CHARACTERISTICS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. <sup>o</sup> F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—Turtle</b>									
123.5 (92.1)	9570 (42.58)	4.84 (7.79)	2203	4.1	0.569 (0.346)	12.18 (2.40)	158 (70)	68 (20)	29.6 (100.3)
<b>75% of Pull at Maximum Power—Turtle</b>									
95.6 (71.3)	7170 (31.90)	5.00 (8.05)	2247	3.1	0.613 (0.373)	11.32 (2.23)	153 (67)	70 (21)	29.6 (100.3)
<b>50% of Pull at Maximum Power—Turtle</b>									
65.4 (48.8)	4775 (21.25)	5.14 (8.26)	2273	2.2	0.713 (0.434)	9.73 (1.92)	151 (66)	70 (21)	29.6 (100.3)
<b>75% of Pull at Reduced Engine Speed—Turtle</b>									
95.9 (71.5)	7165 (31.87)	5.02 (8.07)	1964	3.1	0.524 (0.319)	13.24 (2.61)	151 (66)	68 (20)	29.6 (100.3)
<b>50% of Pull at Reduced Engine Speed—Turtle</b>									
65.3 (48.7)	4765 (21.19)	5.14 (8.28)	1984	2.1	0.594 (0.362)	11.67 (2.30)	149 (65)	70 (21)	29.6 (100.3)
<b>MAXIMUM POWER IN SELECTED GEARS</b>									
121.9 (90.9)	16995 (75.60)	2.69 (4.33)	2021	15.1	Turtle 0.562 (0.342)	12.33 (2.43)	156 (69)	64 (18)	29.6 (100.3)
132.2 (98.6)	15150 (67.39)	3.27 (5.27)	1901	8.7	Turtle 0.502 (0.305)	13.82 (2.72)	151 (66)	73 (23)	29.6 (100.4)
133.4 (99.5)	14280 (63.53)	3.50 (5.64)	1900	7.3	Turtle 0.496 (0.302)	14.00 (2.76)	153 (67)	68 (20)	29.6 (100.4)
133.7 (99.7)	12435 (53.31)	4.03 (6.49)	1899	5.9	Turtle 0.493 (0.300)	14.06 (2.77)	154 (68)	64 (18)	29.7 (100.5)
134.8 (100.5)	10645 (47.34)	4.75 (7.64)	1901	4.4	Turtle 0.490 (0.298)	14.16 (2.79)	156 (69)	72 (22)	29.7 (100.5)
134.4 (100.2)	9480 (42.16)	5.32 (8.55)	1902	4.1	Turtle 0.492 (0.300)	14.09 (2.78)	156 (69)	66 (19)	29.7 (100.5)
133.2 (99.3)	7985 (35.52)	6.25 (10.06)	1903	3.2	Turtle 0.500 (0.304)	13.90 (2.74)	156 (69)	66 (19)	29.6 (100.4)
131.0 (97.7)	6990 (31.09)	7.03 (11.32)	1901	3.0	Turtle 0.506 (0.308)	13.71 (2.70)	158 (70)	68 (20)	29.6 (100.4)
128.9 (96.1)	6005 (26.72)	8.05 (12.95)	1903	2.6	Turtle 0.516 (0.314)	13.45 (2.65)	158 (70)	66 (19)	29.6 (100.4)
125.9 (93.9)	5015 (22.30)	9.42 (15.16)	1904	2.0	Turtle 0.529 (0.322)	13.12 (2.59)	158 (70)	65 (18)	29.6 (100.4)
131.7 (98.2)	9030 (40.16)	5.47 (8.80)	1903	3.9	Rabbit 0.504 (0.306)	13.77 (2.71)	158 (70)	63 (17)	29.6 (100.3)
132.0 (98.4)	7870 (35.01)	6.29 (10.12)	1902	3.4	Rabbit 0.502 (0.305)	13.82 (2.72)	158 (70)	63 (17)	29.6 (100.3)
131.2 (97.8)	7015 (31.20)	7.01 (11.29)	1902	3.1	Rabbit 0.505 (0.307)	13.73 (2.70)	158 (70)	64 (18)	29.6 (100.3)
130.7 (97.5)	6150 (27.35)	7.97 (12.83)	1902	2.7	Rabbit 0.508 (0.309)	13.65 (2.69)	156 (69)	64 (18)	29.6 (100.3)
129.1 (96.3)	5465 (24.32)	8.86 (14.26)	1902	2.4	Rabbit 0.516 (0.314)	13.45 (2.65)	153 (67)	63 (17)	29.6 (100.3)

**TRACTOR SOUND LEVEL WITH CAB**

**dB(A)**

At no load in Turtle-4.6 mph (7.5 km/h)- no load	70.4
Bystander in Rabbit	86.4

**THREE POINT HITCH PERFORMANCE (OECD Static Test)**

CATEGORY: III

Quick Attach: None

Maximum force exerted through whole range: 14283 lbs (63.5 kN)

i) Opening pressure of relief valve: NA

Sustained pressure of the open relief valve: 2875 psi (198 bar)

ii) Pump delivery rate at minimum pressure: 32.2 GPM (122.0 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 29.0 GPM (109.7 l/min)

Delivery pressure: 2610 psi (180 bar)

Power: 44.1 HP (32.9 kW)

	SAE TEST		OECD TEST	
	inch	mm	inch	mm
A	30.3	768	29.7	754
B	14.0	355	14.0	355
C	13.7	347	13.7	347
D	12.0	305	12.0	305
E	12.6	321	12.6	321
F	10.0	255	10.0	255
G	34.2	870	34.2	870
H	2.4	60	2.4	60
I	18.7	476	18.7	476
J	24.2	615	24.2	615
K	27.2	690	27.2	690
L	46.3	1175	46.3	1175
M	26.2	665	26.2	665
N	40.6	1030	40.6	1030
O	8.0	203	9.0	230
P	46.2	1173	51.2	1300
Q	37.3	947	39.5	1003
R	29.9	759	29.3	744

**THREE POINT HITCH PERFORMANCE SAE Test**

Observed Maximum Pressure psi. (bar)	2850 (197)
Location:	lift cylinder
Hydraulic oil temperature: °F (°C)	148 (64)
Location:	hydraulic sump
Category:	III
Quick attach:	None

**SAE Static Test**—System pressure 2665 psi (177 Bar)

Hitch point distance to ground level in. (mm)	8.2 (208)	14.4 (366)	20.8 (528)	27.2 (691)	33.6 (853)	40.0 (1016)
Lift force on frame lb	19719	17748	17721	18009	17874	16992
" " " " " " (kN)	(87.7)	(78.9)	(78.8)	(79.5)	(79.5)	(75.6)

