

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 2002

Tests 2031 & 2055: Case IH JX 85 Diesel

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and [the United States History Commons](#)

Nebraska Tractor Test Lab, "Tests 2031 & 2055: Case IH JX 85 Diesel" (2002). *Nebraska Tractor Tests*. 202.

<https://digitalcommons.unl.edu/tractormuseumlit/202>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TESTS 2031 & 2055—NEBRASKA SUMMARY 405

CASE IH JX 85 DIESEL

12 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
---------------------	--------------------------------	-----------------	-----------------------	-----------------------	--------------------------------

MAXIMUM POWER AND FUEL CONSUMPTION

Rated Engine Speed (PTO speed-614 rpm)					
71.1 (53.0)	2500	4.22 (15.99)	0.410 (0.250)	16.83 (3.32)	
Standard Power Take-off Speed (540 rpm)					
65.8 (49.1)	2200	3.91 (14.80)	0.409 (0.249)	16.85 (3.32)	

VARYING POWER AND FUEL CONSUMPTION

71.1 (53.0)	2500	4.22 (15.99)	0.410 (0.250)	16.83 (3.32)	Air temperature
62.8 (46.8)	2598	3.64 (13.77)	0.400 (0.243)	17.26 (3.40)	79°F (26°C)
48.0 (35.8)	2652	2.89 (10.95)	0.416 (0.253)	16.60 (3.27)	Relative humidity
32.5 (24.2)	2684	2.22 (8.40)	0.472 (0.287)	14.62 (2.88)	36%
16.4 (12.2)	2706	1.58 (5.98)	0.666 (0.405)	10.36 (2.04)	Barometer
--	2741	1.00 (3.80)	--	--	27.0" Hg (91.6 kPa)

Maximum Torque - 169.7 lb.-ft. (230.1 Nm) at 1500 rpm
 Maximum Torque Rise - 13.6%
 Torque rise at 2000 engine rpm - 9%

DRAWBAR PERFORMANCE

(Unballasted-Front Drive Engaged)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °C (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—10th (III-2) Gear									
58.4 (43.5)	2455 (10.92)	8.92 (14.35)	2508	6.0	0.478 (0.291)	14.42 (2.84)	167 (75)	79 (26)	27.1 (91.9)
75% of Pull at Maximum Power—10th (III-2) Gear									
45.2 (33.7)	1840 (8.19)	9.22 (14.83)	2559	4.8	0.569 (0.346)	12.13 (2.39)	167 (75)	79 (26)	27.1 (91.9)
50% of Pull at Maximum Power—10th (III-2) Gear									
31.2 (23.3)	1230 (5.46)	9.53 (15.34)	2623	3.9	0.673 (0.409)	10.25 (2.02)	167 (75)	79 (26)	27.1 (91.9)
75% of Pull at Reduced Engine Speed—11th (III-3) Gear									
45.1 (33.7)	1835 (8.17)	9.22 (14.83)	1875	4.5	0.514 (0.313)	13.43 (2.64)	167 (75)	79 (26)	27.1 (91.9)
50% of Pull at Reduced Engine Speed—11th (III-3) Gear									
28.3 (21.1)	1110 (4.95)	9.54 (15.34)	1933	4.1	0.560 (0.341)	12.32 (2.43)	167 (75)	79 (26)	27.1 (91.9)

Locations of tests: DAEMTC (The Directorate of Agricultural Equipment and Machinery Testing Centre) Ankara, Turkey and CNH America LLC Burr Ridge, IL USA

Dates of Test: PTO & Drwb: May - August, 2002
 Sound tests: December 2, 2003
 Hydraulic flow: August 8, 2003
 Lift tests: December 2, 2003

Manufacturer: CNH America LLC, 700 State St. Racine, Wi. 53404 USA

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60° F (15°/15°C)** 0.829
Fuel weight 6.90 lbs/gal (0.827 kg/l) **Oil SAE** 20W-50 **API service classification** CF-4/SG
Transmission and hydraulic lubricant BP Terrac Tractan 8 fluid **Front axle lubricant** BP Terrac Tractan 8 fluid

ENGINE: Make Iveco Diesel **Type** four cylinder vertical **Serial No.** 846667 **Crankshaft** lengthwise
Rated engine speed 2500 **Bore and stroke** 4.094" x 4.528" (104.0 mm x 115.0 mm) **Compression ratio** 17.0 to 1 **Displacement** 238 cu in (3908 ml)
Starting system 12 volt **Lubrication** pressure **Air cleaner** paper element **Oil filter** two cartridges **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat

CHASSIS: **Type** 2WD & front wheel assist **Serial No.** 2WD - HFD000039, FWA-HFD000300
Tread width rear 59.1" (1500 mm) to 78.7" (2000 mm) front 2WD - 55.5" (1410 mm) to 75.2" (1910 mm) FWA-60.2" (1530 mm) to 77.0" (1955 mm)
Wheel base 2WD - 90.7" (2305 mm), FWA-88.5" (2249 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio **Nominal travel speeds mph (km/h)** first 1.06 (1.71) second 1.64 (2.64) third 2.23 (3.59) fourth 2.49 (4.00) fifth 3.19 (5.14) sixth 3.83 (6.16) seventh 5.21 (8.38) eighth 5.85 (9.42) ninth 7.46 (12.00) tenth 9.02 (14.51) eleventh 12.26 (19.73) twelfth 17.56 (28.26) reverse 1.07 (1.72), 1.65 (2.65), 2.24 (3.60), 2.49 (4.01), 3.21 (5.16), 3.84 (6.18), 5.23 (8.41), 5.87 (9.45), 7.48 (12.04), 9.04 (14.55), 12.30 (19.79), 17.62 (28.35) **Clutch** dual dry disc operated by foot pedal **Brakes** wet disc operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2200 engine rpm and 1000 rpm at 2382 engine rpm **Unladen tractor mass** 2WD - 6425 lb (2914 kg), FWA - 6995 lb (3172 kg)

DRAWBAR PERFORMANCE
(Unballasted – Front Drive Engaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crankshaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F (°C) cooling med	Barom. inch Hg (kPa)		
5th (I-4) Gear									
35.7 (26.6)	4460 (19.84)	3.00 (4.82)	2609	14.4	0.635 (0.386)	10.86 (2.14)	172 (78)	82 (28)	27.2 (92.0)
6th (II-2) Gear									
41.6 (31.0)	4380 (19.48)	3.56 (5.73)	2587	14.3	0.603 (0.367)	11.45 (2.26)	172 (78)	81 (27)	27.2 (92.0)
7th (II-3) Gear									
48.8 (36.4)	3765 (16.74)	4.86 (7.83)	2521	11.4	0.569 (0.346)	12.13 (2.39)	172 (78)	81 (27)	27.2 (92.0)
8th (III-1) Gear									
51.0 (38.0)	3320 (14.77)	5.76 (9.26)	2513	6.8	0.542 (0.329)	12.74 (2.51)	176 (80)	81 (27)	27.2 (92.0)
9th (II-4) Gear									
52.2 (38.9)	2660 (11.83)	7.36 (11.84)	2510	6.4	0.531 (0.323)	12.99 (2.56)	176 (80)	81 (27)	27.2 (92.0)
10th (III-2) Gear									
58.4 (43.5)	2455 (10.93)	8.92 (14.35)	2508	6.0	0.478 (0.291)	14.42 (2.84)	176 (80)	81 (27)	27.2 (92.0)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

NOTE: The PTO and drawbar results shown on this report are from tests conducted on the New Holland TD 85D.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 3 point lift capacity of 5975 lbs (2710 kg). The performance results on this summary were taken from OECD tests conducted under the Code II Test Code procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **2031** & **2055**, Nebraska Summary 405, January 14, 2004.

Leonard L. Bashford
 Director

M.F. Kocher
 V.I. Adamchuk
 W.P. Campbell
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in 7th(II-3) Gear	88.7	88.1
Bystander	-	-

Tested Without Ballast

TIRES AND WEIGHT	Front Wheel Assist		2WD
	Rear tires - No., size, ply & psi (kPa)	Two 18.4-30; 6; 22(150)	Two 18.4-30; 6; 22 (150)
Front tires - No., size, ply & psi (kPa)	Two 12.4-24; 6; 32(220)	Two 7.50-18; 8; 32(220)	
Height of Drawbar	16.1 in (410 mm)	16.7 in (425 mm)	
Static Weight with operator-Rear	4315 lb (1956 kg)	4405 lb (1998 kg)	
- Front	2845 lb (1291 kg)	2185 lb (991 kg)	
- Total	7160 lb (3247 kg)	6590 lb (2989 kg)	

DRAWBAR PERFORMANCE

(Unballasted - 2WD)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp.°F cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—10th(III-2) Gear									
58.2 (43.4)	2530 (11.25)	8.62 (13.88)	2508	8.0	0.517 (0.315)	13.34 (2.63)	167 (75)	79 (26)	27.0 (91.5)
75% of Pull at Maximum Power—10th(III-2) Gear									
46.1 (34.4)	1895 (8.44)	9.12 (14.68)	2604	6.3	0.581 (0.353)	11.88 (2.34)	167 (75)	79 (26)	27.0 (91.5)
50% of Pull at Maximum Power—10th(III-2) Gear									
31.6 (23.4)	1265 (5.63)	9.36 (15.07)	2646	5.3	0.673 (0.409)	10.25 (2.02)	167 (75)	79 (26)	27.0 (91.5)
75% of Pull at Reduced Engine Speed—11th(III-3) Gear									
46.7 (34.8)	1915 (8.53)	9.13 (14.70)	1918	6.3	0.501 (0.305)	13.76 (2.71)	167 (75)	79 (26)	27.0 (91.5)
50% of Pull at Reduced Engine Speed—11th(III-3) Gear									
32.1 (23.9)	1285 (5.71)	9.38 (15.10)	1951	5.3	0.556 (0.338)	12.43 (2.45)	167 (75)	79 (26)	27.0 (91.5)
MAXIMUM POWER IN SELECTED GEARS									
8th(III-1) Gear									
45.5 (33.9)	3145 (14.00)	5.42 (8.72)	2614	14.5	0.589 (0.358)	11.73 (2.31)	176 (80)	77 (25)	27.0 (91.6)
9th(II-4) Gear									
55.2 (41.1)	2925 (13.02)	7.07 (11.38)	2515	9.1	0.543 (0.330)	12.71 (2.50)	176 (80)	77 (25)	27.2 (92.0)
10th(III-2) Gear									
58.2 (43.4)	2530 (11.25)	8.62 (13.88)	2508	8.0	0.517 (0.315)	13.34 (2.63)	176 (80)	77 (25)	27.0 (91.6)

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: none

Maximum Force Exerted Through Whole Range: 3845 lbs (17.1 kN)

- i) Opening pressure of relief valve: NA
- Sustained pressure of the open relief valve: 2680 psi (185 bar)
- ii) Pump delivery rate at minimum pressure and rated engine speed: 11.9 GPM (45.2 l/min)
- iii) Pump delivery rate at maximum hydraulic power: 9.5 GPM (35.9 l/min)
- Delivery pressure: 2314 psi (160 bar)
- Power: 12.8 HP (9.5 kW)

THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi. (bar)	2580 (178)
Location:	hydraulic manifold
Hydraulic oil temperature: °F (°C)	149 (65)
Location:	hydraulic sump
Category:	II
Quick attach:	none

SAE Static Test—System pressure 2325 psi (160 Bar)

Hitch point distance to ground level in. (mm)	8.0 (203)	15.0 (380)	21.9 (556)	29.0 (737)	36.0 (914)
Lift force on frame lb	5652	5862	5487	5658	5002
" " " " " " (kN)	(25.1)	(26.1)	(24.4)	(25.2)	(22.3)

HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	32.7	830	31.6	803
B	10.2	260	10.2	260
C	11.5	291	11.5	291
D	11.4	290	11.4	290
E	7.9	200	9.4	240
F	7.9	200	7.9	200
G	28.4	720	27.4	695
H	0.2	5	0.2	5
I	7.1	180	7.1	180
J	20.5	520	19.5	495
K	18.1	460	21.1	535
L	40.1	1018	40.1	1018
M	28.5	723	28.5	723
N	38.2	970	38.2	970
O	8.1	205	8.0	203
P	44.5	1130	38.3	973
Q	32.3	820	33.6	854
R	23.8	605	25.7	654

