

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1955

Test 544: Oliver Super 66 Diesel

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 544: Oliver Super 66 Diesel" (1955). *Nebraska Tractor Tests*. 528.
<https://digitalcommons.unl.edu/tractormuseumlit/528>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

The Experiment Station
University of Nebraska College of Agriculture
W. V. Lambert, Director, Lincoln, Nebraska

Department of Agricultural Engineering
Dates of test: May 19 to May 26, 1955
Manufacturer: THE OLIVER CORPORATION,
CHARLES CITY, IOWA
Manufacturer's rating: Not rated

NEBRASKA TRACTOR TEST NO. 544

OLIVER SUPER 66 DIESEL

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer inches of mercury		
		Gal per hour	Hp-hr per gal	Lb per hp-hour		Cooling med	Air			
TESTS B AND C—100% MAXIMUM LOAD—TWO HOURS										
33.69	2000	2.378	14.17	0.496	0.00	173	71	28.750		
TEST D—RATED LOAD—ONE HOUR										
30.14	2000	2.111	14.28	0.492	0.00	168	70	28.750		
TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average)										
30.17	2002	2.114	14.27	0.492	...	167	69		
1.53	2178	0.735	2.08	3.373	...	143	70		
15.87	2099	1.405	11.30	0.622	...	159	71		
31.28	1940	2.157	14.50	0.484	...	171	72		
8.11	2141	1.038	7.81	0.899	...	152	71		
23.23	2053	1.730	13.43	0.523	...	164	72		
18.37	2068	1.530	12.01	0.585	0.00	159	71	28.750		
TORQUE (At Dynamometer)										
Eng rpm	1999	1864	1739	1617	1486	1365	1247	1111	994	870
Lb-ft	204.8	211.8	217.0	222.3	220.5	212.6	210.0	196.9	183.8	161.9
Dyn rpm	840	783	730	679	624	573	524	467	416	362

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lb	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer inches of mercury
					Gal per hour	Hp-hr per gal	Lb per hp-hr		Cool- ing med	Air	
TEST H—RATED LOAD—TEN HOURS—4th Gear											
22.49	1622	5.20	1750	3.64	1.778	12.65	0.555	0.00	166	64	28.703
TESTS F AND G—100% MAXIMUM LOAD											
22.32	4393	1.91	1747	12.17	1st gear (part throttle).....				166	72	28.580
26.33	3436	2.87	1749	8.13	2nd gear.....				175	72	28.580
27.08	2896	3.51	1752	6.34	3rd gear				174	72	28.580
27.48	1995	5.16	1751	4.55	4th gear				173	72	28.590
26.83	1639	6.14	1750	3.63	5th gear.....				172	72	28.590
24.50	852	10.78	1751	1.94	6th gear.....				170	74	28.580
TEST J—OPERATING MAXIMUM LOAD											
26.42	1990	4.98	1753	7.54	4th gear.....				168	74	28.210
TEST K—OPERATING MAXIMUM LOAD											
25.39	2060	4.62	1751	10.26	4th gear.....				168	77	28.210

TIRES,*WHEELS AND WEIGHT

	Tests F, G, & H	Test J	Test K
Rear wheels			
Type	Cast iron	Cast iron	Pressed steel
Liquid ballast	358 lb each	None	None
Added cast iron	980 lb each	None	None
Rear tires			
No. and size	Two 10-38	Two 10-38	Two 9-38
Ply	6	6	4
Air pressure	24 lb	12 lb	12 lb
Front wheels			
Type	Pressed steel	Pressed steel	Pressed steel
Liquid ballast	None	None	None
Added cast iron	105 lb each	None	None
Front tires			
No. and size	Two 5.00-15	Two 5.00-15	Two 5.00-15
Ply	4	4	4
Air pressure	28 lb	28 lb	28 lb
Height of drawbar	23 inches	23½ inches	21½ inches
Static weight			
Rear end	5450 lb	2775 lb	2336 lb
Front end	1310 lb	1100 lb	1100 lb
Total weight as tested with operator	6935 lb	4050 lb	3611 lb

FUEL, OIL and TIME Diesel fuel Cetane No. 50 (rating taken from oil company's typical inspection data); weight per gallon 7.025 lb Oil SAE 10 to motor 0.887 gal drained from motor 0.720 gal Total time motor was operated 38½ hours.

CHASSIS Type Tricycle Serial No. 7204-606 Tread width rear 60" to 88" front 6¾" to 11½" Wheel base 86 11/16" Hydraulic control system direct engine drive Advertised speeds mph first 2¼ second 3.08 third 3.68 fourth 5.31 fifth 6.27 sixth 10.81 reverse 2.43 and 4.19 Belt pulley diam 9½" face 7¼" rpm 1232 Belt speed 3064 fpm Clutch single plate dry disc operated by foot pedal Seat pressed steel cushioned by rubber in torsion Brakes double disc brakes operated by two foot pedals Equalized by connecting bar which serves as master brake pedal Power take-off direct engine drive with independent clutch.

ENGINE Make Oliver Diesel Type 4 cylinder vertical Serial No. 947405 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and stroke 3½" x 3¾" Rated rpm belt 2000 drawbar 1750 Compression ratio 16.0 to 1 Displacement 144 cu in Port diameter valves inlet 1½" exhaust 1" Governor variable speed centrifugal Starting system 12 volt battery Air cleaner oil washed wire mesh Muffler was used Oil filter replaceable waste packed filter Fuel filter one permanent edge type fuel strainer, one replaceable filter element and one replaceable filter Cooling medium temperature control thermostat.

REPAIRS AND ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with fuel pump set to develop approximately 35 corrected maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J & K were made with the same setting.

HORSEPOWER SUMMARY

	Drawbar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" HG)	29.09	35.43
2. Observed maximum horsepower (tests F and B)	27.48	33.69
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings)	21.82	30.12

We, the undersigned, certify that this is a true and correct report of official tractor test No. 544.

L. F. LARSEN
Engineer-In-Charge

C. W. SMITH
L. W. HURLBUT
F. D. YUNG
Board of Tractor
Test Engineers

EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissible include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

BELT HORSEPOWER TESTS

TEST B: The throttle valve is held wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel economy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. *This more practical carburetor setting is used in all later tests except test F.* The throttle valve is held wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors, which have an altogether different fuel system.

TEST D: The throttle control lever is set so that the governor will maintain rated engine speed when rated load is applied. Rated load is 85% of 100% maximum, as obtained in test B, corrected to standard conditions.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

TEST E:

Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads, of 20 minutes each: rated load, no load, $\frac{1}{2}$ rated load, maximum load at wide open throttle valve, $\frac{1}{4}$ and $\frac{3}{4}$ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

Torque, lb-ft at dynamometer, is obtained with wide open throttle and sufficient load is applied to give several readings.

DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instrument in the test car. All tests are made on the same dirt test course which is maintained by grading, sprinkling and rolling

so that it remains very nearly the same throughout the season. The same tires, wheels and weights are used for all tests except J and K.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in this test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 16%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated load the throttle control lever is set to maintain rated engine speed. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: Similar to test J except that the smallest tires and lightest wheels offered by the manufacturer are used.

