

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 1941

Test 372: International TracTractor Model T-9 (Gasoline) (Wide Tread)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 372: International TracTractor Model T-9 (Gasoline) (Wide Tread)" (1941). *Nebraska Tractor Tests*. 959.

<https://digitalcommons.unl.edu/tractormuseumlit/959>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Copy of Report of Official Tractor Test No. 372

Dates of test: May 27 to June 18, 1941
 Name and model of tractor: INTERNATIONAL TRACTOR (Wide Tread) T-9 (Gasoline)
 Manufacturer: International Harvester Company, Chicago, Illinois
 Manufacturer's rating: NOT RATED

B E L T H O R S E P O W E R T E S T S

Hp.	Crank- shaft Speed R.P.M.	Fuel Consumption			Water Used Gal. per Hr.	Temperature Deg. F.		Barometer Inches of Mercury
		Gal. per Hr.	Hp.-hr. per Gal.	Lb.-per Hp.-hr.		Cool- ing Medium	Air	

TEST B - 100% MAXIMUM LOAD - TWO HOURS

46.46	1400	3.917	11.86	0.514	0.000	192	76	28.975
-------	------	-------	-------	-------	-------	-----	----	--------

TEST C - OPERATING MAXIMUM LOAD - ONE HOUR

46.03	1400	3.846	11.97	0.510	0.000	191	79	28.940
-------	------	-------	-------	-------	-------	-----	----	--------

* TEST D - ONE HOUR

41.49	1400	3.611	11.49	0.531	0.000	197	81	28.920
-------	------	-------	-------	-------	-------	-----	----	--------

TEST E - VARYING LOAD - TWO HOURS (20 minute runs; last line average)

41.40	1399	3.600	11.50	0.530	- - -	198	83	- - -
1.22	1520	1.697	0.72	8.484	- - -	197	83	- - -
21.95	1476	2.780	7.90	0.768	- - -	197	83	- - -
44.75	1367	3.733	11.99	0.509	- - -	194	85	- - -
11.11	1502	2.203	5.04	1.210	- - -	195	84	- - -
31.90	1433	3.172	10.06	0.607	- - -	195	84	- - -
25.39	1450	2.861	8.87	0.687	0.000	196	84	28.890

D R A W B A R H O R S E P O W E R T E S T S

Hp.	Draw- bar Pull Lbs.	Speed Miles per Hr.	Crank- shaft Speed R.P.M.	Slip of Drive Wheels %	Fuel Consumption			Water Used Gal. per Hr.	Temp. Deg. F.		Barometer Inches of Mercury
					Gal. per Hr.	Hp.-hr. per Gal.	Lb. per Hp.-hr.		Cool- ing Med.	Air	

TEST F - 100% MAXIMUM LOAD - Second GEAR

40.59	7091	2.15	1403	2.69	----- Not Recorded -----			183	85	28.930
-------	------	------	------	------	--------------------------	--	--	-----	----	--------

TEST G - OPERATING MAXIMUM LOAD

39.11	9868	1.49	1405	4.67	----- Not Recorded -----			183	86	28.920
39.48	6904	2.14	1400	2.55	" "			184	83	28.930
38.62	4556	3.18	1402	1.52	" "			187	82	28.985
37.35	3650	3.84	1403	1.22	" "			188	81	28.985
34.15	2434	5.26	1403	0.75	" "			188	78	28.985

* TEST H - TEN HOURS - Second GEAR

32.29	5677	2.13	1400	3.03	3.547	9.10	0.670	0.000	194	83	28.950
-------	------	------	------	------	-------	------	-------	-------	-----	----	--------

* Formerly called RATED LOAD; see REMARKS 4, page 3.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
AGRICULTURAL COLLEGE, LINCOLNCopy of Report of Official Tractor Test No. 372FUEL, OIL and TIME

Fuel Gasoline Octane 73 Weight per gallon 6.10 pounds
 Oil: S.A.E. No. 20 To motor 3.454 gal. Drained from motor 1.924 gal.
 Total time motor was operated 49 hours

BRIEF SPECIFICATIONS

Advertised speeds, miles per hour: First 1 1/2 Second 2 1/4
 Third 3 1/4 Fourth 3 7/8 Fifth 5 1/4 Reverse 1 3/4
 Belt pulley: Diam. 11.313" Face 9" R.P.M. 878 Belt speed 2600 f.p.m.
 Clutch: Make Rockford Type Single plate, dry disc Operated by Hand
 Seat Upholstered
 Total weight as tested (with operator) 10,830 pounds

MOTOR

Make Own Serial No. TCBM517-T1 Type 4 cylinder, vertical
 Head I Mounting Crankshaft lengthwise Lubrication Pressure
 Bore and stroke 4.4" x 5.5" Rated R.P.M. 1400
 Port diameter valves: Inlet 1.875" Exhaust 1.688"
 Magneto: Make Own Model H-4
 Carburetor: Make Own Model E-13 Size 1 3/8"
 Governor: Make Own Type Variable speed, centrifugal
 Air Cleaner: Make Donaldson Type Oil-washed wire screen filter
 Oil Filter: Make Motor Improvements, Inc. Type Partial flow with re-
 placeable bakelite impregnated paper element
 Cooling medium temperature control: Bishop and Babcock thermostat and
 Defiance radiator shutters

CHASSIS

Type Tracklayer Serial No. 2413T7 Drive Enclosed gear
 Tread width: 60" (wide tread) Measured length of track 17.9053'
 Cleats: Type Integral with shoes No. per track 33
 Size 2 1/8" high x 20" long (clipped corners)

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 372

REPAIRS AND ADJUSTMENTS

Before the start of rated load drawbar test, a belt which was missing from one of the track shoes, was replaced by a new one.

REMARKS

1. All results shown on page 1 of this report were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G and H were made with an operating setting of the carburetor (selected by the manufacturer) of 99.5% of maximum belt horsepower.

	<u>DRAWBAR</u>	<u>BELT</u>
2. Observed maximum horsepower (tests F & B)	40.59	46.46
3. "Sea level (calculated) maximum horsepower (based on 60° F, and 29.92" Hg)	42.98	48.69
4. "Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly A.S.A.E. and S.A.E. ratings)	32.24	41.39

We, the undersigned, certify that the above is a true and correct report of official tractor test No. 372.

Carlton L. Zink
 Engineer-in-charge

E. E. Brackett

C. W. Smith

L. W. Hurlbut
 Board of Tractor Test Engineers