

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

January 1941

Test 377: Massey-Harris Model 101-R

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 377: Massey-Harris Model 101-R" (1941). *Nebraska Tractor Tests*. 962. <https://digitalcommons.unl.edu/tractormuseumlit/962>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 377

REPAIRS AND ADJUSTMENTS

No repairs or adjustments.

REMARKS

1. All results shown on pages 1 and 2 of this report were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests was used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J and K were made with an operating setting of the carburetor (selected by the manufacturer of 95.1% of maximum belt horsepower.
2. Observed maximum horsepower (tests F and B)

<u>DRAWBAR</u>	<u>BELT</u>
34.63	46.97
3. Sea level (calculated maximum horsepower
 (based on 60°F. and 29.92" Hg.)

36.67	47.91
-------	-------
4. Seventy-five per cent of calculated maximum
 drawbar horsepower and eighty-five per cent
 of calculated maximum belt horsepower (formerly
 A.S.A.E. and S.A.E. ratings)

27.50	40.72
-------	-------

We, the undersigned, certify that the above is a true and correct report of official tractor test No. 377.

Carlton L. Zink
 Engineer-in-Charge

E. E. Brackett

C. W. Smith

L. W. Hurlbut
 Board of Tractor Test Engineers

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 377

Dates of test: September 30 to October 20, 1941
 Name and model of tractor: MASSEY HARRIS 101 R
 Manufacturer: The Massey Harris Company, Racine, Wisconsin
 Manufacturer's rating: NOT RATED

B R A K E H O R S E P O W E R T E S T S

Hp.	Crank- shaft Speed R.P.M.	Fuel Consumption			Water Used Gal. per Hr.	Temperature Deg. F.		Barometer Inches of Mercury
		Gal. per Hr.	Hp.-hr. per Gal.	Lb. per Hp.-hr.		Cool- ing Medium	Air	

TEST B - 100% MAXIMUM LOAD - TWO HOURS

46.97	1802	4.008	11.72	0.520	0.000	173	54	29.160
-------	------	-------	-------	-------	-------	-----	----	--------

TEST C - OPERATING MAXIMUM LOAD - ONE HOUR

44.11	1799	3.701	11.92	0.511	0.000	177	69	29.210
-------	------	-------	-------	-------	-------	-----	----	--------

* TEST D - ONE HOUR

40.90	1801	3.537	11.56	0.527	0.000	183	79	29.185
-------	------	-------	-------	-------	-------	-----	----	--------

TEST E - VARYING LOAD - TWO HOURS

(20 minute runs; last line average)

40.90	1799	3.542	11.55	0.527	---	184	80	---
1.22	1970	1.384	0.88	6.910	---	166	81	---
21.78	1905	2.433	8.95	0.680	---	169	80	---
42.82	1800	3.645	11.75	0.518	---	186	81	---
11.02	1926	1.803	6.11	0.996	---	164	80	---
32.32	1892	3.054	10.58	0.575	---	177	81	---
25.01	1882	2.644	9.46	0.644	---	173	80	29.145

* Formerly called RATED LOAD; see REMARKS 4, page 5.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 377

D R A W B A R H O R S E P O W E R T E S T S

Hp.	Draw- bar Pull Lbs.	Speed Miles per Hr.	Crank- shaft Speed R.P.M.	Slip of Drive Wheels %	Fuel Consumption			Water Used Gal. per Hr.	Temp. Deg. F.		Barometer Inches of Mercury
					Gal. per Hr.	Hp.-hr. per Gal.	Lb. per Hp.-hr.		Cool- ing Air Med.		

Rear wheels, tires and added weight used in Tests F, G and H: Pressed steel wheels; 11-38, 6 ply tires and 1081 lbs. added weight per wheel.

TEST F - 100% MAXIMUM LOAD - Third GEAR

34.63	2747	4.73	1500	6.51	-----Not Recorded-----			187	75	28.650
-------	------	------	------	------	------------------------	--	--	-----	----	--------

TEST G - OPERATING MAXIMUM LOAD

23.68	3905	2.27	1500	15.84	-----Not Recorded-----			182	81	28.610
31.90	3520	3.40	1501	10.04	"	"		184	77	28.650
33.32	2627	4.76	1500	5.93	"	"		182	73	28.650

*TEST H - TEN HOURS - Third GEAR

28.08	2204	4.78	1500	4.91	2.794	10.05	0.606	0.000	169	60	29.065
-------	------	------	------	------	-------	-------	-------	-------	-----	----	--------

TEST J - OPERATING MAXIMUM LOAD

Same wheels and tires as used in Tests F, G and H, All added weight removed from tractor (liquid, cast iron or any other added forms). Third gear.

28.09	2426	4.34	1490	14.43	-----Not Recorded-----			172	63	29.250
-------	------	------	------	-------	------------------------	--	--	-----	----	--------

TEST K - OPERATING MAXIMUM LOAD

Rear wheels, tires and added weight used: Pressed steel wheels; 10-38, 6 ply tires and no added weight per wheel (**Combination No. 2). Third gear.

23.86	2121	4.22	1500	13.94	-----Not Recorded-----			170	68	29.210
-------	------	------	------	-------	------------------------	--	--	-----	----	--------

* Formerly called RATED LOAD; see REMARKS 4, page 5.

** Combination No. 1: Includes wheels, tires and added weight recommended in the manufacturer's published specifications.

Combination No. 2: When the manufacturer does not make a specific recommendation then the tires used are the smallest size and ply and the wheels are the lightest listed in published specifications or the application for test.

See page 3 for specifications on wheels, tires and weight.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 377

FUEL, OIL AND TIME

Fuel Gasoline Octane 73 Weight per gallon 6.09 pounds

Oil: S.A.E. No. 10 To motor 1.432 gal. Drained from motor 1.052 gal.

Total time motor was operated 46 hours.

TIRES, WHEELS, AND WEIGHT

		TESTS F, G & H	TEST J	TEST K
Rear Wheel: (each)	Type and Weight	Pressed Steel 150 lbs	Pressed Steel 150 lbs	Pressed Steel 145 lbs
	Liquid Ballast	361 lbs	None	None
	Added Cast Iron	720 lbs	None	None
Rear Tires:	No., Size & Ply	2, 11-38, 6 ply	2, 11-38, 6 ply	2, 10-36, 6 ply
	Type of Tread	Ground Grip	Ground Grip	Ground Grip
	Make	Firestone	Firestone	Firestone
	Air Pressure	16 lbs	16 lbs	16 lbs
Front Wheel: (each)	Type and Weight	Pressed Steel 27 lbs	Pressed Steel 27 lbs	Pressed Steel 27 lbs
	Liquid Ballast	22 lbs	None	None
	Added Cast Iron	None	None	None
Front Tires:	No., Size & Ply	2, 5.00-15, 4 ply	2, 5.00-15, 4 ply	2, 5.00-15, 4 ply
	Type of Tread	Guide Grip	Guide Grip	Guide Grip
	Make	Firestone	Firestone	Firestone
	Air Pressure	28 lbs	28 lbs	28 lbs
Height of Drawbar		19"	19 1/2"	18 1/2"
Static Weight:	Rear End	4625 lbs	2460 lbs	2370 lbs
	Front End	1265 lbs	1225 lbs	1230 lbs
Total Weight as tested (with operator)		6070 lbs	3865 lbs	3780 lbs

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 377

CHASSIS

Type Tricycle Serial No. 258390 Drive Enclosed gear
 Tread width: Rear 52" to 88" Front: (Top 12 1/2" and 19 3/8"
(Bottom 8 1/4" and 14 7/8"
 Advertised speeds, miles per hour: First 2.68 Second 3.74 Third 5.00
Fourth (1800 r.p.m.) 17.85 Reverse 2.40
 Belt Pulley: Diam. 13 1/2" Face 6 1/4" R.P.M. 838 Belt Speed 2960 f.p.m.
 Clutch: Make Borg and Beck Type Dry disc Operated by Foot
 Seat Pressed steel
 Brakes: Make Own Type Internal expanding
 Location Bull gear pinion
 Gear reduction (brake drum to rear wheel) 5.077 to 1
 Operated by Right foot on adjacent pedals, either independently or interlocked
 Locked by Ratch and latch
 Equalization None

MOTOR

Make Chrysler Serial No. T112-501-525 Type 6 cylinder, vertical
 Head L Mounting Crankshaft lengthwise Lubrication Pressure
 Bore and stroke 3 1/4" x 4 3/8" Rated R.P.M. (Drawbar 1500
(Belt 1400
 Port diameter valves: Inlet 1 13/32" Exhaust 1 9/32"
 Ignition: Type Battery Make Auto-Lite Distributor Model IGZ-EO6979
 Generator: Make Auto-Lite Model GM-4610A5
 Starter: Make Auto-Lite Model MAW-4013-A
 Carburetor: Make Marvel-Schebler Model TRX-22 Size 1"
 Governor: Make Novi Type Variable speed, centrifugal
 Air Cleaner: Make United Type Oil-washed, crimped wire filter
 Oil Filter: Make Purolator Products, Inc. Type Renewable waste-packed element
 Cooling medium temperature control: Fulton thermostat