

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

10-29-1952

Test 488: Cockshutt Model 50

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 488: Cockshutt Model 50" (1952). *Nebraska Tractor Tests*. 1003.
<https://digitalcommons.unl.edu/tractormuseumlit/1003>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

The Experiment Station
University of Nebraska College of Agriculture
W. V. Lambert, Director, Lincoln, Nebraska

Department of Agricultural Engineering
Dates of test: October 29 to November 6, 1952.
Manufacturer: COCKSHUTT FARM EQUIPMENT
CO. LTD., BRANTFORD, ONTARIO, CANADA.
Manufacturer's rating: Not rated.

NEBRASKA TRACTOR TEST NO. 488

COCKSHUTT 50*

BELT HORSEPOWER TESTS

| Hp | Crank shaft speed rpm | Fuel Consumption | | | Water used gal per hour | Temp Deg F | | Barometer inches of mercury | | |
|-------------------------------------------------------------------|--------------------------------|------------------|------------------|-------------------|----------------------------------|----------------|-------|--------------------------------------|-------|-------|
| | | Gal per hour | Hp-hr per gal | Lb per hp-hour | | Cooling med | Air | | | |
| TEST B—100% MAXIMUM LOAD—TWO HOURS | | | | | | | | | | |
| * 55.56 | 1650 | 5.003 | 11.11 | 0.549 | 0.00 | 175 | 61 | 28.780 | | |
| TEST C—OPERATING MAXIMUM LOAD—ONE HOUR | | | | | | | | | | |
| 52.18 | 1650 | 4.263 | 12.24 | 0.498 | 0.00 | 173 | 66 | 28.765 | | |
| TEST D—RATED LOAD—ONE HOUR | | | | | | | | | | |
| 49.24 | 1651 | 4.106 | 11.99 | 0.508 | 0.00 | 177 | 72 | 28.760 | | |
| TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average) | | | | | | | | | | |
| 49.40 | 1654 | 4.116 | 12.00 | 0.508 | ... | 177 | 72 | | | |
| 1.63 | 1797 | 1.713 | 0.95 | 6.405 | ... | 158 | 73 | | | |
| 26.15 | 1746 | 2.752 | 9.50 | 0.641 | ... | 162 | 74 | | | |
| 50.16 | 1571 | 4.071 | 12.32 | 0.495 | ... | 179 | 74 | | | |
| 13.31 | 1771 | 2.112 | 6.30 | 0.967 | ... | 160 | 76 | | | |
| 38.11 | 1703 | 3.407 | 11.19 | 0.545 | ... | 170 | 78 | | | |
| 29.79 | 1707 | 3.028 | 9.84 | 0.620 | 0.00 | 168 | 75 | 28.760 | | |
| TORQUE (at dynamometer) | | | | | | | | | | |
| RPM | 1651 | 1547 | 1448 | 1344 | 1250 | 1145 | 1043 | 942 | 844 | 754 |
| Lb-ft | 320.6 | 329.0 | 337.2 | 342.5 | 346.3 | 348.4 | 347.6 | 343.9 | 334.4 | 334.1 |

DRAWBAR HORSEPOWER TESTS

| Hp | Draw bar pull lb | Speed miles per hr | Crank shaft speed rpm | Slip of drive wheels % | Fuel Consumption | | | Water used gal per hour | Temp Deg F | | Barometer inches of mercury |
|----------------------------------------|---------------------------|-----------------------------|--------------------------------|------------------------------------|--------------------|---------------------|--------------------|-------------------------------------|---------------------|-----|--------------------------------------|
| | | | | | Gal per hour | Hp-hr per gal | Lb per hp-hr | | Cool- ing med | Air | |
| TEST F—100% MAXIMUM LOAD—4th Gear | | | | | | | | | | | |
| 51.59 | 4399 | 4.40 | 1651 | 7.96 | | Not Recorded | | | 158 | 40 | 29.390 |
| TEST G—OPERATING MAXIMUM LOAD | | | | | | | | | | | |
| 24.19 | 6463 | 1.40 | 1649 | 16.68 | | Not Recorded | | | 154 | 52 | 29.385 |
| 41.16 | 6303 | 2.45 | 1646 | 13.98 | | Not Recorded | | | 156 | 52 | 29.390 |
| +6.80 | 5022 | 3.49 | 1651 | 9.53 | | Not Recorded | | | 159 | 49 | 29.400 |
| 48.11 | 4069 | 4.43 | 1651 | 7.16 | | Not Recorded | | | 156 | 42 | 29.400 |
| 47.35 | 2860 | 6.21 | 1652 | 5.15 | | Not Recorded | | | 157 | 45 | 29.400 |
| 43.83 | 1546 | 10.63 | 1650 | 2.84 | | Not Recorded | | | 158 | 54 | 29.405 |
| TEST H—RATED LOAD—TEN HOURS—4th Gear | | | | | | | | | | | |
| 38.78 | 3246 | 4.48 | 1650 | 6.09 | 3.628 | 10.69 | 0.570 | 0.00 | 157 | 60 | 28.922 |
| TEST J—OPERATING MAXIMUM LOAD—4th Gear | | | | | | | | | | | |
| 37.77 | 3492 | 4.06 | 1652 | 15.59 | | Not Recorded | | | 148 | 45 | 29.140 |

TIRES, WHEELS and WEIGHT

| | Tests F, G, & H | Test J | Test K |
|---------------------------------------------|-----------------|-------------|--------|
| Rear wheels | | | |
| Type | Cast iron | Cast iron | |
| Liquid ballast | 576 lb each | None | |
| Added cast iron | 1960 lb each | None | |
| Rear tires | | | |
| No. and size | Two 14-34 | Two 14-34 | |
| Ply | 6 | 6 | |
| Air pressure | 20 lb | 12 lb | |
| Front wheels | | | |
| Type | Cast iron | Cast iron | |
| Liquid ballast | None | None | |
| Added cast iron | None | None | |
| Front tires | | | |
| No. and size | Two 7.50-16 | Two 7.50-16 | |
| Ply | 4 | 4 | |
| Air pressure | 28 lb | 28 lb | |
| Height of drawbar | 16½ inches | 18 inches | |
| Static weight | | | |
| Rear end | 9186 lb | 4115 lb | |
| Front end | 1758 lb | 1751 lb | |
| Total weight as tested with operator | 11,119 lb | 6041 lb | |

No smaller or lighter wheel equipment recommended by manufacturer.

HORSEPOWER SUMMARY

| | Draw- bar | Belt |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|
| 1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg) | 51.51 | 57.81 |
| 2. Observed maximum horsepower (tests F & B) | 51.59 | 55.56 |
| 3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings) | 38.63 | 49.14 |

We, the undersigned, certify that this is a true and correct report of official tractor test No. 488.

L. F. LARSEN
Engineer in Charge

C. W. SMITH
F. D. YUNG
L. W. HURLBUT
Board of Tractor
Test Engineers

FUEL, OIL and TIME Gasoline octane No ASTM 76 Research 82 (rating taken from oil company's typical inspection data); weight per gallon 6.094 lb Oil SAE 10 to motor 1.623 gal; drained from motor 0.806 gal Total time motor was operated 46½ hours.

CHASSIS Type standard Serial No 50142 Tread width rear 60" front 55" Wheel Base 86 9/16" Hydraulic control system direct engine drive with independent throw out control Adverised speeds mph first 1.52 second 2.57 third 3.53 fourth 4.32 fifth 5.95 sixth 9.85 reverse 2.1 and 4.75 Belt pulley diam 12" face 8½" rpm 997 Belt speed 3132 fpm Clutch single plate dry disc operated by foot pedal Seat spring cushion with padded back rest Brakes double disc brakes operated by two foot pedals Equalized by locking brakes together Power take-off "live" power take-off with independent clutch.

ENGINE Make Buda Type 6 cylinder vertical Serial No 355263 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and Stroke 3¼" x 4½" Rated rpm 1650 Compression ratio 6.6 to 1 Displacement 273 cu in Port Diameter Valves inlet 1½" exhaust 1½" Governor variable speed centrifugal Carburetor Size 1½" Ignition System battery Starting System 6 volt battery Air Cleaner oil washed wire mesh Muffler was used Oil Filter replaceable paper element Cooling medium temperature control thermostat.

REPAIRS and ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, and J were made with an operating setting of the carburetor (selected by the manufacturer) of 94.4% of maximum belt horsepower.

Engine ran unsteady during no load and ¼ load in Test E.

* Also designated as Co-op E5.

EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissible include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

BELT HORSEPOWER TESTS

TEST B: The throttle valve is held wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel economy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. *This more practical carburetor setting is used in all later tests except test F.* The throttle valve is held wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors, which have an altogether different fuel system.

TEST D: The throttle control lever is set so that the governor will maintain rated engine speed when rated load is applied. Rated load is 85% of 100% maximum, as obtained in test B, corrected to standard conditions.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

TEST E:

Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads of 20 minutes each: rated load, no load, $\frac{1}{2}$ rated load, maximum load at wide open throttle valve, $\frac{1}{4}$ and $\frac{3}{4}$ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

Torque, lb-ft at dynamometer, is obtained with wide open throttle and sufficient load is applied to give several readings.

DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instrument in the test car. All tests are made on the same dirt test course which is maintained by grading, sprinkling and rolling so that it remains very nearly the same throughout the season.

The same tires, wheels and weights are used for all tests except J and K.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in this test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 16%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated load the throttle control lever is set to maintain rated engine speed. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: Similar to test J except that the smallest tires and lightest wheels offered by the manufacturer are used.

