

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

1-1-1955

Test 561: Ford Model 660

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 561: Ford Model 660" (1955). *Nebraska Tractor Tests*. 1048.
<https://digitalcommons.unl.edu/tractormuseumlit/1048>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

The Experiment Station
University of Nebraska College of Agriculture
W. V. Lambert, Director, Lincoln, Nebraska

Department of Agricultural Engineering
Dates of test: September 21, 1955 to October 7, 1955
Manufacturer: FORD MOTOR COMPANY, BIRMINGHAM, MICHIGAN
Manufacturer's rating: Not rated

NEBRASKA TRACTOR TEST NO. 561

FORD 660

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer inches of mercury		
		Gal per hour	Hp-hr per gal	Lb per hp-hour		Cooling med	Air			
TEST B—100% MAXIMUM LOAD—TWO HOURS										
34.25	2201	3.172	10.80	0.567	0.00	183	58	29.060		
TEST C—OPERATING MAXIMUM LOAD—ONE HOUR										
32.34	2200	2.864	11.29	0.542	0.00	183	56	29.060		
TEST D—RATED LOAD—ONE HOUR										
30.19	2203	2.725	11.08	0.553	0.00	185	56	29.065		
TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average)										
30.31	2204	2.743	11.05	0.554	...	184	55		
1.85	2400	1.171	1.58	3.876	...	148	55		
16.03	2349	1.935	8.28	0.739	...	160	56		
30.25	2015	2.669	11.33	0.540	...	168	55		
8.07	2360	1.484	5.44	1.126	...	151	54		
23.58	2308	2.395	9.85	0.622	...	168	55		
18.35	2273	2.066	8.88	0.690	0.00	163	55	29.085		
TORQUE (At Dynamometer)										
Eng. rpm	2210	2072	1936	1804	1666	1546	1408	1276	1150	980
Lb-ft	208.8	212.1	214.6	216.3	218.8	220.0	220.9	228.4	234.5	234.5
Dyn rpm	820	768	718	669	618	573	522	473	426	362

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lb	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Water used gal per hour	Temp Deg F		Barometer inches of mercury
					Gal per hour	Hp-hr per gal	Lb per hp-hr		Cool- ing med	Air	
TEST H—RATED LOAD—TEN HOURS—3rd Gear											
22.36	1782	4.70	1995	4.79	2.226	10.04	0.610	0.00	178	74	28.479
TEST F—100% MAXIMUM LOAD											
28.23	2277	4.65	2003	6.32	3rd gear.....				183	70	28.660
TEST G—OPERATING MAXIMUM LOAD											
20.24	3859	1.97	2004	16.35	1st gear (part throttle).....				172	70	28.650
26.62	2930	3.41	1998	8.59	2nd gear.....				176	69	28.650
26.10	2100	4.66	1995	5.73	3rd gear.....				178	70	28.660
24.56	1394	6.61	2000	3.48	4th gear.....				177	75	28.480
22.10	693	11.96	1998	1.64	5th gear.....				174	71	28.480
TEST J—OPERATING MAXIMUM LOAD											
23.71	2017	4.41	2001	12.95	3rd gear.....				170	61	29.090
TEST K—OPERATING MAXIMUM LOAD											
19.88	1824	4.09	2001	17.15	3rd gear (part throttle).....				177	74	29.040

TIRES, WHEELS AND WEIGHT

	Tests F, G, & H	Test J	Test K
Rear wheels			
Type	Pressed steel	Pressed steel	Pressed steel
Liquid ballast	332 lb each	None	None
Added cast iron	579 lb each	None	None
Rear tires			
No. and size	Two 11-28	Two 11-28	Two 10-28
Ply	4	4	4
Air pressure	12 lb	12 lb	12 lb
Front wheels			
Type	Pressed steel	Pressed steel	Pressed steel
Liquid ballast	None	None	None
Added cast iron	None	None	None
Front tires			
No. and size	Two 5.50-16	Two 5.50-16	Two 5.50-16
Ply	4	4	4
Air pressure	28 lb	28 lb	28 lb
Height of drawbar	22 inches	23½ inches	22½ inches
Static weight			
Rear end	3580 lb	1758 lb	1736 lb
Front end	1162 lb	1162 lb	1140 lb
Total weight as tested with operator	4917 lb	3095 lb	3051 lb

FUEL, OIL and TIME Gasoline Octane No. ASTM 80.1 Research 85.7 (rating taken from oil company's typical inspection data) Weight per gallon 6.125 lb OIL SAE 20 To motor 1.242 gal Drained from motor 1.020 gal Total time motor was operated 39 hours.

CHASSIS Type Standard Serial No. 24432 Tread width rear 52" to 76" Front 52" to 80" Wheel base 74.5" Hydraulic control system direct engine drive Advertised speeds mph first 2.22 second 3.52 third 4.72 fourth 6.48 fifth 11.75 reverse 3.80 Belt pulley diam 9" Face 6½" rpm 1279 Belt speed 3015 fpm Clutch dual dry disc clutch operated by single foot pedal Seat pressed steel Brakes internal expanding shoes operated by two foot pedals located on right hand side of tractor Equalized by foot action only Power take-off constant running—controlled by secondary clutch.

ENGINE Make Ford Type 4 cylinder vertical Serial No. 24432 Crankshaft mounted lengthwise Head I Lubrication pressure Bore and stroke 3.4375" x 3.60" Rated rpm belt 2200 drawbar 2000 Compression ratio 6.6 to 1 Displacement 134 cu in Port diameter valves inlet 1.46" exhaust 1.26" Governor variable speed centrifugal fly ball Carburetor size ¾" Ignition system battery Starting system 6 volt battery Air cleaner oil washed wire mesh Muffler was used Oil filter full flow with replaceable paper element Cooling medium temperature control thermostat.

REPAIRS AND ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J, and K were made with an operating setting of the carburetor (selected by the manufacturer) of 94.2% of maximum belt horsepower.

HORSEPOWER SUMMARY

	Drawbar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F. and 29.92" Hg)	29.75	35.20
2. Observed maximum horsepower (tests F and B)	28.23	34.25
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings)	22.31	29.92

We, the undersigned, certify that this is a true and correct report of official tractor test No. 561.

L. F. LARSEN
Engineer-In-Charge

L. W. HURLBUT
G. W. STEINBRUEGGE
J. J. SULEK
Board of Tractor
Test Engineers

EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissible include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

BELT HORSEPOWER TESTS

TEST B: The throttle valve is held wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel economy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. *This more practical carburetor setting is used in all later tests except test F.* The throttle valve is held wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors, which have an altogether different fuel system.

TEST D: The throttle control lever is set so that the governor will maintain rated engine speed when rated load is applied. Rated load is 85% of 100% maximum, as obtained in test B, corrected to standard conditions.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

TEST E:

Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads, of 20 minutes each: rated load, no load, $\frac{1}{2}$ rated load, maximum load at wide open throttle valve, $\frac{1}{4}$ and $\frac{3}{4}$ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

Torque, lb-ft at dynamometer, is obtained with wide open throttle and sufficient load is applied to give several readings.

DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instrument in the test car. All tests are made on the same dirt test course which is maintained by grading, sprinkling and rolling

so that it remains very nearly the same throughout the season. The same tires, wheels and weights are used for all tests except J and K.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in this test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 16%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated load the throttle control lever is set to maintain rated engine speed. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: Similar to test J except that the smallest tires and lightest wheels offered by the manufacturer are used.

