

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

10-8-1958

Test 675: McCormick-Farmall Model 560 (LPG)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 675: McCormick-Farmall Model 560 (LPG)" (1958). *Nebraska Tractor Tests*. 1104.

<https://digitalcommons.unl.edu/tractormuseumlit/1104>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Department of Agricultural Engineering
Dates of test: October 8, 1958 to October 20, 1958
Manufacturer: INTERNATIONAL HARVESTER COMPANY, CHICAGO, ILLINOIS
Manufacturer's rating: Not Rated

NEBRASKA TRACTOR TEST NO. 675

MC CORMICK FARMALL 560 LPG

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Temp. Deg. F.			Barometer inches of mercury
		Gal per hr	Hp-hr per gal	Lb per hp-hr	Cooling medium	Air wet bulb	Air dry bulb	
TEST B—100% MAXIMUM POWER—TWO HOURS								
60.11	1800	6.480	9.28	0.458	171	63	71	29.053
TEST C—OPERATING MAXIMUM POWER—ONE HOUR								
57.06	1800	5.864	9.73	0.437	167	61	69	29.028
TEST D—RATED POWER—ONE HOUR								
53.44	1871	5.633	9.49	0.448	166	61	70	29.025
TEST E—VARYING POWER—TWO HOURS (20 minute runs; last line average)								
53.55	1875	5.612	9.54	0.445	167	62	71
1.40	1930	1.892	0.74	5.743	154	63	72
27.41	1913	3.769	7.27	0.584	162	64	73
56.81	1800	5.816	9.77	0.435	171	64	74
13.94	1944	2.781	5.01	0.848	158	64	75
40.43	1884	4.694	8.61	0.493	166	65	75
32.26	1891	4.094	7.88	0.539	163	63	73	29.027

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lbs	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Temp. Deg. F.			Barometer inches of mercury
					Gal per hr	Hp-hr per gal	Lb per hp-hr	Cooling med	Air wet bulb	Air dry bulb	
TEST H—RATED POWER—TEN HOURS—3rd Gear											
43.96	2968	5.55	1889	3.49	5.140	8.55	0.497	164	53	66	29.064
TEST F—100% MAXIMUM POWER											
55.02	3958	5.21	1798	4.92	3rd Gear			180	64	77	28.825
TEST G—OPERATING MAXIMUM POWER											
38.08	7467	1.91	1801	13.66	1st Gear (prt thrtl)			165	61	70	28.855
51.70	5318	3.65	1800	6.87	2nd Gear			176	64	77	28.825
51.53	3689	5.24	1800	4.43	3rd Gear			172	65	78	28.840
51.75	2628	7.38	1803	3.24	4th Gear			168	65	78	28.840
47.12	1059	16.69	1795	1.42	5th Gear			172	65	78	28.840
25.74	7524	1.28	1803	14.34	1st Gear TA (prt thrtl)			164	61	70	28.855
43.63	7196	2.27	1800	13.89	2nd Gear TA (prt thrtl)			165	60	66	28.850
49.89	5450	3.43	1799	7.20	3rd Gear Torq. Amp.			176	64	77	28.825
50.24	3841	4.90	1799	4.50	4th Gear Torq. Amp.			175	65	78	28.840
49.61	1657	11.23	1804	2.30	5th Gear Torq. Amp.			172	65	78	28.840
TEST J—OPERATING MAXIMUM POWER											
48.83	3655	5.08	1795	7.62	3rd Gear			167	60	70	28.420
TEST K—SPEED-PULL CHARACTERISTIC											
Pounds Pull		2968	3689	3700	3800	3800	3800	3850	3750		
Horsepower		43.96	51.53	46.4	41.5	36.5	36.5	31.8	26.0		
Miles Per Hour		5.55	5.24	4.7	4.1	3.6	3.6	3.1	2.6		

TIRES, WHEELS AND WEIGHT

	Tests F, G, H & K	Test J
Rear wheels		
Type	Cast Iron	Cast Iron
Liquid ballast	794 lb each	None
Added cast iron	441 lb each	None
Rear tires		
No. and size	Two 15.5-38	Two 15.5-38
Ply	6	6
Air pressure	18 lb	14 lb
Front wheels		
Type	Pressed Steel	Pressed Steel
Liquid ballast	None	None
Added cast iron	88 lb each	None
Front tires		
No. and size	Two 6.50-16	Two 6.50-16
Ply	6	6
Air pressure	32 lb	32 lb
Height of drawbar	21 inches	22 inches
Static weight		
Rear end	7010 lb	4540 lb
Front end	2130 lb	1955 lb
Total weight as tested with operator	9315 lb	6670 lb

HORSEPOWER SUMMARY

	Drawbar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg)	58.04	62.55
2. Observed maximum horsepower (tests F and B)	55.02	60.11
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (ASAE and SAE ratings)	43.53	53.17

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. 675.

L. F. LARSEN
Engineer-in-Charge

L. W. HURLBUT, Chairman
G. W. STEINBRUEGGE
J. J. SULEK
Board of Tractor
Test Engineers

EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissible include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

BELT HORSEPOWER TESTS

TEST B: The manual throttle control lever is set so that the throttle valve is held wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel economy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. *This more practical carburetor setting is used in all later tests except test F.* The throttle valve is wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors which have an altogether different fuel system.

TEST D: The manual throttle control lever is set the same as for tests B and C allowing the governor to control engine speed at part throttle. Load is applied until 85% of maximum corrected horsepower found in test B is obtained.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

TEST E: Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads, of 20 minutes each; rated load, no load, $\frac{1}{2}$ rated load, maximum load at wide open throttle valve, $\frac{1}{4}$ and $\frac{3}{4}$ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instrument in the test car. When rubber tires are used, all tests are made on the concrete test course. The same tires, wheels and weights are used for all tests except J. All crawler type tractors are tested on an earthen test course which is maintained by grading, sprinkling and rolling so that it remains very nearly the same for each test.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in the test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The manual throttle control lever is set so that the throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 15%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated horsepower the manual throttle control lever is set the same as in tests F and G allowing the governor to maintain engine speed at part throttle. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: This is intended to show the pull, horsepower, and travel speed of the tractor at rated horsepower (taken from test H); maximum horsepower (taken from test G); and at least four other conditions obtained by reducing travel speed in 10% increments by overload.

