

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

---

8-18-1960

## Test 753: International T-5 (Gasoline)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, [tractortestlab@unl.edu](mailto:tractortestlab@unl.edu)

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Nebraska Tractor Test Lab, "Test 753: International T-5 (Gasoline)" (1960). *Nebraska Tractor Tests*. 1174. <https://digitalcommons.unl.edu/tractormuseumlit/1174>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA TRACTOR TEST 753 - INTERNATIONAL T-5 GASOLINE

The University of Nebraska Agricultural Experiment Station

E. F. Frolik, Dean and Acting Director, Lincoln, Nebraska

## POWER TAKE-OFF PERFORMANCE

Hp	Crank shaft speed rpm	Fuel Consumption Gal per hr	Lb per hp-hr	Hp-hr per gal	Temp Cool- ing med	Degrees F Air wet bulb	Air dry bulb	Barometer inches of mercury
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>								
Rated Engine Speed—Two Hours								
36.01*	2000	2.932	0.508	12.28	184	69	75	28.780
<b>VARYING POWER AND FUEL CONSUMPTION—TWO HOURS</b>								
32.33	2112	2.852	0.550	11.34	178	69	75	.....
0.00	2206	1.087	.....	.....	155	69	74	.....
16.43	2148	1.948	0.740	8.43	165	69	75	.....
35.96	2000	2.949	0.511	12.19	183	69	75	.....
8.37	2184	1.539	1.147	5.44	159	69	75	.....
24.46	2132	2.376	0.606	10.29	172	70	76	.....
Av 19.59	2130	2.125	0.677	9.22	169	69	75	28.788

## DRAWBAR PERFORMANCE

Hp	Draw- bar pull lbs	Speed miles per hr	Crank shaft speed rpm	Slip of drivers %	Fuel Consumption		Temperature	Degrees F			
					Gal per hr	Lb hp hr	Hp-hr per gal	Cooling medium	Air wet bulb	Air dry bulb	Barometer inches of mercury
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours—2nd Gear											
28.59	4858	2.21	2010	2.80	2.899	0.632	9.86	205	79	93	28.755
75% of Pull at Maximum Power—Ten Hours—2nd Gear											
23.56	3781	2.34	2101	1.71	2.581	0.683	9.13	188	76	86	28.759
50% of Pull at Maximum Power—Two Hours—2nd Gear											
16.13	2529	2.39	2137	1.13	2.148	0.830	7.51	182	82	90	28.730
MAXIMUM POWER WITH BALLAST											
27.47	7430	1.39	2020	5.73	1st Gear.....			190	76	87	28.795
29.80	5050	2.21	2000	2.20	2nd Gear.....			187	72	77	28.795
29.18	3078	3.55	2006	1.17	3rd Gear.....			189	73	80	28.780
27.31	2153	4.76	1997	0.95	4th Gear.....			190	76	84	28.780
24.00	1383	6.51	1999	0.46	5th Gear.....			190	76	84	28.780
28.29	7300	1.45	2004	4.48	2nd Gear Torque-Amp			190	77	86	28.750
29.01	4594	2.37	2003	2.23	3rd Gear Torque-Amp			190	74	81	28.780
28.35	3323	3.20	2001	1.20	4th Gear Torque-Amp			194	74	81	28.780
27.82	2370	4.40	2009	0.74	5th Gear Torque-Amp			190	76	84	28.780
VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—2nd Gear											
Pounds pull			5050	5250	5500	5700	5650	5400			
Horsepower			29.8	28.0	26.4	22.8	19.6	15.8			
Miles per hour			2.2	2.0	1.8	1.5	1.3	1.1			

Department of Agricultural Engineering

Dates of Test: August 18 to September 3, 1960

Manufacturer: INTERNATIONAL HARVESTER  
COMPANY OF CANADA LTD., HAMILTON,  
ONTARIO, CANADA

Manufacturer's Power Rating: Not Rated

**FUEL, OIL and TIME** Fuel regular gasoline Octane No Motor 84 Research 92 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7492 Weight per gallon 6.237 lb Oil SAE 10W-30 API service classification MS, DM To motor 1.238 gal Drained from motor 1.070 gal Transmission lubricant I. H. Hy Tran Final Drive lubricant SAE 90 Type gear lube Total time engine was operated 44½ hours.

**ENGINE Make** International Harvester Gasoline Type 4 cylinder vertical Serial No 21288 Crankshaft mounted lengthwise Rated rpm 2000 Bore and stroke 3¼" x 4½/16" Compression ratio 7.5 to 1 Displacement 134.8 cu in Carburetor size 7/8" Ignition system battery Cranking system 6 volt battery Lubrication pressure Air cleaner oil washed wire screen Oil filter replaceable treated paper element Muffler was used Cooling medium temperature control thermostat.

**CHASSIS Type** tracklayer Serial No 2328-ADT Tread width 48" Wheel base 68" Drawbar height 13" Measured length of track 17½ ft Cleats integral with shoes Cleats per track 35 Size of cleats 12" x 2" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 31.55" Vertical distance above roadway 18.77" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission fixed ratio operator controlled partial range power shifting Advertised speeds mph first 1.48 second 2.26 third 3.58 fourth 4.79 fifth 6.54 reverse 2.12 (using torque-amplifier) first 1.00 second 1.53 third 2.42 fourth 3.23 fifth 4.31 reverse 1.43 Clutch single plate dry disc operated by foot pedal Brakes contracting bands operated independently by two hand levers or by one foot pedal Steering hand levers controlling multiple disc clutches and brakes Turning space diameter (with brake applied) right 153" left 153" Belt pulley 1270 rpm at 2000 engine rpm diam 9½" face 6⅝" Belt speed 3160 fpm Power take-off 980 rpm at 2000 engine rpm.

**TOTAL WEIGHT** with operator 7005 lb including front end weights 375 lbs, and crankcase guard 100 lbs.

**REPAIRS and ADJUSTMENTS** No repairs or adjustments.

**REMARKS** All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

First gear torque amplifier drive was not run as it was necessary to limit the pull in first gear direct drive to avoid excessive slippage.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 753.

L. F. LARSEN

Engineer-in-Charge

L. W. HURLBUT, Chairman  
G. W. STEINBRUEGGE  
J. J. SULEK  
Board of Tractor  
Test Engineers

# EXPLANATION OF TEST REPORT

## GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

## PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

## BELT OR POWER TAKE-OFF PERFORMANCE

**Maximum Power and Fuel Consumption.** The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

**Varying Power and Fuel Consumption.** Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque,  $\frac{1}{2}$  the 85% torque; maximum power;  $\frac{1}{4}$  and  $\frac{3}{4}$  of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

## DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

**Varying Power and Fuel Consumption With Ballast.** The varying power runs are made to show the effect of speed-control devices (engine governor, automatic transmissions, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree

turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

**Maximum Power with Ballast.** Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

**Maximum Power Without Ballast.** All added ballast is removed from the tractor. The maximum drawbar power of the tractor is determined by the same procedure used for getting maximum power with ballast. The gear (or travel speed) is the same as that used in the 10-hour test.

**Varying Power and Travel Speed with Ballast.** Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions; (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.



International T-5 Gasoline