

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

4-24-1961

Test 792: Minneapolis-Moline Gvi (Diesel)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 792: Minneapolis-Moline Gvi (Diesel)" (1961). *Nebraska Tractor Tests*. 1204.

<https://digitalcommons.unl.edu/tractormuseumlit/1204>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 792 - MINNEAPOLIS - MOLINE Gvi DIESEL

The University of Nebraska Agricultural Experiment Station

E. F. Frolik, Dean; A.W. Epp, Acting Director, Lincoln, Nebraska

POWER TAKE-OFF PERFORMANCE

Hp	Crank shaft speed rpm	Fuel Consumption		Hp-hr per gal	Temp. Degrees F			Barometer inches of mercury
		Gal per hr	Lb per hp-hr		Cool- ing med	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
Rated Engine Speed—Two Hours								
78.49	1500	5.419	0.477	14.48	191	57	75	29.102
Standard Power Take-off Speed (540 rpm)—One Hour								
67.09	1199	4.535	0.467	14.79	193	57	75	29.085
VARYING POWER AND FUEL CONSUMPTION—TWO HOURS								
69.31	1558	4.777	0.476	14.51	187	58	76
0.00	1654	1.372	165	56	74
35.49	1596	2.918	0.568	12.16	171	57	75
78.64	1501	5.428	0.477	14.49	191	58	77
18.06	1624	2.076	0.794	8.70	167	57	75
52.39	1570	3.752	0.495	13.96	175	58	76
Av 42.32	1584	3.387	0.553	12.49	176	57	75	29.070

DRAWBAR PERFORMANCE

Hp	Draw- bar pull lbs	Speed miles per hr	Crank shaft speed rpm	Slip of driv- ers %	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of mercury
					Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours—3rd Gear											
66.06	5116	4.84	1500	6.24	5.299	0.554	12.47	178	60	68	28.743
75% of Pull at Maximum Power—Ten Hours—3rd Gear											
54.21	3966	5.13	1559	4.51	4.425	0.564	12.25	169	48	54	28.936
50% of Pull at Maximum Power—Two Hours—3rd Gear											
36.63	2601	5.28	1579	2.79	3.377	0.637	10.85	169	61	72	28.763
MAXIMUM POWER WITH BALLAST											
63.82	9023	2.65	1500	14.86	1st Gear.....		177	55	60		28.690
68.06	6284	4.06	1501	8.14	2nd Gear.....		177	55	60		28.690
68.30	5308	4.83	1501	6.44	3rd Gear.....		173	58	64		28.730
68.22	3602	7.10	1499	4.47	4th Gear.....		173	58	64		28.730
MAXIMUM POWER WITHOUT BALLAST											
67.02	5328	4.72	1500	10.36	3rd Gear.....		177	53	64		29.065
VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—3rd Gear											
Pounds pull			5300		5600		5650		5550		5150
Horsepower			68.3		64.2		58.8		51.2		42.9
Miles per hour			4.8		4.3		3.9		3.4		2.9

TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 18.4-34;6;16	Two 18.4-34;6;16
Ballast	—Liquid	1048 lb each	None
	—cast iron	1140 lb each	None
Front tires	—No, size, ply & psi	Two 7.50-18;4;24	Two 7.50-18;4;24
Ballast	—Liquid	None	None
	—cast iron	None	None
Height of drawbar		15 1/2 inches	17 1/2 inches
Static weight	—Rear	9875 lb	5500 lb
	—Front	2645 lb	2660 lb
Total weight with operator		12,695 lb	8335 lb

Department of Agricultural Engineering

Dates of Test: April 24 to May 9, 1961

Manufacturer: MOTEC INDUSTRIES INC., HOPKINS, MINNESOTA

Manufacturer's Power Rating: Not Rated

FUEL, OIL and TIME Fuel No 2 Diesel Cetane No 54 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.8297 Weight per gallon 6.908 lb Oil SAE 10W-30 API service classification MS, DM To motor 3.029 gal Drained from motor 2.285 gal Transmission and final-drive lubricant SAE 90 Type E.P. gear lubricant Total time engine was operated 40 1/2 hours.

ENGINE Make Minneapolis-Moline Diesel Type 6 cylinder vertical Serial No 16401733 Crankshaft mounted lengthwise Rated rpm 1500 Bore and stroke 4 1/4" x 5" Compression ratio 14.9 to 1 Displacement 425.5 cu in Cranking system 12 volt electric (three 12 volt batteries) Lubrication pressure Air cleaner oil washed wire screen Oil filter replaceable paper element Fuel filter two replaceable paper elements Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No 16201489 Tread width rear 64 1/2" front 54 1/4" Wheel base 96 3/16" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 32.1" Vertical distance above roadway 37.1" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 3.1 second 4.4 third 5.1 fourth 7.4 fifth 17.1 reverse 2.4 Clutch double disc over center operated by hand lever Brakes double disc operated by two foot pedals Steering power assisted Turning radius (on concrete surface with brake applied) right 196" left 196" (on concrete surface without brake) right 229" left 229" Turning space diameter (on concrete surface with brake applied) right 408" left 408" (on concrete surface without brake) right 474" left 474" Belt pulley 741 rpm at 1300 engine rpm diam 16" face 7" Belt speed 3110 fpm Power take-off 675 rpm at 1500 engine rpm.

REPAIRS and ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

Fifth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 792.

L. F. LARSEN

Engineer-in-Charge

L. W. HURLBUT, Chairman

G. W. STEINBRUEGGE

J. J. SULEK

Board of Tractor
Test Engineers

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

BELT OR POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effect of speed-control devices (engine governor, automatic transmissions, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree

turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Maximum Power Without Ballast. All added ballast is removed from the tractor. The maximum drawbar power of the tractor is determined by the same procedure used for getting maximum power with ballast. The gear (or travel speed) is the same as that used in the 10-hour test.

Varying Power and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the **Nebraska Tractor Tests** write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.



Minneapolis-Moline Gvi Diesel