

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1963

Test 833: Minneapolis-Moline G706 (Diesel)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 833: Minneapolis-Moline G706 (Diesel)" (1963). *Nebraska Tractor Tests*. 1233.

<https://digitalcommons.unl.edu/tractormuseumlit/1233>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 833 - MINNEAPOLIS-MOLINE G706 DIESEL

(ALSO MASSEY-FERGUSON MF97 FOUR-WHEEL DRIVE DIESEL)

The University of Nebraska Agricultural Experiment Station
E. F. Frolik, Dean; H. H. Kramer, Director, Lincoln, Nebraska

POWER TAKE-OFF PERFORMANCE

Hp	Crankshaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	

MAXIMUM POWER AND FUEL CONSUMPTION

Rated Engine Speed—Two Hours								
101.68	1600	7.538	0.511	13.49	181	56	75	29.000
Standard Power Take-off Speed (540 rpm)—One Hour								
81.68	1200	5.854	0.494	13.95	183	56	75	28.983

VARYING POWER AND FUEL CONSUMPTION—TWO HOURS

89.90	1664	6.324	0.485	14.22	172	58	77
0.00	1765	1.818	140	56	74
46.35	1716	3.888	0.579	11.92	167	57	75
100.99	1600	7.528	0.514	13.42	185	58	77
23.49	1740	2.796	0.821	8.40	152	56	73
68.65	1693	4.975	0.500	13.80	172	57	75
Av 54.90	1696	4.555	0.572	12.05	165	57	75	28.947

DRAWBAR PERFORMANCE

Hp	Draw-bar pull lbs	Speed miles per hr	Crankshaft speed rpm	Slip of drivers %	Fuel Consumption		Hp-hr per gal	Temp Degrees F			Barometer inches of Mercury
					Gal per hr	Lb per hp-hr		Cooling med	Air wet bulb	Air dry bulb	

VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST

Maximum Available Power—Two Hours—3rd Gear											
87.83	6553	5.03	1598	4.79	7.439	0.584	11.81	179	49	58	29.165
75% of Pull at Maximum Power—Ten Hours—3rd Gear											
70.44	5013	5.27	1656	3.68	5.848	0.573	12.05	181	58	72	28.510
50% of Pull at Maximum Power—Two Hours—3rd Gear											
47.75	3272	5.47	1700	2.58	4.440	0.641	10.75	171	50	62	29.148

MAXIMUM POWER WITH BALLAST

87.99	11491	2.87	1605	10.55	1st Gear	172	46	53	29.200
89.19	7878	4.25	1600	6.11	2nd Gear	180	48	56	29.185
89.13	6680	5.00	1597	5.02	3rd Gear	174	50	60	29.195
88.73	4521	7.36	1601	3.22	4th Gear	179	48	56	29.185

MAXIMUM POWER WITHOUT BALLAST

85.57	6613	4.85	1601	10.68	3rd Gear	188	55	71	28.420
-------	------	------	------	-------	----------	-------	-----	----	----	--------

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—3rd Gear

Pounds pull	6680	6965	7275	7487	7355	7029
Horsepower	89.13	83.35	77.51	69.38	58.37	46.86
Crankshaft speed rpm	1597	1435	1279	1115	954	799
Miles per hour	5.00	4.49	4.00	3.48	2.98	2.50
Slip of drivers, %	5.02	5.30	5.43	5.70	5.57	5.16

TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 23.1-26; 8; 16	Two 23.1-26; 8; 16
Ballast	—Liquid	1550 lb each	None
	—Cast iron	2000 lb each	None
Front tires	—No, size, ply & psi	Two 9.5-24; 6; 28	Two 9.5-24; 6; 28
Ballast	—Liquid	None	None
	—Cast iron	None	None
Height of drawbar		11½ inches	15 inches
Static weight	—Rear	12130 lb	5030 lb
	—Front	3840 lb	3960 lb
Total weight with operator		16145 lb	9165 lb

Department of Agricultural Engineering

Dates of Test: April 6 to April 17, 1963

Manufacturer: MINNEAPOLIS-MOLINE, INC.,
HOPKINS, MINNESOTA

Manufacturer's Power Rating: Not rated

FUEL, OIL and TIME Fuel No 2 Diesel Cetane No 56.7 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.8285 Weight per gallon 6.898 lb Oil SAE 20-20W API service classification MS, DM To motor 3.650 gal Drained from motor 2.168 gal Transmission and final-drive lubricant SAE 90 Type EP Total time engine was operated 52 hours.

ENGINE Make Minneapolis-Moline Diesel Type 6 cylinder vertical Serial No 23700186 Crankshaft mounted lengthwise Rated rpm 1600 Bore and stroke 4½" x 5" Compression ratio 14.8 to 1 Displacement 504 cu in Cranking system 12 volt electric (three 12 volt batteries) Lubrication pressure Air cleaner oil washed wire screen Oil filter two replaceable pleated paper elements Fuel filter primary filter with replaceable cotton element and secondary filter with replaceable paper element Muffler was used Cooling medium temperature control two thermostats.

CHASSIS Type 4-wheel drive Serial No 23900101 Tread width rear 72¼" front 68¼" Wheel base 84½" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 32.8" Vertical distance above roadway 35" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 3.3 second 4.7 third 5.5 fourth 7.9 fifth 18.3 reverse 2.56 Clutch double disc over center operated by hand lever Brakes double disc operated by two foot pedals Steering mechanical with power assist Turning radius (on concrete surface with brake applied) right 171" left 169" (on concrete surface without brake) right 251" left 252" Turning space diameter (on concrete surface with brake applied) right 338" left 342" (on concrete surface without brake) right 512" left 513" Belt pulley 741 rpm at 1300 engine rpm diam 16" face 7" Power take-off 540 rpm at 1200 engine rpm Belt speed 3110 fpm.

REPAIRS and ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

Fifth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 833.

L. F. LARSEN
Engineer-in-Charge

L. W. HURLBUT, Chairman
G. W. STEINBRUEGGE
J. J. SULEK
Board of Tractor Test
Engineers

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

BELT OR POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effect of speed-control devices (engine governor, automatic trans-

mission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Maximum Power Without Ballast. All added ballast is removed from the tractor. The maximum drawbar power of the tractor is determined by the same procedure used for getting maximum power with ballast. The gear (or travel speed) is the same as that used in the 10-hour test.

Varying Power and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.



Minneapolis-Moline G706 Diesel