

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1963

Test 858: Farmall 706 (Gasoline)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 858: Farmall 706 (Gasoline)" (1963). *Nebraska Tractor Tests*. 1248.
<https://digitalcommons.unl.edu/tractormuseumlit/1248>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 858 - FARMALL 706 GASOLINE

The University of Nebraska Agricultural Experiment Station
E. F. Frolik, Dean; H. H. Kramer, Director, Lincoln, Nebraska

POWER TAKE-OFF PERFORMANCE

Hp	Crank- shaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury	
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb		
MAXIMUM POWER AND FUEL CONSUMPTION									
Rated Engine Speed—Two Hours									
73.82	2300	5.741	0.477	12.86	176	55	75	29.130	
Standard Power Take-off Speed (1000 rpm)—One Hour									
68.77	2071	5.224	0.466	13.16	175	54	75	29.120	
VARYING POWER AND FUEL CONSUMPTION—TWO HOURS									
66.62	2442	5.482	0.505	12.15	172	54	75	
0.00	2578	2.044	163	52	71	
34.15	2503	3.702	0.665	9.22	170	52	73	
74.24	2300	5.770	0.477	12.87	176	54	75	
17.44	2556	2.890	1.017	6.03	167	53	73	
50.84	2485	4.621	0.558	11.00	172	53	74	
Av	40.55	2477	4.085	0.618	9.93	170	53	74	29.120

DRAWBAR PERFORMANCE

Hp	Drawbar pull lbs	Speed miles per hr	Crankshaft speed rpm	Slip of drivers %	Fuel Consumption			Temp Degrees F			Barometer inches of Mercury
					Gal per hr	Lb per hp-hr	Hp-hr per gal	Cooling med	Air wet bulb	Air dry bulb	

VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST

Maximum Available Power—Two Hours—10th Gear. (2nd Hi-TA)											
66.18	4783	5.19	2295	6.25	5.923	0.549	11.17	182	36	39	29.173
75% of Pull at Maximum Power—Ten Hours—10th Gear (2nd Hi-TA)											
54.29	3593	5.67	2458	4.46	5.196	0.587	10.45	181	32	36	29.150
50% of Pull at Maximum Power—Two Hours—10th Gear (2nd Hi-TA)											
38.13	2456	5.82	2495	3.31	4.166	0.670	9.15	180	34	37	29.170

MAXIMUM POWER WITH BALLAST

52.93	7976	2.49	2437	14.92	5th Gear (3rd Lo-TA)	178	52	65	28.635
62.19	7123	3.27	2300	10.99	6th Gear (4th Lo-TA)	182	28	30	29.220
63.17	6448	3.67	2303	9.20	7th Gear (3rd Lo-DD)	181	28	30	29.220
65.00	6441	3.78	2299	9.33	8th Gear (1st Hi-TA)	181	30	33	29.220
64.25	4785	5.04	2296	6.55	9th Gear (4th Lo-DD)	184	30	33	29.220
66.51	4793	5.20	2299	6.21	10th Gear (2nd Hi-TA)	181	36	40	29.170
65.10	4224	5.78	2299	5.54	11th Gear (1st Hi-DD)	179	33	36	29.180
64.88	3124	7.79	2300	4.23	12th Gear (2nd Hi-DD)	179	33	36	29.180
65.23	2637	9.28	2304	3.81	13th Gear (3rd Hi-TA)	180	33	36	29.180
63.25	1891	12.54	2305	2.52	14th Gear (4th Hi-TA)	178	34	39	29.180
61.86	1680	13.81	2301	2.23	15th Gear (3rd Hi-DD)	178	34	39	29.180

MAXIMUM POWER WITHOUT BALLAST

63.63	4681	5.10	2302	7.30	10th Gear (2nd Hi-TA)	182	49	57	29.000
-------	------	------	------	------	-----------------------	-----	----	----	--------

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST 10th Gear (2nd Hi-TA)

Pounds pull	4793	4868	4969	4992	5008	4941
Horsepower	66.51	60.36	54.43	48.09	41.01	33.75
Crankshaft speed rpm	2299	2062	1825	1606	1356	1138
Miles per hour	5.20	4.65	4.11	3.61	3.07	2.56
Slip of drivers %	6.21	6.62	6.75	6.75	6.75	6.75

TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 15.5-38; 8; 20	Two 15.5-38; 8; 14
Ballast	—Liquid	783 lb each	None
	—Cast iron	None	None
Front tires	—No, size, ply & psi	Two 6.50-16; 6; 32	Two 6.50-16; 6; 32
Ballast	—Liquid	None	None
	—Cast iron	None	None
Height of drawbar		20½ inches	20 inches
Static weight	—Rear	7575 lb	6010 lb
	—Front	2145 lb	2100 lb
Total weight with operator		9895 lb	8285 lb

Department of Agricultural Engineering

Dates of Test: October 30 to November 20, 1963

Manufacturer: INTERNATIONAL HARVESTER COMPANY, CHICAGO, ILLINOIS

Manufacturer's Power Rating: Not rated

FUEL OIL and TIME Fuel regular gasoline Octane No Motor 84 Research 92.8 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7370 Weight per gallon 6.135 lb Oil SAE 10W-20W-30 API service classification MS To motor 2.232 gal Drained from motor 2.053 gal Transmission and final-drive lubricant IH Hy-Tran fluid Total time engine was operated 42 hours.

ENGINE Make International Gasoline Type 6 cylinder vertical Serial No 2222 Crankshaft mounted lengthwise Rated rpm 2300 Bore and stroke 3⁹/₁₆" x 4²⁵/₆₄" Compression ratio 7.6 to 1 Displacement 263 cu in Carburetor size 1½" Ignition system battery Cranking system 12 volt electric Lubrication pressure Air cleaner two stage dry type with automatic dust unloader using replaceable pleated paper element Oil filter full flow replaceable paper element Oil cooler radiator for transmission and hydraulic oil Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type Tricycle Serial No 1392S-Y Tread width rear 56" to 94" front 8" or 16" Wheel base 97.5" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from centerline of rear wheels 26.5" Vertical distance above roadway 33.9" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio with partial range operator controlled power shifting Advertised speeds mph first 1.17 second 1.55 third 1.71 fourth 2.28 fifth 2.70 sixth 3.60 seventh 3.95 eighth 4.08 ninth 5.27 tenth 5.43 eleventh 5.98 twelfth 7.96 thirteenth 9.42 fourteenth 12.57 fifteenth 13.81 sixteenth 18.43 Reverse first 2.01 second 2.67 third 2.94 fourth 3.91 fifth 4.63 sixth 6.18 seventh 6.79 eighth 9.06 Clutch single plate dry disc operated by foot pedal Brakes dry disc hydraulically power actuated operated by two foot pedals Steering hydraulic with power assist Turning radius (on concrete surface with brake applied) right 111" left 111" (on concrete surface without brake) right 116" left 117" Turning space diameter (on concrete surface with brake applied) right 236" left 237" (on concrete surface without brake) right 248" left 250" Belt pulley 1067 rpm at 2100 engine rpm diam 11" face 7.5" Belt speed 3073 fpm Power take-off 539 or 1014 rpm at 2100 engine rpm.

REPAIRS and ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

First, second, third, and fourth gears were not run as it was necessary to limit the pull in fifth gear to avoid excessive wheel slippage. Sixteenth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 858.

L. F. LARSEN

Engineer-in-Charge

L. W. HURLBUT, Chairman

G. W. STEINBRUEGGE

J. J. SULEK

Board of Tractor Test Engineers

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

BELT OR POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effect of speed-control devices (engine governor, automatic trans-

mission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Maximum Power Without Ballast. All added ballast is removed from the tractor. The maximum drawbar power of the tractor is determined by the same procedure used for getting maximum power with ballast. The gear (or travel speed) is the same as that used in the 10-hour test.

Varying Power and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.



Farmall 706 Gasoline