

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

---

10-8-1965

## Test 920: Case 941 GP (Gasoline)

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, [tractortestlab@unl.edu](mailto:tractortestlab@unl.edu)

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Nebraska Tractor Test Lab, "Test 920: Case 941 GP (Gasoline)" (1965). *Nebraska Tractor Tests*. 1297.  
<https://digitalcommons.unl.edu/tractormuseumlit/1297>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA TRACTOR TEST 920 - CASE 941 GP GASOLINE

## POWER TAKE-OFF PERFORMANCE

Hp	Crank- shaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
*								

## DRAWBAR PERFORMANCE

Hp	Draw- bar pull lbs	Speed miles per hr	Crank- shaft speed rpm	Slip of drivers %	Fuel Consumption		Hp-hr per gal	Temp Degrees F			
					Gal per hr	Lb per hp-hr		Cool- ing med	Air wet bulb	Air dry bulb	Barom- eter inches of Mercury
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours—4th Gear											
69.77	5759	4.54	1791	5.83	7.425	0.656	9.40	184	61	67	28.700
75% of Pull at Maximum Power—Ten Hours—4th Gear											
58.95	4503	4.91	1905	4.23	6.706	0.702	8.79	180	50	57	28.973
50% of Pull at Maximum Power—Two Hours—4th Gear											
40.54	2962	5.13	1961	2.80	5.478	0.833	7.40	182	50	58	29.055
MAXIMUM POWER WITH BALLAST											
62.02	10122	2.30	1825	14.56	2nd Gear .....		181	61	66	28.720	
69.53	8562	3.05	1804	9.31	3rd Gear .....		179	61	66	28.720	
72.91	5964	4.58	1801	5.41	4th Gear .....		183	61	65	28.745	
72.42	4777	5.69	1799	4.25	5th Gear .....		184	60	62	28.750	
71.82	3318	8.12	1799	2.76	6th Gear .....		184	60	62	28.760	
70.57	2564	10.32	1798	2.00	7th Gear .....		187	60	62	28.760	
MAXIMUM POWER WITHOUT BALLAST											
74.61	6333	4.42	1800	9.16	4th Gear .....		190	43	54	29.050	

## VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—4th Gear

Pounds pull	5964	6237	6511	6596	6687	6731	6739	6400
Horsepower	72.91	68.72	63.20	55.97	48.41	40.59	32.51	23.87
Crankshaft speed, rpm	1801	1631	1441	1261	1078	899	720	554
Miles per hour	4.58	4.13	3.64	3.18	2.71	2.26	1.81	1.40
Slip of drivers, %	5.41	5.90	6.18	6.32	6.60	6.47	6.74	6.32

## TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 18.4-34; 8; 20	Two 18.4-34; 8; 16
Ballast	—Liquid	1085 lb each	None
	—Cast iron	1160 lb each	None
Front tires	—No, size, ply & psi	Two 7.50-15; 6; 36	Two 7.50-15; 6; 36
Ballast	—Liquid	None	None
	—Cast iron	35 lb each	None
Height of drawbar		17 inches	17½ inches
Static weight	—Rear	10895 lb	6405 lb
	—Front	2300 lb	2230 lb
Total weight with operator		13370 lb	8810 lb

## Department of Agricultural Engineering

Dates of Test: OCTOBER 8 TO OCTOBER 27, 1965

Manufacturer: J. I. CASE COMPANY, RACINE, WISCONSIN

**FUEL, OIL and TIME** Fuel regular gasoline Octane No Motor 85.2 Research 92.3 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7410 Weight per gallon 6.168 lb Oil SAE 20-20W API service classification MS, DM To motor 2.875 gal Drained from motor 2.226 gal Transmission and final-drive lubricant SAE 10W Type Case TCH oil Total time engine was operated 61½ hours.

**ENGINE** Make Case gasoline Type 6 cylinder vertical Serial No 2102081 Crankshaft mounted lengthwise Rated rpm 1800 Bore and stroke 4" x 5" Compression ratio 7.5 to 1 Displacement 377 cu in Carburetor size 1½" Ignition system battery Cranking system 12 volt electric (two 6-volt batteries) Lubrication pressure Air cleaner oil washed wire mesh Oil filter replaceable pleated paper element Fuel filter sediment bowl with screen Muffler was used Cooling medium temperature control thermostat.

**CHASSIS** Type standard Serial No 8254945 Tread width rear 64" to 96" front 53¾" to 83¾" Wheel base 108" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 27.6" Vertical distance above roadway 37.0" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 1.8 second 2.6 third 3.2 fourth 4.7 fifth 5.7 sixth 8.1 seventh 10.2 eighth 14.7 reverse 2.3 and 7.3 Clutch single plate dry disc operated by foot pedal Brakes double disc operated by two foot pedals which can be locked together Steering mechanical with power assist Turning radius (on concrete surface with brake applied) right 130" left 130" (on concrete surface without brake) right 157" left 157" Turning space diameter (on concrete surface with brake applied) right 265" left 265" (on concrete surface without brake) right 321" left 321" Belt pulley 920 rpm at 1700 engine rpm diam 10½" face 7¼" Belt speed 2523 fpm Power take-off 545 rpm at 1700 engine rpm (1000 rpm power take-off is also available).

**REPAIRS and ADJUSTMENTS** No repairs or adjustments.

**REMARKS** All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

First gear was not run as it was necessary to limit the pull in second gear to avoid excessive wheel slippage.

Eighth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 920.

L. F. LARSEN

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

J. J. SULEK

D. E. LANE

Board of Tractor Test Engineers

The University of Nebraska Agricultural Experiment Station  
E. F. Frolik, Dean; H. H. Kramer, Director, Lincoln, Nebraska

# EXPLANATION OF TEST REPORT

## GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

## PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

## BELT OR POWER TAKE-OFF PERFORMANCE

**Maximum Power and Fuel Consumption.** The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

**Varying Power and Fuel Consumption.** Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque,  $\frac{1}{2}$  of the 85% torque; maximum power,  $\frac{1}{4}$  and  $\frac{3}{4}$  of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

## DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

**Varying Power and Fuel Consumption With Ballast.** The varying power runs are made to show the effect of speed-control devices (engine, governor, automatic trans-

mission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

**Maximum Power with Ballast.** Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

**Maximum Power Without Ballast.** All added ballast is removed from the tractor. The maximum drawbar power of the tractor is determined by the same procedure used for getting maximum power with ballast. The gear (or travel speed) is the same as that used in the 10-hour test.

**Varying Power and Travel Speed with Ballast.** Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.



Case 941 GP Gasoline