

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1975

Test 1188: Massey-Ferguson 265 Diesel

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 1188: Massey-Ferguson 265 Diesel" (1975). *Nebraska Tractor Tests*. 1510.

<https://digitalcommons.unl.edu/tractormuseumlit/1510>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1188 – MASSEY-FERGUSON MF 265 DIESEL

POWER TAKE-OFF PERFORMANCE

Hp	Crank- shaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
60.73	Rated Engine Speed—Two Hours (PTO Speed—642 rpm)							
	2000	3.821	0.435	15.90	189	65	76	29.093
54.76	Standard Power Take-Off Speed (540 rpm)—One Hour							
	1683	3.448	0.435	15.88	198	67	81	29.085
VARYING POWER AND FUEL CONSUMPTION—Two Hours								
53.25	2062	3.290	0.427	16.18	187	68	84
0.00	2235	1.103	178	69	84
27.64	2142	2.105	0.526	13.13	181	69	84
60.35	2001	3.846	0.440	15.69	197	70	86
14.30	2218	1.589	0.768	9.00	179	70	86
40.51	2093	2.648	0.452	15.30	185	70	86
Av 32.68	2125	2.430	0.514	13.44	184	69	85	29.080

DRAWBAR PERFORMANCE

Hp	Draw- bar pull lbs	Speed miles per hr	Crank- shaft speed rpm	Slip of drivers %	Fuel Consumption Gal per hr	Lb per hp-hr	Hp-hr per gal	Temp Cool- ing med	Degrees F Air wet bulb	Air dry bulb	Barometer inches of Mercury
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours—7th (1 H L) Gear											
50.38	3627	5.21	1998	7.47	3.726	0.511	13.52	189	63	68	28.985
75% of Pull at Maximum Power—Ten Hours—7th (1 H L) Gear											
41.00	2791	5.51	2069	5.41	3.035	0.512	13.51	182	49	62	28.902
50% of Pull at Maximum Power—Two Hours—7th (1 H L) Gear											
29.02	1897	5.74	2116	3.68	2.387	0.569	12.16	181	69	73	28.930
50% of Pull at Reduced Engine Speed—Two Hours—9th (2 H L) Gear											
28.84	1887	5.73	1446	4.09	2.062	0.494	13.99	181	51	63	29.110
MAXIMUM POWER WITH BALLAST											
38.68	6248	2.32	2065	14.98	4th Gear (2 L H)			181	45	52	29.100
48.28	5651	3.20	2001	13.58	5th Gear (3 L L)			186	60	63	28.990
50.12	4241	4.43	1998	8.46	6th Gear (3 L H)			188	60	63	28.990
51.87	3721	5.23	2002	7.30	7th Gear (1 H L)			187	59	62	28.990
51.61	2778	6.97	2001	5.45	8th Gear (1 H H)			188	61	64	28.990
51.59	2462	7.86	1999	4.77	9th Gear (2 H L)			188	61	64	28.990

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—(7th Gear 1 H L)

Pounds Pull	3721	3953	4095	4166	4137	4012
Horsepower	51.87	49.30	44.92	39.80	33.92	27.56
Crankshaft Speed rpm	2002	1798	1590	1389	1190	995
Miles Per Hour	5.23	4.68	4.11	3.58	3.07	2.58
Slip of Drivers %	7.30	7.59	8.28	8.40	8.40	8.05

TRACTOR SOUND LEVEL (without cab)

	db(A)
Maximum Available Power 2 Hours	95.5
75% of Pull at Max. Power 10 Hours	96.0
50% of Pull at Max. Power 2 Hours	96.0
50% of Pull at Reduced Engine Speed 2 Hours	93.0
Bystander (in 12th—3 H H-gear)	87.5

TIRES, BALLAST AND WEIGHT

	With Ballast	Without Ballast
Rear Tires	Two 16.9-28; 6; 16	Two 16.9-28; 6; 16
Ballast	740 lb each	None
Cast Iron	60 lb each	None
Front Tires	Two 7.5L-15; 6; 36	Two 7.5L-15; 6; 36
Ballast	None	None
Front weight	215 lb total	None
Height of drawbar	19.5 inches	19.5 inches
Static weight with operator—rear	6000 lb	4400 lb
front	2200 lb	1985 lb
total	8200 lb	6385 lb

Department of Agricultural Engineering

Dates of Test: September 4 to 23, 1975

Manufacturer: MASSEY-FERGUSON INC.,
1901 Bell Avenue, Des Moines, Iowa 50315

FUEL, OIL AND TIME Fuel No 2 Diesel Cetane No 51.7 (ratings taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.830 Weight per gallon 6.911 lb Oil SAE 20/20W API service classification SB/SE-CA/CC To motor 2.052 gal Drained from motor 1.458 gal Transmission and final drive lubricant SAE Massey-Ferguson M-1129(A) Total time engine was operated 44.5 hours.

ENGINE Make Perkins Type 4 cylinder Serial No 103 093 L Crankshaft Mounted lengthwise Rated rpm 2000 Bore and stroke 3.875" x 5" Compression ratio 16 to 1 Displacement 236 cu in Lubrication pressure Cranking system 12 volt Air cleaner dry dual pleated paper element Oil filter full flow paper cartridge Oil cooler radiator for hydraulic and transmission oil Fuel filter pleated paper element Muffler vertical Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No. 9A 223 934 Tread width rear 56" to 90" front 48" to 80" Wheel base 82" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 26.5" Vertical distance above roadway 34" Horizontal distance from center of rear wheel tread 0.4" to the left Hydraulic control system constant running except when PTO clutch is disengaged Transmission selective gear fixed ratio with partial range operator controlled power shift Advertised speeds mph first 1.4 second 1.8 third 2.0 fourth 2.6 fifth 3.6 sixth 4.8 seventh 5.4 eighth 7.1 ninth 7.9 tenth 10.4 eleventh 14.5 twelfth 19.0 reverse 1.8, 2.4, 7.4, 9.6 Clutch single plate dry disc operated by foot pedal Brakes double dry disc operated by two foot pedals which can be locked together Steering power assist Turning radius (on concrete surface with brake applied) right 116.5" left 112.5" (on concrete surface without brake) right 129" left 127" Turning space diameter (on concrete surface with brake applied) right 239" left 231" (on concrete surface without brake) right 265" left 261" Power take-off 540 rpm at 1683 engine rpm.

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with SAE and ASAE test code or official Nebraska test procedure. Fuel temperature at injection pump return was 160°F. Six gears were chosen between 15% slip and 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 1188.

LOUIS I. LEVITICUS

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

W. E. SPLINTER

D. E. LANE

Board of Tractor Test Engineers

The Agricultural Experiment Station
Institute of Agriculture and Natural Resources
University of Nebraska—Lincoln
H. W. Ottoson, Director

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories may be disconnected only when the means for disconnecting can be reached from the operator station. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. Prior to the maximum power run the tire tread-bar height must be at least 65% of new tread height.

POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ of the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general use.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effects of speed-control devices (engine, governor, automatic transmission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 4 different runs as follows: (1) as near to the pull at maximum power as

possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; (3) 50% of the pull at maximum power; and (4) maintaining the same load and travel speed as in (3) by shifting to a higher gear and reducing the engine rpm.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 6 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe limit for the test course. The manufacturer's representative has the option of selecting one gear or speed over eight miles per hour. The maximum safe speed for the Nebraska Test Course has been set at 15 mph. The slip limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Varying Drawbar Pull and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

SOUND MEASUREMENT

Sound is recorded during each of the Varying Power and Fuel Consumption runs as the tractor travels on a straight section of the test course. The dB(A) sound level is obtained with the microphone located near the right ear of the operator. Bystander sound readings are taken with the microphone placed 25 feet from the line of travel of the tractor.

An increase of 10 dB(A) will approximately double the loudness to the human ear.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska 68583.



MASSEY-FERGUSON MF 265 DIESEL