

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1976

Test 1206: Ford 2600 Gasoline 6-Speed

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 1206: Ford 2600 Gasoline 6-Speed" (1976). *Nebraska Tractor Tests*. 1527.

<https://digitalcommons.unl.edu/tractormuseumlit/1527>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1206 – FORD 2600 GASOLINE – 6 SPEED

POWER TAKE-OFF PERFORMANCE

Hp	Crank- shaft speed rpm	Fuel Consumption Gal per hr	Lb per hp-hr	Hp-hr per gal	Cooling medium	Temperature Degrees F Air wet bulb	Air dry bulb	Barometer inches of Mercury
MAXIMUM POWER AND FUEL CONSUMPTION								
	Rated Engine Speed—Two Hours (PTO Speed—597 rpm)							
32.78	2000	3.048	0.569	10.76	193	55	75	28.937
	Standard Power Take-off Speed (540 rpm)—One Hour							
31.03	1810	2.786	0.549	11.14	192	55	75	28.915
VARYING POWER AND FUEL CONSUMPTION—Two Hours								
29.38	2111	2.878	0.599	10.21	183	55	76
0.00	2191	1.172	162	55	76
14.92	2144	2.177	0.893	6.86	169	54	76
33.15	2000	3.157	0.583	10.50	191	55	75
7.55	2169	1.677	1.359	4.50	165	55	75
22.14	2120	2.525	0.698	8.77	173	54	75
Av 17.86	2122	2.264	0.776	7.89	174	55	75	28.867

DRAWBAR PERFORMANCE

Hp	Draw- bar pull lbs	Speed miles per hr	Crank- shaft speed rpm	Slip of drivers %	Fuel Consumption			Temp	Degrees F		Barometer inches of Mercury
					Gal per hr	Lb per hp-hr	Hp-hr per gal	Cool- ing med	Air wet bulb	Air dry bulb	
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours 3rd Gear											
27.04	2540	3.99	2001	7.74	3.064	0.693	8.83	191	66	72	28.690
75% of Pull at Maximum Power—Ten Hours 3rd Gear											
22.55	1975	4.28	2100	5.73	2.762	0.749	8.17	179	66	74	28.512
50% of Pull at Maximum Power—Two Hours 3rd Gear											
15.12	1288	4.40	2117	3.87	2.247	0.910	6.73	175	69	78	28.715
50% of Pull at Reduced Engine Speed—Two Hours 4th Gear											
15.43	1319	4.39	1549	3.79	1.900	0.753	8.12	181	74	82	28.665
MAXIMUM POWER WITH BALLAST											
26.04	4198	2.33	2093	14.81	2nd Gear			175	57	66	28.360
28.01	2633	3.99	2001	7.76	3rd Gear			194	71	77	28.750
28.25	1901	5.57	2001	5.46	4th Gear			193	73	78	28.750
28.00	1407	7.46	2003	3.93	5th Gear			193	73	78	28.720

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST 3rd Gear

Pounds Pull	2633	2724	2767	2833	2879	3014	2885
Horsepower	28.01	26.00	23.37	20.94	18.27	15.76	12.13
Crankshaft Speed rpm	2001	1801	1598	1402	1206	1000	800
Miles Per Hour	3.99	3.58	3.17	2.77	2.38	1.96	1.58
Slip of Drivers %	7.76	8.17	8.27	8.47	8.68	9.27	8.88

TRACTOR SOUND LEVEL WITHOUT CAB

	dB(A)
Maximum Available Power 2 Hours	92.0
75% of Pull at Max. Power 10 Hours	90.0
50% of Pull at Max. Power 2 Hours	89.5
50% of Pull at Reduced Engine Speed 2 Hours	87.0
Bystander (in 6th gear)	78.0

TIRES, BALLAST AND WEIGHT

	With Ballast	Without Ballast
Rear Tires	—No., size, ply & psi	Two 14.9-24; 4; 14
Ballast	—Liquid	507 lb each
	Cast Iron	200 lb each
Front Tires	—No., size, ply & psi	Two 5.50-16; 4; 36
Ballast	—Liquid	None
	Cast Iron	115 lb each
Height of drawbar	22.5 inches	22.5 inches
Static weight with operator—rear	4150 lb	2735 lb
front	1850 lb	1620 lb
total	6000 lb	4355 lb

Department of Agricultural Engineering

Dates of Test: March 26 to April 20, 1976

Manufacturer: : FORD MOTOR COMPANY,
Tractor Operations, 2500 East Maple Road,
Troy, Michigan 48084

FUEL, OIL AND TIME Fuel no-lead gasoline Octane No. Motor 82.2 Research 91.8 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7350 Weight per gallon 6.119 lb Oil SAE 10W-30 API service classification SB/SE CA/CB To motor 1.482 gal Drained from motor 1.462 gal Transmission and final drive lubricant Ford M-2C53-A Total time engine was operated 41.5 hours.

ENGINE Make Ford gasoline Type 3 cylinder Serial No. B024048 Crankshaft mounted lengthwise Rated rpm 2000 Bore and stroke 4.2" x 3.8" Compression ratio 7.75 to 1 Displacement 158 cu in Carburetor size 1 1/4" Ignition system battery Cranking system 12 volt Lubrication pressure Air cleaner double paper element with dust evacuator Oil filter full flow cotton blend spin-on cartridge Oil cooler radiator for hydraulic system Fuel filter edge type filter element Muffler vertical Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No C489194 Tread width rear 52" to 76" front 52" to 80" Wheel base 75.8" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from centerline of rear wheels 32.8" Vertical distance above roadway 25.2" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 1.4 second 2.6 third 4.2 fourth 5.8 fifth 7.6 sixth 17.4 reverse 2.4 and 7.0 Clutch single plate dry disc operated by foot pedal Brakes internal expanding shoe operated by two foot pedals which can be locked together Steering power assist Turning radius (on concrete surface with brake applied) right 117" left 117" (on concrete surface without brake) right 129" left 129" Turning space diameter (on concrete surface with brake applied) right 240" left 240" (on concrete surface without brake) right 267" left 267" Belt pulley 1113 rpm at 2000 engine rpm diam 10.25" face 6.5" Belt speed 2986 fpm Power take-off 540 rpm at 1810 engine rpm.

REPAIRS AND ADJUSTMENTS: No 2 spark plug was removed, cleaned and reinstalled before 10 hour test.

REMARKS: All test results were determined from observed data obtained in accordance with SAE and ASAE test code or official Nebraska test procedure. Four gears were chosen between 15% slip and 15 mph. Coolant overflowed from radiator at completion of 10 hour test.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 1206.

LOUIS I. LEVITICUS

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

W. E. SPLINTER

D. E. LANE

Board of Tractor Test Engineers

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories may be disconnected only when the means for disconnecting can be reached from the operator station. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. Prior to the maximum power run the tire tread-bar height must be at least 65% of new tread height.

POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ of the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general use.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effects of speed-control devices (engine, governor, automatic transmission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 4 different runs as follows: (1) as near to the pull at maximum power as

possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; (3) 50% of the pull at maximum power; and (4) maintaining the same load and travel speed as in (3) by shifting to a higher gear and reducing the engine rpm.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 6 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe limit for the test course. The manufacturer's representative has the option of selecting one gear or speed over eight miles per hour. The maximum safe speed for the Nebraska Test Course has been set at 15 mph. The slip limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Varying Drawbar Pull and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

SOUND MEASUREMENT

Sound is recorded during each of the Varying Power and Fuel Consumption runs as the tractor travels on a straight section of the test course. The dB(A) sound level is obtained with the microphone located near the right ear of the operator. Bystander sound readings are taken with the microphone placed 25 feet from the line of travel of the tractor.

An increase of 10 dB(A) will approximately double the loudness to the human ear.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska 68583.



FORD 2600 GASOLINE 6-SPEED