

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

---

1-1-1976

## Test 1227: Ford 5600 Diesel 16-Speed

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, [tractortestlab@unl.edu](mailto:tractortestlab@unl.edu)

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Nebraska Tractor Test Lab, "Test 1227: Ford 5600 Diesel 16-Speed" (1976). *Nebraska Tractor Tests*. 1548. <https://digitalcommons.unl.edu/tractormuseumlit/1548>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA TRACTOR TEST 1227 — FORD 5600 DIESEL, 16-SPEED

## POWER TAKE-OFF PERFORMANCE

Power Hp (kW)	Crank shaft speed rpm	Fuel Consumption			Temperature °F (°C)			Barometer inch Hg (kPa)
		gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
Rated Engine Speed—Two Hours (PTO Speed—597 rpm)								
58.46 (43.59)	2101	3.988 (15.098)	0.478 (0.290)	14.66 (2.887)	197 (91.7)	58 (14.3)	75 (24.0)	28.987 (97.884)
Standard Power Take-off Speed (540 rpm)—One Hour								
56.00 (41.76)	1901	3.719 (14.078)	0.465 (0.283)	15.06 (2.966)	200 (93.5)	57 (13.8)	75 (23.8)	28.995 (97.912)
VARYING POWER AND FUEL CONSUMPTION—Two Hours								
52.62 (39.24)	2225	3.626 (13.727)	0.482 (0.293)	14.51 (2.859)	186 (85.8)	58 (14.2)	76 (24.4)	.....
0.00 (0.00)	2340	1.290 (4.884)	..... .....	..... .....	172 (77.8)	57 (13.9)	76 (24.4)	..... .....
27.06 (20.18)	2289	2.396 (9.070)	0.620 (0.377)	11.29 (2.225)	174 (78.9)	57 (13.9)	76 (24.4)	..... .....
58.82 (43.86)	2100	3.999 (15.138)	0.476 (0.289)	14.71 (2.897)	196 (90.8)	57 (13.9)	76 (24.4)	..... .....
13.69 (10.21)	2312	1.817 (6.880)	0.929 (0.565)	7.53 (1.484)	172 (77.5)	57 (13.9)	76 (24.4)	..... .....
40.14 (29.93)	2264	2.979 (11.277)	0.519 (0.316)	13.47 (2.654)	178 (81.4)	57 (13.9)	76 (24.2)	..... .....
Av 32.05 Av (23.90)	2255	2.685 (10.163)	0.586 (0.357)	11.94 (2.352)	180 (82.0)	57 (13.9)	76 (24.4)	28.987 (97.884)

## DRAWBAR PERFORMANCE

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption			Temp. °F (°C)			Barom. inch Hg (kPa)
					gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cool- ing med	Air wet bulb	Air dry bulb	
Maximum Available Power—Two Hours 8th (5PD) Gear											
47.86 (35.69)	4246 (18.89)	4.23 (6.80)	2102	7.59	3.965 (15.009)	0.580 (0.353)	12.07 (2.378)	196 (90.8)	62 (16.7)	79 (25.8)	28.575 (96.493)
75% of Pull at Maximum Power—Ten Hours 8th (5PD) Gear											
40.94 (30.53)	3276 (14.57)	4.69 (7.54)	2282	5.63	3.429 (12.980)	0.586 (0.357)	11.94 (2.352)	165 (73.9)	41 (4.8)	50 (9.7)	29.019 (97.993)
50% of Pull at Maximum Power—Two Hours 8th (5PD) Gear											
28.12 (20.96)	2195 (9.76)	4.80 (7.73)	2291	3.63	2.697 (10.209)	0.671 (0.408)	10.42 (2.054)	168 (75.6)	63 (17.2)	81 (27.2)	28.545 (96.392)
50% of Pull at Reduced Engine Speed—Two Hours 12th (6DD) Gear											
28.12 (20.97)	2196 (9.77)	4.80 (7.73)	1432	3.97	2.286 (8.654)	0.569 (0.346)	12.30 (2.424)	161 (71.7)	36 (2.2)	36 (2.2)	28.985 (97.878)
MAXIMUM POWER IN SELECTED GEARS											
36.41 (27.15)	7140 (31.76)	1.91 (3.08)	2300	14.85	4th (2DD) Gear			166 (74.4)	34 (1.1)	35 (1.7)	29.100 (98.266)
47.56 (35.47)	5159 (22.95)	3.46 (5.56)	2099	9.31	7th (4PD) Gear			184 (84.4)	56 (13.3)	66 (18.9)	28.620 (96.645)
49.00 (36.54)	4353 (19.36)	4.22 (6.79)	2101	7.81	8th (5PD) Gear			180 (82.2)	54 (12.2)	63 (17.2)	28.630 (96.679)
49.79 (37.13)	3480 (15.48)	5.36 (8.64)	2099	5.93	10th (6PD) Gear			186 (85.3)	58 (14.4)	70 (21.1)	28.610 (96.612)
48.60 (36.24)	2601 (11.57)	7.01 (11.28)	2097	4.39	12th (6DD) Gear			185 (85.0)	60 (15.6)	74 (23.3)	28.600 (96.578)
43.85 (32.70)	1306 (5.81)	12.60 (20.27)	2099	2.01	14th (7DD) Gear			183 (83.9)	61 (16.1)	76 (24.4)	28.590 (96.544)

## LUGGING ABILITY IN RATED GEAR (8th (5PD))

Crankshaft Speed rpm	2101	1882	1675	1469	1263	1056
Pull—lbs (kN)	4353 (19.36)	4639 (20.64)	4839 (21.52)	4885 (21.73)	4886 (21.73)	4859 (21.61)
Increase in Pull %	0	7	11	12	12	12
Power—Hp (kW)	49.00 (36.54)	46.50 (34.67)	43.00 (32.06)	37.98 (28.32)	32.69 (24.37)	27.15 (20.25)
Speed—Mph (km/h)	4.22 (6.79)	3.76 (6.05)	3.33 (5.36)	2.92 (4.69)	2.51 (4.04)	2.10 (3.37)
Slip %	7.81	8.19	8.57	8.57	8.69	8.69

Department of Agricultural Engineering

Dates of Test: October 5 to 20, 1976

Manufacturer: FORD MOTOR COMPANY,  
Tractor Operations, 2500 East Maple Rd., Troy,  
Michigan 48084

**FUEL, OIL AND TIME:** Fuel No. 2 Diesel  
Cetane No. 51.8 (rating taken from oil company's  
typical inspection data) **Specific gravity converted  
to 60°/60° (15.6°/15.6°)** 0.8406 **Fuel weight** 6.999  
lbs/gal (0.841 kg/l) **Oil SAE 30 API service  
classification** SB/SE-CA/CD **To motor** 2.665 gal  
(10.088 l) **Drained from motor** 1.612 gal  
(6.102 l) **Transmission and final drive lubricant**  
Ford M-2C53A **Total time engine was operated**  
45.5 hours.

**ENGINE Make** Ford Diesel **Type** 4 cylinder  
vertical **Serial No.** \*L069298\* **Crankshaft**  
lengthwise **Rated rpm** 2100 **Bore and stroke** 4.2"  
× 4.2" (106.68 mm × 106.68 mm) **Compression  
ratio** 16.3 to 1 **Displacement** 233 cu in (3814 ml)  
**Cranking system** 12 volt **Oil filter** full flow cotton  
blend spin-on cartridge **Oil cooler** radiator for  
transmission and hydraulic oil **Fuel filter** nylon  
gauze in bottom of tank and paper element **Muf-  
fler** vertical **Cooling medium temperature con-  
trol** thermostat

**CHASSIS: Type** standard **Serial No.**  
\*C510281\* **Tread width** rear 56" (1420 mm) to 80"  
(2030 mm) front 52" (1320 mm) to 80" (2030 mm)  
**Wheel base** 87.5" (2222 mm) **Center of gravity**  
(without operator or ballast, with minimum tread,  
with fuel tank filled and tractor serviced for oper-  
ation) Horizontal distance forward from center-  
line of rear wheels 27.5" (699 mm) Vertical distance  
above roadway 40.0" (1016 mm) Horizontal dis-  
tance from center of rear wheel tread 0.3" (8 mm)  
to the right **Hydraulic control system** direct en-  
gine drive **Transmission** selective gear fixed ratio  
with partial (2 range) operator controlled power  
shift **Advertised speeds mph (km/h)** first 1.2 (1.9)  
second 1.4 (2.2) third 1.5 (2.4) fourth 1.9 (3.0)  
fifth 2.6 (4.1) sixth 3.3 (5.3) seventh 3.5 (5.6)  
eighth 4.2 (6.7) ninth 4.5 (7.2) tenth 5.2 (8.4)  
eleventh 5.4 (8.7) twelfth 6.7 (10.8) thirteenth 9.2  
(14.8) fourteenth 11.8 (19.0) fifteenth 12.5 (20.1)  
sixteenth 16.1 (26.8) reverse 1.7 (2.7), 2.2 (3.5), 6.0  
(9.6), 7.7 (12.5) **Clutch** single plate dry disc oper-  
ated by foot pedal **Brakes** wet multiple disc oper-  
ated by two foot pedals which can be locked to-  
gether **Steering** power assist **Turning radius** (on  
concrete surface with brake applied) right 120"  
(3.05 m) left 120" (3.05 m) (on concrete surface  
without brake) right 138" (3.51 m) left 138"  
(3.51 m) **Turning space diameter** (on concrete  
surface with brake applied) right 252" (6.40 m) left  
252" (6.40 m) (on concrete surface without brake)  
right 291" (7.39 m) left 291" (7.39 m) **Belt pulley**  
1072 rpm at 2050 engine rpm diameter 11" (279  
mm) face 6.5" (165 mm) **Belt speed** 3087 fpm (15.7  
m/s) **Power take-off** 540 rpm at 1901 engine rpm.

**REPAIRS and ADJUSTMENTS:** No repairs or  
adjustments.

TRACTOR SOUND LEVEL WITH CAB	dB(A)
Maximum Available Power—Two Hours	82.5
75% of Pull at Maximum Power—Ten Hours	83.5
50% of Pull at Maximum Power—Two Hours	84.5
50% of Pull at Reduced Engine Speed—Two Hours	80.5
Bystander in 16th (8DD) gear	88.0

#### TIRES, BALLAST AND WEIGHT

		With Ballast	Without Ballast
<b>Rear Tires</b>	—No., size, ply & psi (kPa)	Two 18.4-30; 6; 16 (110)	Two 18.4-30; 6; 16 (110)
Ballast	—Liquid (each)	810 lb (367 kg)	None
	—Cast Iron (each)	300 lb (136 kg)	None
<b>Front Tires</b>	—No., size, ply & psi (kPa)	Two 7.50-16; 6; 40 (280)	Two 7.50-16; 6; 40 (280)
Ballast	—Liquid (each)	None	None
	—Cast Iron (each)	80 lb (36 kg)	None
<b>Height of drawbar</b>		22.5 in (570 mm)	22.5 in (570 mm)
<b>Static weight with operator</b> —rear		7230 lb (3279 kg)	5010 lb (2273 kg)
front		2460 lb (1116 kg)	2300 lb (1043 kg)
total		9690 lb (4395 kg)	7310 lb (3316 kg)

**REMARKS:** All test results were determined from observed data obtained in accordance with SAE and ASAE test code or official Nebraska test procedure. Temperature at injection pump return was 157°F (69.4°C). Six gears were chosen between 15% slip and 15 mph (24.1 km/h). Scratches on all cylinders and slight scoring on cylinder No. 4 were found during final inspection.

We, the undersigned, certify that this is a true and correct report of official Tractor Test **1227**.

LOUIS I. LEVITICUS

Engineer-in Charge

G. W. STEINBRUEGGE, Chairman

W. E. SPLINTER

K. VON BARGEN

Board of Tractor Test Engineers



**Ford 5600 Diesel**