

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

1-1-1981

Test 1413: Steiger Cougar III PTA-280 and Cougar IV CS-280 Diesel 10-Speed

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 1413: Steiger Cougar III PTA-280 and Cougar IV CS-280 Diesel 10-Speed" (1981). *Nebraska Tractor Tests*. 1729.

<https://digitalcommons.unl.edu/tractormuseumlit/1729>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1413

STEIGER COUGAR III PTA-280 CATERPILLAR DIESEL

ALSO STEIGER COUGAR IV CS-280 DIESEL

10 SPEED

DRAWBAR PERFORMANCE

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption			Temp. °F (°C)			Barom. inch Hg (kPa)
					gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cool- ing med	Air wet bulb	Air dry bulb	
Maximum Available Power—Two Hours 5th (4L) Gear											
231.61 (172.71)	15507 (68.98)	5.60 (9.01)	2099	3.31	16.262 (61.558)	0.484 (0.294)	14.24 (2.806)	180 (81.9)	49 (9.4)	56 (13.1)	28.940 (97.726)
75% of Pull at Maximum Power—Ten Hours 5th (4L) Gear											
186.72 (139.24)	11878 (52.84)	5.89 (9.49)	2189	2.43	14.213 (53.803)	0.525 (0.319)	13.14 (2.588)	178 (81.1)	53 (11.8)	63 (17.3)	28.866 (97.476)
50% of Pull at Maximum Power—Two Hours 5th (4L) Gear											
127.62 (95.16)	7920 (35.23)	6.04 (9.72)	2225	1.62	11.403 (43.166)	0.616 (0.375)	11.19 (2.205)	179 (81.7)	56 (13.1)	67 (19.4)	28.910 (97.625)
50% of Pull at Reduced Engine Speed—Two Hours 7th (2H) Gear											
127.68 (95.21)	7924 (35.25)	6.04 (9.72)	1545	1.74	8.974 (33.970)	0.485 (0.295)	14.23 (2.803)	177 (80.6)	54 (11.9)	59 (14.7)	28.710 (96.949)

MAXIMUM POWER IN SELECTED GEARS

149.98 (111.84)	32085 (142.72)	1.75 (2.82)	2197	14.73	1st (1L) Gear			178 (80.8)	47 (8.3)	50 (10.0)	28.760 (97.118)
224.19 (167.18)	24761 (110.14)	3.40 (5.46)	2099	6.39	2nd (2L) Gear			182 (83.3)	56 (13.3)	68 (20.0)	28.910 (97.625)
224.55 (167.45)	19460 (86.56)	4.33 (6.96)	2098	4.28	3rd (1H) Gear			183 (83.9)	56 (13.3)	69 (20.6)	28.920 (97.659)
232.96 (173.72)	19943 (88.71)	4.38 (7.05)	2100	4.44	4th (3L) Gear			182 (83.1)	55 (12.8)	66 (18.9)	28.920 (97.659)
236.40 (176.28)	15813 (70.34)	5.61 (9.02)	2101	3.31	5th (4L) Gear			182 (83.1)	54 (12.2)	65 (18.3)	28.930 (97.692)
236.55 (176.39)	12538 (55.77)	7.07 (11.39)	2099	2.41	6th (5L) Gear			182 (83.1)	55 (12.8)	67 (19.4)	28.920 (97.659)
233.58 (174.18)	10705 (47.62)	8.18 (13.17)	2100	1.99	7th (2H) Gear			182 (83.3)	56 (13.3)	68 (20.0)	28.920 (97.659)

LUGGING ABILITY IN 5th (4L) GEAR

Crankshaft Speed rpm	2101	1888	1681	1470	
Pull—lbs (kN)	15813 (70.34)	18365 (81.69)	20381 (90.66)	21977 (97.76)	At 1460 RPM the automatic transmission shifted down to 4th (3L) gear and the test was terminated.
Increase in Pull %	0	16	29	39	
Power—Hp (kW)	236.40 (176.28)	244.98 (182.68)	240.48 (179.32)	225.62 (168.24)	
Speed—Mph (km/h)	5.61 (9.02)	5.00 (8.05)	4.42 (7.12)	3.85 (6.20)	
Slip %	3.31	4.12	4.60	5.07	

TRACTOR SOUND LEVEL WITH CAB

	dB(A)
Maximum Available Power—Two Hours	76.5
75% of Pull at Maximum Power—Ten Hours	77.0
50% of Pull at Maximum Power—Two Hours	77.0
50% of Pull at Reduced Engine Speed—Two Hours	75.0
Bystander in 10th (5H) gear	98.0

TIRES, BALLAST AND WEIGHT

	With Ballast	Without Ballast
Rear Tires		
—No., size, ply & psi (kPa)	Four 23.1-34; 8; inner 14 (95) outer 12 (85)	Four 23.1-34; 8; inner 14 (95) outer 12 (85)
Ballast	None	None
—Liquid (each)	None	None
—Test Equip. (each)	80 lb (36 kg)	None
Front Tires		
—No., size, ply & psi (kPa)	Four 23.1-34; 8; inner 14 (95) outer 12 (85)	Four 23.1-34; 8; inner 14 (95) outer 12 (85)
Ballast	None	None
—Liquid (each inner)	1025 lb (465 kg)	None
—Cast Iron (each)	None	None
Height of Drawbar	17.5 in (445 mm)	17.5 in (445 mm)
Static Weight with Operator—Rear	13120 lb (5951 kg)	12800 lb (5806 kg)
—Front	20030 lb (9086 kg)	17980 lb (8156 kg)
—Total	33150 lb (15037 kg)	30780 lb (13962 kg)

Department of Agricultural Engineering

Dates of Test: October 21 to November 3, 1981

Manufacturer: STEIGER TRACTOR, INC.,
1701 Westview Drive, Fargo, North Dakota
58103

FUEL, OIL AND TIME: Fuel No. 2 Diesel Cetane No. 46.3 (rating taken from oil company's inspection data) **Specific gravity converted to 60°/60° (15°/15°)** 0.8281 **Fuel weight** 6.895 lbs/gal (0.826 kg/l) **Oil** SAE 15W-40 **API service classification** CC, CD, SE **To motor** 7.296 gal (27.618 l) **Drained from motor** 6.094 gal (23.068 l) **Transmission lubricant** hydraulic transmission fluid type C-3 (Dextron) **Transfer case lubricant** 303 or equivalent **Hydraulic oil** SAE 10 hydraulic oil, 303 or equivalent **Final drive lubricant** SAE 85W 90 **Total time engine was operated** 31.5 hours.

ENGINE: Make Caterpillar Diesel **Type** six cylinder vertical with turbocharger **Serial No.** 90U15964 **Crankshaft** lengthwise **Rated rpm** 2100 **Bore and stroke** 5.4" × 6.5" (137 mm × 165 mm) **Compression ratio** 14.5 to 1 **Displacement** 893 cu in (14634 ml) **Starting system** 12 volt **Lubrication pressure** **Air cleaner** two paper elements with aspirator **Oil filter** one full flow cartridge **Oil cooler** separate engine coolant heat exchangers for crankcase oil and transmission oil, separate radiators for hydraulic and transfer case oil **Fuel Filter** one paper cartridge and prestrainer **Muffler** none **Cooling medium temperature control** one thermostat.

CHASSIS: **Type** four wheel drive with duals **Serial No.** 155-00002 81 **Tread width** rear 79.0" (2007 mm) to 136.4" (3464 mm) front 79.0" (2007 mm) to 136.4" (3464 mm) **Wheel base** 132.5" (3365 mm) **Center of gravity** (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 77.4" (1966 mm) Vertical distance above roadway 45.5" (1156 mm) Horizontal distance from center of rear wheel tread 0" (0 mm) to the right/left **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with automatic power-shift and torque converter lockup **Advertised speeds mph (km/h)** first 1.9 (3.0) second 3.4 (5.6) third 4.3 (6.9) fourth 4.4 (7.0) fifth 5.5 (8.9) sixth 6.9 (11.1) seventh 7.9 (12.8) eighth 10.0 (16.2) ninth 12.7 (20.4) tenth 15.9 (25.6) reverse 2.4 (3.8), 5.4 (8.7) **Clutch** none **Brakes** multiple dry disc hydraulically operated by foot pedal or mechanically by hand lever **Steering** hydrostatic and articulated **Turning radius** (on concrete surface without brake) right 257" (6.53 m) left 261.5" (6.64 m) **Turning space diameter** (on concrete surface without brake) right 537" (13.64 m) left 546" (13.87 m) **Power take-off** none.

REPAIRS and ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with SAE and ASAE test codes or official Nebraska test procedure. For the maximum power tests, the fuel temperature at the injection pump return was maintained at 158°F (70.0°C) Seven gears were chosen between 15% slip and 10 mph (16.1 km/h).

NOTE: Supplemental permit for Cougar IV CS-280 granted October, 1983.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. 1413.

LOUIS I. LEVITICUS
Engineer-in-Charge

K. VON BARGEN
W. E. SPLINTER
L. L. BASHFORD

Board of Tractor Test Engineers



Steiger Cougar III PTA-280 Caterpillar Diesel