

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1982

Test 1461: John Deere 4850 Powershift Diesel 15-Speed

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 1461: John Deere 4850 Powershift Diesel 15-Speed" (1982). *Nebraska Tractor Tests*. 1795.

<https://digitalcommons.unl.edu/tractormuseumlit/1795>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1461

JOHN DEERE 4850 POWERSHIFT DIESEL

15 SPEED

POWER TAKE-OFF PERFORMANCE

Power Hp (kW)	Crank shaft speed rpm	Fuel Consumption			Temperature °F (°C)			Barometer inch Hg (kPa)	
		gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cooling medium	Air wet bulb	Air dry bulb		
MAXIMUM POWER AND FUEL CONSUMPTION									
Rated Engine Speed—Two Hours (PTO Speed—998 rpm)									
192.99 (143.91)	2200	11.046 (41.814)	0.399 (0.243)	17.47 (3.442)	194 (90.1)	59 (15.1)	75 (23.7)	29.223 (98.683)	
VARYING POWER AND FUEL CONSUMPTION—Two Hours									
166.58 (124.22)	2233	9.883 (37.411)	0.414 (0.252)	16.86 (3.320)	188 (86.7)	58 (14.2)	72 (21.9)	
0.00 (0.00)	2333	2.579 (9.763)	172 (77.5)	57 (13.9)	71 (21.7)	
85.18 (63.52)	2288	6.211 (23.511)	0.509 (0.310)	13.71 (2.702)	183 (83.9)	60 (15.3)	74 (23.6)	
191.94 (143.13)	2199	11.039 (41.787)	0.401 (0.244)	17.39 (3.425)	196 (91.1)	60 (15.8)	76 (24.4)	
43.00 (32.07)	2302	4.518 (17.102)	0.733 (0.446)	9.52 (1.875)	176 (80.3)	62 (16.4)	76 (24.2)	
126.56 (94.38)	2263	8.068 (30.541)	0.445 (0.271)	15.69 (3.090)	185 (85.0)	60 (15.3)	74 (23.1)	
Av Av	102.21 (76.22)	2270	7.050 (26.687)	0.481 (0.293)	14.50 (2.856)	183 (84.1)	59 (15.2)	74 (23.2)	29.240 (98.739)

DRAWBAR PERFORMANCE WITH BIAS PLY TIRES

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption			Temp. °F (°C)			Barom. inch Hg (kPa)
					gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cool- ing med	Air wet bulb	Air dry bulb	
Maximum Available Power—Two Hours 10th Gear											
162.53 (121.20)	9875 (43.92)	6.17 (9.93)	2199	4.54	11.069 (41.900)	0.475 (0.289)	14.68 (2.892)	188 (86.7)	49 (9.4)	56 (13.1)	28.690 (96.882)
75% of Pull at Maximum Power—Ten Hours 10th Gear											
127.90 (95.37)	7496 (33.34)	6.40 (10.30)	2249	3.31	9.267 (35.080)	0.506 (0.308)	13.80 (2.719)	183 (83.6)	49 (9.6)	58 (14.2)	28.762 (97.125)
50% of Pull at Maximum Power—Two Hours 10th Gear											
87.52 (65.26)	4998 (22.23)	6.57 (10.57)	2287	2.26	7.290 (27.595)	0.581 (0.354)	12.01 (2.365)	176 (79.7)	38 (3.1)	42 (5.3)	28.805 (97.270)
50% of Pull at Reduced Engine Speed—Two Hours 13th Gear											
87.54 (65.28)	4997 (22.23)	6.57 (10.57)	1434	2.26	5.857 (22.171)	0.467 (0.284)	14.95 (2.944)	179 (81.4)	45 (6.9)	53 (11.7)	28.805 (97.270)

MAXIMUM POWER IN SELECTED GEARS

142.44 (106.22)	18789 (83.58)	2.84 (4.58)	2231	14.95	5th Gear			184 (84.4)	47 (8.3)	50 (10.0)	28.680 (96.848)
158.79 (118.41)	17935 (79.78)	3.32 (5.34)	2200	11.18	6th Gear			184 (84.4)	48 (8.9)	51 (10.6)	28.690 (96.882)
165.73 (123.58)	15745 (70.04)	3.95 (6.35)	2200	8.26	7th Gear			188 (86.7)	48 (8.9)	52 (11.1)	28.700 (96.916)
162.86 (121.44)	13168 (58.57)	4.64 (7.46)	2199	6.22	8th Gear			191 (88.3)	51 (10.6)	60 (15.6)	28.640 (96.713)
163.35 (121.81)	11342 (50.45)	5.40 (8.69)	2199	5.21	9th Gear			192 (88.6)	51 (10.6)	59 (15.0)	28.650 (96.747)
164.65 (122.78)	9994 (44.45)	6.18 (9.94)	2200	4.42	10th Gear			188 (86.4)	49 (9.4)	57 (13.9)	28.670 (96.814)
165.23 (123.21)	8664 (38.54)	7.15 (11.51)	2197	3.94	11th Gear			190 (87.8)	51 (10.6)	61 (16.1)	28.640 (96.713)
171.27 (127.72)	7988 (35.53)	8.04 (12.94)	2198	3.53	12th Gear			191 (88.3)	51 (10.6)	61 (16.1)	28.640 (96.713)

LUGGING ABILITY IN 10th GEAR

Crankshaft Speed rpm		2200	1983	1760	1538	1322	1103
Pull—lbs (kN)		9994 (44.45)	11432 (50.85)	12617 (56.12)	13213 (58.77)	12568 (55.91)	10413 (46.32)
Increase in Pull %		0	14	26	32	26	4
Power—Hp (kW)		164.65 (122.78)	168.35 (125.54)	163.90 (122.22)	149.46 (111.45)	122.55 (91.38)	85.70 (63.91)
Speed—Mph (km/h)		6.18 (9.94)	5.52 (8.89)	4.87 (7.84)	4.24 (6.83)	3.66 (5.88)	3.09 (4.97)
Slip %		4.42	5.21	5.84	6.15	5.84	4.90

TRACTOR SOUND LEVEL WITH CAB	RATED RPM	Radial Ply			Bias Ply
		1700 dB(A)	2000 dB(A)	2200 dB(A)	2200 dB(A)
Maximum Available Power—Two Hours		74.5	74.0	75.5	75.5
75% of Pull at Maximum Power—Ten Hours					75.0
50% of Pull at Maximum Power—Two Hours					74.5
50% of Pull at Reduced Engine Speed—Two Hours					72.5
Bystander in 15th gear					87.5

Department of Agricultural Engineering

Dates of Test: October 11 to November 11, 1982

Manufacturer: JOHN DEERE TRACTOR WORKS, P.O. Box 270, Waterloo, Iowa 50702

FUEL, OIL AND TIME: Fuel No. 2 Diesel Cetane No. 46.6 (rating taken from oil company's inspection data) **Specific gravity converted to 60°/60° (15°/15°)** 0.8382 **Fuel weight** 6.979 lbs/gal (0.836 kg/l) **Oil SAE 15W-40 API service classification** CD, CC, SD **To motor** 4.759 gal (18.014 l) **Drained from motor** 4.211 gal (15.941 l) **Transmission and final drive lubricant** John Deere Hy-Gard transmission and hydraulic fluid **Total time engine was operated** 67.5 hours.

ENGINE: Make John Deere Diesel **Type** six cylinder vertical with turbocharger and intercooler **Serial No.** *RG6466A231046* **Crankshaft** lengthwise **Rated rpm** 1700 to 2200 **Bore and stroke** 4.57" × 4.75" (116.0 mm × 120.6 mm) **Compression ratio** 15.0 to 1 **Displacement** 466 cu in (7636 ml) **Starting system** 12 volt **Lubrication pressure** **Air cleaner** two paper elements **Oil filter** one full flow paper cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** two paper elements with prestrainer **Muffler** vertical **Cooling medium temperature control** three thermostats and variable speed fan.

CHASSIS: **Type** standard with duals **Serial No.** *RW4850P001113* **Tread width** rear 63" (1600 mm) to 130" (3300 mm) front 60.2" (1530 mm) to 86.3" (2192 mm) **Wheel base** 118.5" (3010 mm) **Center of gravity** (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 31.9" (810 mm) Vertical distance above roadway 45.3" (1151 mm) Horizontal distance from center of rear wheel tread 0.3" (8 mm) to the right **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with full range operator controlled powershift **Advertised speeds mph (km/h)** first 1.3 (2.1) second 1.9 (3.1) third 2.3 (3.7) fourth 2.9 (4.7) fifth 3.3 (5.3) sixth 3.8 (6.1) seventh 4.3 (7.0) eighth 5.0 (8.0) ninth 5.7 (9.2) tenth 6.5 (10.5) eleventh 7.5 (12.0) twelfth 8.4 (13.5) thirteenth 10.4 (16.7) fourteenth 14.5 (23.4) fifteenth 18.0 (29.0) reverse 1.8 (2.9), 2.6 (4.2), 4.0 (6.4), 6.0 (9.7) **Clutch** wet multiple disc hydraulically power actuated and operated by foot pedal **Brakes** wet disc hydraulically power actuated and operated by two foot pedals which can be locked together **Steering** hydrostatic **Turning radius** (on concrete surface with brake applied) right 165" (4.2 m) left 165" (4.2 m) (on concrete surface without brake) right 181" (4.6 m) left 181" (4.6 m) **Turning space diameter** (on concrete surface with brake applied) right 346" (8.79 m) left 346" (8.79 m) (on concrete surface without brake) right 380" (9.65 m) left 380" (9.65 m) **Power take-off** 998 rpm at 2200 engine rpm.

REPAIRS and ADJUSTMENTS: No repairs or adjustments.

POWER AND FUEL CONSUMPTION AT 2200 RPM

MAXIMUM POWER IN SELECTED GEARS

LUGGING ABILITY IN 10th GEAR

POWER TAKE-OFF PERFORMANCE

MAXIMUM POWER AND FUEL CONSUMPTION

DRAWBAR PERFORMANCE WITH RADIAL PLY TIRES

MAXIMUM POWER IN SELECTED GEARS

POWER TAKE-OFF PERFORMANCE

MAXIMUM POWER AND FUEL CONSUMPTION

DRAWBAR PERFORMANCE WITH RADIAL PLY TIRES

Maximum Available Power—Two Hours 10th Gear

MAXIMUM POWER IN SELECTED GEARS

00	1701	2.84	10th Gear	188
----	------	------	-----------	-----

Bias Ply Tires

With Ballast

Radial Ply Tires

With Ballast

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. 1461.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. 1461.

Engineer-in-Charge

Board of Tractor Test Engineers



John Deere 4850 Powershift Diesel