

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

1-1-1991

Test 1649: Case International 9230 and Steiger 9230 (12-Speeds) Diesels

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 1649: Case International 9230 and Steiger 9230 (12-Speeds) Diesels" (1991). *Nebraska Tractor Tests*. 1959.

<https://digitalcommons.unl.edu/tractormuseumlit/1959>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA OECD TRACTOR TEST 1649—SUMMARY 087

CASE INTERNATIONAL 9230 DIESEL

ALSO STEIGER 9230 DIESEL

12 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
---------------------	--------------------------------	-----------------	-----------------------	-----------------------	--------------------------------

MAXIMUM POWER AND FUEL CONSUMPTION

Rated Engine Speed—(PTO speed—1048 rpm)					
198.63 (148.12)	2199	11.74 (44.44)	0.413 (0.251)	16.92 (3.33)	

Standard PTO Speed (PTO—1000 RPM)					
207.83 (154.98)	2097	11.85 (44.86)	0.399 (0.243)	17.54 (3.45)	

Maximum Power (2 Hours)					
218.20 (162.71)	1900	11.87 (44.93)	0.380 (0.231)	18.38 (3.62)	

VARYING POWER AND FUEL CONSUMPTION

198.63 (148.12)	2199	11.74 (44.44)	0.413 (0.251)	16.92 (3.33)	Air temperature 73°F (23°C)
174.25 (129.94)	2252	10.68 (40.44)	0.429 (0.261)	16.31 (3.21)	
131.59 (98.13)	2286	8.75 (33.13)	0.465 (0.283)	15.04 (2.96)	Relative humidity 69%
89.44 (66.70)	2320	7.04 (26.63)	0.550 (0.335)	12.71 (2.50)	
44.28 (33.02)	2350	4.93 (18.68)	0.779 (0.474)	8.98 (1.77)	Barometer 28.92" Hg (97.92 kPa)
0.38 (0.28)	2375	3.22 (12.18)	59.995 (36.493)	0.12 (0.02)	

Maximum Torque 628 lb.-ft (852 Nm) at 1800 rpm

Maximum Torque Rise 32.4%

DRAWBAR PERFORMANCE

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.*F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—5th Gear									
177.51 (132.37)	14127 (62.84)	4.71 (7.58)	2198	2.72	0.458 (0.279)	15.26 (3.01)	183 (84)	81 (27)	28.83 (97.63)
75% of Pull at Maximum Power—5th Gear									
138.50 (103.28)	10601 (47.16)	4.90 (7.88)	2268	2.14	0.493 (0.300)	14.18 (2.79)	184 (84)	88 (31)	28.81 (97.56)
50% of Pull at Maximum Power—5th Gear									
94.45 (70.43)	7059 (31.40)	5.02 (8.08)	2306	1.31	0.567 (0.345)	12.34 (2.43)	182 (83)	88 (31)	28.81 (97.56)
75% of Pull at Reduced Engine Speed—6th Gear									
138.40 (103.20)	10599 (47.14)	4.90 (7.88)	1842	1.98	0.441 (0.268)	15.86 (3.12)	183 (84)	88 (31)	28.81 (97.56)
50% of Pull at Reduced Engine Speed—6th Gear									
94.31 (70.32)	7060 (31.40)	5.01 (8.06)	1870	1.31	0.482 (0.293)	14.50 (2.86)	181 (83)	88 (31)	28.81 (97.56)

Location of Test: Tractor Testing Laboratory,
University of Nebraska, Lincoln, Nebraska 68583-
0832, U.S.A.

Dates of Test: June 10-14, 1991

Manufacturer: J.I. CASE CO. 3401 First Avenue
North, Fargo ND 58102

FUEL OIL and TIME: Fuel No. 2 Diesel Cetane
No. 53.9 Specific gravity converted to 60°/60°F
(15°/15°C) 0.8399 Fuel weight 6.993 lbs/gal (0.838
kg/l) Oil SAE 15W-40 API service classification
CC, CD To motor 4.343 gal (16.440 l) Drained
from motor 3.886 gal (14.711 l) Transmission and
final drive lubricant Case IH Hytran Plus fluid
Hydraulic lubricant Case IH Hytran Plus fluid
Total time engine was operated 21.0 hours.

ENGINE: Make Consolidated Diesel Corpora-
tion Diesel Type six cylinder vertical with turbo-
charger and intercooler Serial No. 44577092
Crankshaft lengthwise Rated rpm 2200 Bore and
stroke (as specified) 4.488" × 5.315" (114.0 mm ×
135.0 mm) Compression ratio 16.5 to 1 Displace-
ment 505 cu in (8269 ml) Starting system 12 volt
Lubrication pressure Air cleaner two paper ele-
ments and aspirator Oil filter one full flow car-
tridge Oil cooler engine coolant heat exchanger
for crankcase oil, radiator for hydraulic and trans-
mission oil Fuel filter one paper element Muffler
vertical Cooling medium temperature control two
thermostats.

ENGINE OPERATING PARAMETERS: Fuel
rate 75.6-83.8 lb/hr (34.3-38.0 kg/hr) High idle
2350-2450 rpm Turbo boost nominal 12-15.5 psi
(81-106 kPa) as measured 15.5 psi (106 kPa).

CHASSIS: Type four wheel drive with duals,
articulated Serial No. *JCB0027357- Tread width
rear 60.0" (1524 mm) to 130.0" (3302 mm) front
60.0" (1524 mm) to 130.0" (3302 mm) Wheel base
120.4" (3058 mm) Hydraulic control system direct
engine drive Transmission selective gear fixed ra-
tio with full range operator controlled powershift
Nominal travel speeds mph (km/h) first 2.17 (3.50)
second 2.63 (4.24) third 3.24 (5.21) fourth 3.93
(6.33) fifth 4.76 (7.66) sixth 5.86 (9.43) seventh
6.92 (11.13) eighth 8.37 (13.47) ninth 10.30 (16.58)
tenth 12.51 (20.13) eleventh 15.14 (24.36) twelfth
18.64 (29.99) reverse 2.85 (4.58), 5.15 (8.28), 9.05
(14.56) Clutch multiple wet disc hydraulically power
actuated by foot pedal Brakes caliper disc hy-
draulically operated by foot pedal Steering hy-
drostatic and articulated Power take-off 1000 rpm
at 2098 engine rpm Unladen tractor mass 24106
lb (10934 kg).

REPAIRS AND ADJUSTMENTS: No repairs
or adjustments.

DRAWBAR PERFORMANCE **MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
2nd Gear									
163.74 (122.10)	25061 (111.47)	2.45 (3.94)	2223	9.45	0.492 (0.299)	14.21 (2.80)	182 (83)	76 (24)	28.75 (97.36)
3rd Gear									
178.54 (133.14)	23717 (105.50)	2.82 (4.54)	2046	8.09	0.463 (0.282)	15.09 (2.97)	183 (84)	76 (24)	28.75 (97.36)
4th Gear									
189.20 (141.09)	21714 (96.59)	3.27 (5.26)	1903	5.79	0.437 (0.266)	16.01 (3.15)	184 (84)	76 (24)	28.75 (97.36)
5th Gear									
191.67 (142.93)	17867 (79.48)	4.02 (6.47)	1900	3.92	0.432 (0.263)	16.18 (3.19)	185 (85)	82 (28)	28.83 (97.63)
6th Gear									
193.41 (144.23)	14539 (64.67)	4.99 (8.03)	1895	2.88	0.428 (0.260)	16.35 (3.22)	186 (86)	83 (28)	28.83 (97.63)
7th Gear									
193.41 (144.23)	12198 (54.26)	5.95 (9.57)	1902	2.31	0.427 (0.260)	16.38 (3.23)	188 (86)	84 (29)	28.83 (97.63)
8th Gear									
192.83 (143.80)	10013 (44.54)	7.22 (11.62)	1900	1.81	0.431 (0.262)	16.22 (3.20)	187 (86)	86 (30)	28.82 (97.60)
9th Gear									
192.73 (143.72)	8091 (35.99)	8.93 (14.38)	1900	1.65	0.431 (0.262)	16.24 (3.20)	188 (87)	88 (31)	28.82 (97.60)

TRACTOR SOUND LEVEL WITH CAB

	dB(A)
Gear closest to 4.7 mph (7.5 km/h) 5th gear	78.0
Maximum Sound Level 4th gear	80.0
Transport speed—no load 12th gear	76.5
Bystander	—

TIRES AND WEIGHT

Rear Tires—No., size, ply & psi (kPa)

Front Tires—No., size, ply & psi (kPa)

Height of Drawbar

Static Weight with Operator—Rear

—Front

—Total

Tested Without Ballast

Four 18.4R38; *, inner 14 (95) outer 12 (85)

Four 18.4R38; *, inner 14 (95) outer 12 (85)

13.5 in (345 mm)

11772 lb (5340 kg)

12500 lb (5670 kg)

24272 lb (11010 kg)

REMARKS: All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. For the maximum power tests, the fuel temperature at the injection pump inlet was maintained at 130° F (54° C). The drawbar pull in 2nd gear was limited to avoid tractor bouncing. The performance figures on this summary were taken from a test conducted under the OECD Code II restricted standard test code procedure.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **1649**, Summary 087, August 20, 1991.

LOUIS I. LEVITICUS

Engineer-in-Charge

K. VON BARGEN

R. D. GRISSO

G. J. HOFFMAN

Board of Tractor Test Engineers

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: III

Quick Attach: yes

Maximum Force Exerted Through Whole Range:

12942 lbs (57.5 kN)

i) Opening pressure of relief valve:

NA

Sustained pressure at compensator cutoff:

2550 psi (176 bar)

ii) Pump delivery rate at minimum pressure:

29.0 GPM (109.8 l/min)

iii) Pump delivery rate at maximum hydraulic power:


24.9 GPM (94.3 l/min)

Delivery pressure:

2350 psi (162 bar)

Power:

34.1 HP (25.5 kW)



HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	29.1	740
B	21.0	533
C	25.6	651
D	25.1	637
E	11.4	289
F	9.9	251
G	32.3	820
H	2.2	56
I	22.8	579
J	22.4	569
K	23.0	584
L	52.2	1326
L'	57.2	1453
M	20.0	508
N	42.0	1067
O	5.2	132
P	44.4	1128
Q	37.6	956
R	37.8	959

L' to end of Quick Attach



Case International 9230 Diesel

Agricultural Research Division
Institute of Agriculture and Natural Resources
University of Nebraska—Lincoln
Darrell Nelson, Dean and Director