

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

2012

Test 2045: John Deere 9560RT

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Test 2045: John Deere 9560RT" (2012). *Nebraska Tractor Tests*. 2448.
<https://digitalcommons.unl.edu/tractormuseumlit/2448>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA OECD TRACTOR TEST 2045—SUMMARY 836

JOHN DEERE 9560RT DIESEL

18 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
SEE NOTE 1 - PAGE 2					
Rated Engine Speed—(PTO speed—1108 rpm)					
309.98 (231.15)	2099	20.49 (77.56)	0.465 (0.283)	15.13 (2.98)	Fuel used during active exhaust regeneration -2.88 gal (10.90 l) (see Note 2 p.2)
Standard Power Take-off Speed—(PTO speed—1000 rpm)					
346.35 (258.27)	1895	20.83 (78.85)	0.423 (0.258)	16.63 (3.28)	
Maximum Power (1 hour)					
354.45 (264.31)	1650	20.41 (77.25)	0.405 (0.247)	17.37 (3.42)	

VARYING POWER AND FUEL CONSUMPTION

309.98 (231.15)	2099	20.49 (77.56)	0.465 (0.283)	15.13 (2.98)	Air temperature
263.50 (196.49)	2099	18.73 (70.90)	0.500 (0.304)	14.07 (2.77)	73°F (23°C)
199.10 (148.47)	2119	15.88 (60.10)	0.561 (0.341)	12.54 (2.47)	Relative humidity
134.50 (100.30)	2140	13.06 (49.44)	0.684 (0.416)	10.30 (2.03)	25%
67.60 (50.41)	2160	10.00 (37.84)	1.041 (0.633)	6.76 (1.33)	Barometer
2.30 (1.72)	2177	7.26 (27.48)	22.217 (13.514)	0.32 (0.06)	28.32" Hg (95.90 kPa)

Maximum Torque - 1175 lb.-ft. (1593 Nm) at 1400 rpm

Maximum Torque Rise - 51.7%

Torque rise at 1679 engine rpm - 43%

Power increase at 1650 engine rpm - 14.3%

DRAWBAR PERFORMANCE (Unballasted)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F cool- ing med	°C Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—7th Gear									
433.29 (323.10)	32100 (142.79)	5.06 (8.14)	2100	1.9	0.458 (0.278)	15.39 (3.03)	188 (87)	49 (9)	29.03 (98.31)
75% of Pull at Maximum Power—7th Gear									
338.01 (252.05)	24012 (106.81)	5.28 (8.49)	2165	1.3	0.490 (0.298)	14.36 (2.83)	191 (88)	72 (22)	28.67 (97.09)
50% of Pull at Maximum Power—7th Gear									
228.96 (170.74)	15994 (71.14)	5.37 (8.63)	2189	0.6	0.577 (0.351)	12.20 (2.40)	189 (87)	78 (26)	28.58 (96.78)
75% of Pull at Reduced Engine Speed—10th Gear									
337.94 (252.00)	24141 (107.38)	5.25 (8.45)	1576	1.2	0.426 (0.259)	16.53 (3.26)	201 (94)	73 (23)	28.66 (97.05)
50% of Pull at Reduced Engine Speed—10th Gear									
228.90 (170.69)	16069 (71.48)	5.34 (8.59)	1594	0.6	0.469 (0.285)	15.02 (2.96)	192 (89)	78 (26)	28.57 (96.75)

Location of tests: Nebraska Tractor Test Laboratory, University of Nebraska, Lincoln, Nebraska 68583-0832

Dates of tests: October 12 - 23, 2012

Manufacturer: John Deere Tractor Works, 3500 East Donald St., P.O. Box 270, Waterloo Ia, 50704-0270

FUEL, OIL and TIME: Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.8455 Fuel weight 7.040 lbs/gal (0.844 kg/l) Oil SAE 15W-40 API service classification CJ-4 Transmission and hydraulic lubricant John Deere Hy-Gard fluid Total time engine was operated: 31.5 hours

ENGINE: Make John Deere Diesel Type six cylinder vertical with two turbochargers and air to air aftercooler Serial No. *RG6135R002747* Crankshaft lengthwise Rated engine speed 2100 Bore and stroke 5.197" x 6.496" (132.0 mm x 165.0 mm) Compression ratio 16.0 to 1 Displacement 826 cu in (13548 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements and aspirator Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, separate radiators for hydraulic and transmission oil, radiator for rear axle oil Fuel filter two paper cartridges Fuel cooler radiator for returned fuel Exhaust regenerative particulate filter integrated within a vertical muffler Cooling medium temperature control 3 thermostats and variable speed fan

ENGINE OPERATING PARAMETERS: Fuel rate: Stationary PTO operation 141.5 - 153.4 lb/h (64.2 - 69.6 kg/h), (460 engine hp) 161.8 - 175.3 lb/h (73.4 - 79.5 kg/h), (485 engine hp) 168.7 - 182.8 lb/h (76.5 - 82.9 kg/h), (510 engine hp) 177.2 - 191.9 lb/h (80.4 - 87.1 kg/h), (560 engine hp) 192.6 - 208.7 lb/h (87.4 - 94.6 kg/h) High idle: 2215 - 2265 rpm (2160 - 2200 rpm with PTO engaged) Turbo boost: (560 engine hp) nominal 35.5 - 39.9 psi (245 - 275 kPa) as measured 38.0 psi (260 kPa)

CHASSIS: Type track layer-rubber tracked Serial No. *1RW9560RJCP901320* Track width 107.4" (2728 mm) Length of track on ground 111.0" (2819 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio with full range operator controlled power shift Nominal travel speeds mph (km/h) first 2.51 (4.04) second 3.09 (4.97) third 3.41 (5.49) fourth 3.82 (6.14) fifth 4.20 (6.76) sixth 4.70 (7.56) seventh 5.20 (8.36) eighth 5.77 (9.29) ninth 6.39 (10.29) tenth 7.10 (11.43) eleventh 7.85 (12.63) twelfth 8.73 (14.05) thirteenth 9.66 (15.55) fourteenth 10.75 (17.30) fifteenth 13.29 (21.39) sixteenth 16.35 (26.31) seventeenth 20.07 (32.30) eighteenth 24.72 (39.77) reverse 2.51 (4.04), 3.41 (5.49), 3.82 (6.14), 5.20 (8.36), 5.77 (9.29), 7.85 (12.63)

DRAWBAR PERFORMANCE

(Unballasted at 2100 rpm)

MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp.°F cool- ing med	°C Air dry bulb	Barom. inch Hg (kPa)
1st Gear									
282.13 (210.38)	48255 (214.65)	2.20 (3.53)	2136	13.8	0.585 (0.356)	12.04 (2.37)	186 (86)	53 (11)	28.71 (97.22)
2nd Gear									
324.38 (241.89)	42167 (187.57)	2.89 (4.64)	2101	6.3	0.517 (0.314)	13.62 (2.68)	187 (86)	56 (13)	28.71 (97.22)
3rd Gear									
342.89 (255.69)	39361 (175.09)	3.27 (5.25)	2100	4.0	0.491 (0.298)	14.35 (2.83)	187 (86)	53 (12)	28.89 (97.83)
4th Gear									
368.44 (274.74)	37626 (167.37)	3.68 (5.91)	2100	3.5	0.477 (0.290)	14.76 (2.91)	187 (86)	53 (12)	28.91 (97.90)
5th Gear									
391.22 (291.73)	36192 (160.99)	4.06 (6.53)	2099	3.1	0.469 (0.285)	15.00 (2.95)	188 (87)	53 (12)	28.90 (97.87)
6th Gear									
425.29 (317.14)	35070 (156.00)	4.55 (7.31)	2101	2.9	0.467 (0.284)	15.08 (2.97)	189 (87)	49 (9)	29.03 (98.31)
7th Gear									
433.29 (323.10)	32100 (142.79)	5.06 (8.14)	2101	2.3	0.458 (0.278)	15.39 (3.03)	188 (87)	49 (9)	29.03 (98.31)
8th Gear									
436.38 (325.41)	28947 (128.76)	5.65 (9.09)	2101	1.7	0.454 (0.276)	15.49 (3.05)	189 (87)	49 (9)	29.03 (98.31)
9th Gear									
434.24 (323.81)	25914 (115.27)	6.29 (10.11)	2101	1.3	0.456 (0.277)	15.44 (3.04)	188 (87)	50 (10)	29.03 (98.31)
10th Gear									
435.57 (324.80)	23290 (103.60)	7.02 (11.29)	2101	1.0	0.456 (0.277)	15.43 (3.04)	189 (87)	50 (10)	29.01 (98.24)
11th Gear									
435.88 (325.04)	21038 (93.58)	7.77 (12.50)	2100	0.8	0.456 (0.277)	15.45 (3.04)	191 (88)	52 (11)	28.99 (98.17)
12th Gear									
434.89 (324.30)	18867 (83.92)	8.65 (13.91)	2101	0.7	0.454 (0.276)	15.51 (3.05)	191 (88)	52 (11)	28.99 (98.17)

Clutch wet multiple disc hydraulically actuated by foot pedal **Brakes** wet multiple disc hydraulically actuated foot pedal **Steering** electro-hydraulic differential steering controlled by steering wheel **Power take-off** 1000 rpm at 1895 engine rpm **Unladen tractor mass** 47015 lb (21326 kg)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE 1. The engine on this model operates in a derated mode when the PTO is engaged. This run was done with the field cruise system engaged.

NOTE 2. The manufacturer declares that the average time between active regenerations is 15 hours, while operated in Auto Filter Cleaning Mode, at rated speed, full PTO load, under steady state conditions.

NOTE 3. The 9560RT engine has an electronic control system which provides a vehicle protection system to avoid overloading the drive train. This system provides four different engine power levels. At 2100 rpm the engine produces up to 460 hp when the transmission is in forward gears 1 through 3. At 2100 rpm the engine produces 485 hp when the transmission is in gear 4. The engine produces 510 hp when the transmission is in gear 5. The engine produces 560 hp at 2100 rpm for all other gears.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. For the maximum power tests the fuel temperature at the primary fuel filter was maintained at 104°F (40°C). The performance figures on this summary were taken from a test conducted under the OECD Code II test code procedure.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **2045**, Nebraska Summary 836, February 20, 2013.

Roger M. Hoy
Director

M.R. Riley
P.J. Jasa
J.D. Luck
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB

	dB(A)
At no load in 6th gear	72.5
Transport speed-no load- 18th gear	75.4
Bystander in 18th gear	88.9

TIRES, BALLAST AND WEIGHT

	With Ballast	Without Ballast
Track width	36.0 in (915 mm)	36.0 in (915 mm)
Ballast - Cast iron (front)	3235 lb (1467 kg)	None
- Cast iron (idlers)	2520 lb (1143 kg)	None
- Cast iron (side)	1055 lb (478 kg)	None
Height of Drawbar	20.5 in (520 mm)	20.0 in (510 mm)
Static Weight with operator	54000 lb (24494 kg)	47190 lb (21405 kg)

DRAWBAR PERFORMANCE
(Unballasted at 1800 RPM)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
282.17 (210.41)	48276 (214.74)	2.20 (3.53)	2135	13.8	1st Gear 0.585 (0.356)	12.03 (2.37)	186 (86)	53 (11)	28.71 (97.22)
334.73 (249.61)	46411 (206.44)	2.71 (4.35)	2033	9.2	2nd Gear 0.517 (0.314)	13.62 (2.68)	188 (87)	59 (15)	28.71 (97.22)
358.86 (267.60)	45320 (201.59)	2.97 (4.78)	1987	7.8	3rd Gear 0.487 (0.296)	14.45 (2.85)	190 (88)	61 (16)	28.70 (97.19)
387.29 (288.80)	44331 (197.19)	3.28 (5.28)	1945	7.0	4th Gear 0.470 (0.286)	14.98 (2.95)	194 (90)	66 (19)	28.70 (97.19)
416.55 (310.62)	43616 (194.01)	3.58 (5.76)	1920	6.5	5th Gear 0.459 (0.279)	15.35 (3.02)	199 (93)	66 (19)	28.69 (97.16)
454.90 (339.22)	42776 (190.27)	3.99 (6.42)	1904	6.2	6th Gear 0.456 (0.277)	15.44 (3.04)	210 (99)	68 (20)	28.68 (97.12)
461.73 (344.31)	41303 (183.72)	4.19 (6.74)	1803	5.7	7th Gear 0.447 (0.272)	15.73 (3.10)	215 (102)	70 (21)	28.68 (97.12)
482.37 (359.70)	38069 (169.34)	4.76 (7.65)	1800	3.7	8th Gear 0.430 (0.261)	16.38 (3.23)	202 (94)	53 (12)	28.92 (97.93)
482.84 (360.05)	34031 (151.38)	5.32 (8.56)	1800	2.6	9th Gear 0.429 (0.261)	16.41 (3.23)	205 (96)	53 (12)	28.90 (97.87)
490.50 (365.76)	30867 (137.30)	5.96 (9.59)	1801	1.9	10th Gear 0.421 (0.256)	16.73 (3.30)	207 (97)	53 (12)	28.96 (98.07)
491.69 (366.65)	27898 (124.10)	6.61 (10.64)	1801	1.5	11th Gear 0.420 (0.256)	16.76 (3.30)	210 (99)	53 (12)	28.96 (98.07)
491.97 (366.86)	25095 (111.63)	7.35 (11.83)	1803	1.3	12th Gear 0.420 (0.256)	16.76 (3.30)	211 (99)	53 (12)	28.94 (98.00)
484.80 (361.51)	22234 (98.90)	8.18 (13.16)	1800	0.9	13th Gear 0.424 (0.258)	16.61 (3.27)	213 (101)	53 (12)	28.94 (98.00)

Lugging ability in 11th gear

Crankshaft speed rpm	2100	2000	1899	1801	1701	1501	1400	1104
Pull-lbs (kN)	21038 (93.58)	23885 (106.25)	26075 (115.99)	27611 (122.82)	28903 (128.57)	29792 (132.52)	29534 (131.37)	27646 (122.98)
Increase in pull%	0	14	24	31	37	42	40	31
Power-Hp (kW)	435.88 (325.04)	469.50 (350.11)	485.84 (362.29)	487.21 (363.31)	480.04 (357.97)	436.31 (325.36)	403.30 (300.74)	298.95 (222.93)
Speed-mph (km/h)	7.77 (12.50)	7.37 (11.86)	6.99 (11.25)	6.62 (10.65)	6.23 (10.03)	5.49 (8.84)	5.12 (8.24)	4.06 (6.53)
Slip %	0.8	1.1	1.3	1.5	1.7	1.8	1.8	1.5

DRAWBAR PERFORMANCE
(Ballasted at 1800 RPM)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
323.76 (241.43)	57845 (257.31)	2.10 (3.37)	2024	13.1	1st Gear 0.535 (0.325)	13.16 (2.59)	187 (86)	46 (8)	28.54 (96.65)
369.15 (275.27)	54111 (240.70)	2.56 (4.11)	1879	7.2	2nd Gear 0.475 (0.289)	14.81 (2.92)	190 (88)	47 (8)	28.53 (96.61)
382.58 (285.29)	52527 (233.65)	2.73 (4.39)	1800	6.5	3rd Gear 0.458 (0.279)	15.36 (3.03)	190 (88)	47 (8)	28.55 (96.68)
403.73 (301.06)	48793 (217.04)	3.11 (5.00)	1800	4.9	4th Gear 0.448 (0.272)	15.73 (3.10)	192 (89)	48 (9)	28.56 (96.72)
432.73 (322.68)	47315 (210.47)	3.43 (5.52)	1800	4.5	5th Gear 0.441 (0.268)	15.97 (3.15)	195 (90)	48 (9)	28.56 (96.72)
470.40 (350.78)	45951 (204.40)	3.84 (6.18)	1801	4.6	6th Gear 0.441 (0.268)	15.95 (3.14)	205 (96)	54 (12)	28.53 (96.61)
487.39 (363.45)	42600 (189.49)	4.29 (6.90)	1801	3.5	7th Gear 0.426 (0.259)	16.54 (3.26)	208 (98)	52 (11)	28.54 (96.65)
492.40 (367.18)	38455 (171.05)	4.80 (7.72)	1801	2.7	8th Gear 0.420 (0.255)	16.78 (3.31)	208 (98)	52 (11)	28.54 (96.65)
489.66 (365.14)	34220 (152.22)	5.37 (8.63)	1800	1.9	9th Gear 0.426 (0.259)	16.53 (3.26)	205 (96)	52 (11)	28.54 (96.65)
494.88 (369.03)	31011 (137.94)	5.99 (9.63)	1800	1.5	10th Gear 0.418 (0.254)	16.83 (3.32)	205 (96)	51 (11)	28.55 (96.68)
494.77 (368.95)	27978 (124.45)	6.63 (10.67)	1800	1.2	11th Gear 0.420 (0.255)	16.77 (3.30)	204 (96)	49 (9)	28.57 (96.75)
485.28 (361.87)	24595 (109.40)	7.40 (11.91)	1800	0.9	12th Gear 0.426 (0.259)	16.53 (3.26)	207 (97)	49 (9)	28.57 (96.75)
479.79 (357.78)	21909 (97.45)	8.21 (13.21)	1800	0.7	13th Gear 0.429 (0.261)	16.40 (3.23)	212 (100)	49 (9)	28.56 (96.72)

HYDRAULIC PERFORMANCE

CATEGORY: IV

Quick Attach: yes

OECD Static test

Maximum force exerted through whole range: 15642 lbs (69.6 kN) (1 x 90 mm and 1 x 100 mm)
21147 lbs (94.1 kN) (2 x 110 mm)

High flow pump Base pump

three outlet sets combined

i) Sustained pressure at compensator cutoff: 2927 psi (202 bar) 2959 psi (204 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed: 53.3 GPM (201.7 l/min) 32.3 GPM (122.1 l/min)
Combined flow: 85.6 GPM (323.8 l/min)


iii) Pump delivery rate at maximum hydraulic power: 52.9 GPM (200.4 l/min) 31.8 GPM (120.5 l/min)
Delivery pressure: 2550 psi (176 bar) 2772 psi (191 bar)
Power: 78.7 HP (58.7 kW) 51.5 HP (38.4 kW)

single outlet set
i) Sustained pressure at compensator cutoff: 2923 psi (202 bar) 2957 psi (204 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed: 37.2 GPM (140.7 l/min) 32.1 GPM (121.4 l/min)
iii) Pump delivery rate at maximum hydraulic power: 35.2 GPM (133.1 l/min) 32.3 GPM (122.1 l/min)
Delivery pressure: 2206 psi (152 bar) 2387 psi (165 bar)
Power: 45.2 HP (33.7 kW) 44.9 HP (33.5 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	30.7	780
B	19.7	500
C	31.9	810
D	30.4	772
E	13.2	335
F	13.8	350
G	37.6	955
H	0.7	19
I	23.1	586
J	23.8	605
K	30.9	785
L	57.0	1447
*L'	62.4	1584
M	32.4	822
N	45.6	1159
O	9.0	230
P	50.8	1291
Q	38.6	980
R	50.4	1280

*L' to Quick Attach ends



JOHN DEERE 9560RT DIESEL

Institute of Agriculture and Natural Resources
University of Nebraska-Lincoln