

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

2014

## Test 2094A: New Holland T9.530

Nebraska Tractor Test Laboratory

*University of Nebraska-Lincoln*, [tractortestlab@unl.edu](mailto:tractortestlab@unl.edu)

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Laboratory, Nebraska Tractor Test, "Test 2094A: New Holland T9.530" (2014). *Nebraska Tractor Tests*. 2511.

<https://digitalcommons.unl.edu/tractormuseumlit/2511>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA OECD TRACTOR TEST 2094A - SUMMARY 959A

## NEW HOLLAND T9.530 DIESEL

### 16 SPEED

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption		D.E.F. Consumption		Mean Atmospheric Conditions
		Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Gal/hr (l/h)	
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>						
<b>Rated Engine Speed—(PTO speed—1160 rpm)</b>						
417.16 (311.07)	2101	24.08 (91.14)	0.405 (0.247)	17.33 (3.41)	1.85 (7.02)	
<b>Maximum Power (1 hour)</b>						
468.35 (349.25)	1901	25.27 (95.66)	0.379 (0.230)	18.53 (3.65)	2.21 (8.37)	
<b>Standard Power Take-off Speed (1000 rpm)</b>						
459.94 (342.97)	1811	24.45 (92.53)	0.373 (0.227)	18.82 (3.71)	2.12 (8.01)	

#### VARYING POWER AND FUEL CONSUMPTION

417.16 (311.07)	2101	24.08 (91.14)	0.405 (0.247)	17.33 (3.41)	1.85 (7.02)	Air temperature
362.45 (270.28)	2146	21.52 (81.46)	0.417 (0.254)	16.84 (3.32)	1.66 (6.29)	73°F (23°C)
272.67 (203.33)	2155	17.24 (65.24)	0.444 (0.270)	15.82 (3.12)	1.28 (4.84)	Relative humidity
182.74 (136.27)	2163	13.06 (49.42)	0.502 (0.305)	14.00 (2.76)	0.89 (3.36)	45%
91.74 (68.41)	2176	9.04 (34.23)	0.692 (0.421)	10.15 (2.00)	0.52 (1.95)	Barometer
2.17 (1.61)	2185	5.29 (20.02)	17.156 (10.435)	0.41 (0.08)	0.26 (1.00)	29.01" Hg (98.25 kPa)

Maximum torque - 1514 lb.-ft. (2053 Nm) at 1400 rpm

Maximum torque rise - 45.2%

Torque rise at 1681 engine rpm - 35%

Power increase at 1901 engine rpm - 12.3%

#### DRAWBAR PERFORMANCE

##### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	D.E.F. Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Barom. inch Hg (kPa)
<b>Maximum Power—4th Gear</b>								
387.67 (289.08)	29229 (130.02)	4.97 (8.00)	2100	3.4	0.436 (0.265)	16.11 (3.17)	202 (94)	63 (17)
<b>75% of Pull at Maximum Power—4th Gear</b>								
300.22 (223.87)	21896 (97.40)	5.14 (8.27)	2151	2.3	0.461 (0.280)	15.23 (3.00)	203 (95)	75 (24)
<b>50% of Pull at Maximum Power—4th Gear</b>								
202.87 (151.28)	14604 (64.96)	5.21 (8.38)	2161	1.5	0.509 (0.310)	13.80 (2.72)	204 (95)	77 (25)
<b>75% of Pull at Reduced Engine Speed—8th Gear</b>								
299.40 (223.26)	21969 (97.72)	5.11 (8.22)	1407	2.4	0.389 (0.236)	18.07 (3.56)	204 (95)	76 (25)
<b>50% of Pull at Reduced Engine Speed—8th Gear</b>								
202.86 (151.27)	14588 (64.89)	5.22 (8.39)	1424	1.5	0.419 (0.255)	16.75 (3.30)	202 (94)	78 (25)

**Location of tests:** Nebraska Tractor Test Laboratory, University of Nebraska, Lincoln, Nebraska 68583-0832

**Dates of tests:** September 11- 22, 2014

**Manufacturer:** CNH Industrial America LLC, 700 State St. Racine, Wi. 53404 USA

**CONSUMABLE Fluids, OIL and TIME: Fuel** No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.8434 **Fuel weight** 7.022 lbs/gal (0.842 kg/l) **Diesel Exhaust Fluid (DEF)** 32% aqueous urea solution **DEF weight** 9.071 lbs/gal (1.087 kg/l) **Oil SAE 10W40 API service classification** CJ-4 **Transmission lubricant** New Holland Mastertran Ultrtraction fluid **Hydraulic and axle lubricant** New Holland Mastertran Ultrtraction fluid **Total time engine was operated:** 18.0 hours

**ENGINE: Make** FPT Industrial Diesel **Type** six cylinder vertical with turbocharger, air to air intercooler and D.E.F. (diesel exhaust fluid) exhaust treatment **Serial No.** 000010353 **Crankshaft** lengthwise **Rated engine speed** 2100 **Bore and stroke** 5.315" x 5.906" (135.0 mm x 150.0 mm) **Compression ratio** 16.5 to 1 **Displacement** 786 cu in (12880 ml) **Starting system** 24 volt **Lubrication** pressure **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, separate radiators for hydraulic and transmission oil **Fuel filter** two paper elements **Exhaust** DOC (diesel oxidation catalyst) and SCR (selective catalyst reduction) with a vertical muffler **Cooling medium temperature control** thermostat and variable speed fan

**ENGINE OPERATING PARAMETERS: Fuel rate:** 160.9 - 170.9 lb/h (73.0 - 77.5 kg/h) **High idle:** 2175 - 2225 rpm **Turbo boost:** nominal 21.8 - 24.7 psi (150 - 170 kPa) as measured 23.3 psi (160 kPa)

**CHASSIS: Type** four wheel drive with duals **Serial No.** \*ZEF300725\* **Tread width** rear 60.0" (1524 mm) to 130.0" (3302 mm) front 60.0" (1524 mm) to 130.0" (3302 mm) **Wheelbase** 148.0" (3759 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with full range operator controlled powershift **Nominal travel speeds mph (km/h)** first 2.97 (4.78) second 3.58 (5.76) third 4.32 (6.95) fourth 5.20 (8.37) fifth 5.97 (9.61) sixth 6.56 (10.56) seventh 7.20 (11.58) eighth 7.90 (12.72) ninth 8.69 (13.98) tenth 9.55 (15.37) eleventh 10.46 (16.84) twelfth 11.50 (18.51) thirteenth 13.20 (21.25) fourteenth 15.91 (25.60) fifteenth 19.21 (30.91) sixteenth 23.13 (37.23) reverse 4.50 (7.24), 9.05 (14.57) **Clutch** multiple wet disc electrohydraulically operated by foot pedal **Brakes** wet disc hydraulically operated by foot pedal **Steering** hydrostatic and articulated

**DRAWBAR PERFORMANCE AT 2100 ENGINE RPM**  
**DRAWBAR POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	D.E.F Consumption lb/hp.hr (kg/kW.h)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
					<b>1st Gear</b>					
300.48 (224.07)	43495 (193.48)	2.59 (4.17)	2142	13.5	0.499 (0.304)	14.08 (2.77)	0.045 (0.028)	204 (96)	64 (18)	28.75 (97.36)
					<b>2nd Gear</b>					
365.08 (272.24)	42703 (189.95)	3.21 (5.17)	2100	9.7	0.464 (0.282)	15.13 (2.98)	0.041 (0.025)	205 (96)	64 (18)	28.74 (97.33)
					<b>3rd Gear</b>					
384.64 (286.82)	35392 (157.43)	4.08 (6.56)	2100	4.6	0.440 (0.268)	15.95 (3.14)	0.040 (0.024)	203 (95)	68 (20)	28.75 (97.36)
					<b>4th Gear</b>					
387.67 (289.08)	29229 (130.02)	4.97 (8.00)	2099	3.4	0.436 (0.265)	16.11 (3.17)	0.040 (0.024)	202 (94)	63 (17)	28.66 (97.05)
					<b>5th Gear</b>					
387.68 (289.09)	25307 (112.57)	5.75 (9.25)	2100	2.7	0.437 (0.266)	16.08 (3.17)	0.040 (0.025)	203 (95)	60 (16)	28.67 (97.09)
					<b>6th Gear</b>					
390.18 (290.95)	23136 (102.91)	6.33 (10.18)	2100	2.4	0.432 (0.263)	16.27 (3.21)	0.040 (0.025)	203 (95)	61 (16)	28.67 (97.09)
					<b>7th Gear</b>					
387.17 (288.71)	20890 (92.92)	6.95 (11.18)	2099	2.1	0.437 (0.266)	16.08 (3.17)	0.039 (0.024)	203 (95)	65 (18)	28.67 (97.09)
					<b>8th Gear</b>					
389.50 (290.45)	19098 (84.95)	7.65 (12.31)	2099	1.9	0.434 (0.264)	16.18 (3.19)	0.038 (0.023)	203 (95)	71 (22)	28.67 (97.09)
					<b>9th Gear</b>					
385.65 (287.58)	17158 (76.32)	8.43 (13.57)	2100	1.7	0.429 (0.261)	16.35 (3.22)	0.038 (0.023)	202 (94)	73 (23)	28.66 (97.05)

**Power take-off** MY 2014 - 1000 rpm at 1998 engine rpm, MY 2015 - 1000 rpm at 1811 engine rpm **Unladen tractor mass** 42290 lb (19182 kg)

**Note 1:** The performance results on this report were obtained from tests carried out on the Case IH Steiger 470 Diesel.

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. For the maximum power tests, the fuel temperature at the primary fuel filter was maintained at 110°F (43°C). The performance figures on this Summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **2094A**, Nebraska Summary 959A, December 19, 2014.

Roger M. Hoy  
Director

M.F. Kocher  
J.D. Luck  
P.J. Jasa  
Board of Tractor Test Engineers

**TRACTOR SOUND LEVEL WITH CAB** **dB(A)**

At no load in 4th gear	73.9
Bystander in 16th gear	87.8

**TIRES AND WEIGHT**

**Rear Tires** -No., size, ply & psi (kPa)

**Front Tires** -No., size, ply & psi (kPa)

**Height of Drawbar**

**Static Weight with operator** -Rear

-Front

-Total

**Tested Without Ballast**

Four 480/95R50;\*\*\*;9(65)

Four 480/95R50;\*\*\*;12(85)

21.0 in (535 mm)

17920 lb (8128 kg)

24545 lb(11134 kg)

42465 lb(19262 kg)

**DRAWBAR PERFORMANCE AT 1900 RPM**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	D.E.F Consumption lb/hp.hr (kg/kW.h)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
1st Gear										
300.99 (224.44)	43364 (192.89)	2.61 (4.19)	2143	13.0	0.498 (0.303)	14.10 (2.78)	0.045 (0.028)	204 (96)	65 (18)	28.75 (97.36)
2nd Gear										
365.86 (272.82)	42347 (188.37)	3.24 (5.21)	2104	8.8	0.462 (0.281)	15.20 (3.00)	0.041 (0.025)	205 (96)	64 (18)	28.74 (97.33)
3rd Gear										
411.62 (306.94)	41051 (182.60)	3.76 (6.05)	1985	6.8	0.428 (0.261)	16.40 (3.23)	0.044 (0.027)	204 (95)	69 (20)	28.75 (97.36)
4th Gear										
427.20 (318.56)	36225 (161.13)	4.42 (7.11)	1900	5.2	0.416 (0.253)	16.88 (3.33)	0.042 (0.025)	203 (95)	68 (20)	28.75 (97.36)
5th Gear										
432.36 (322.41)	31460 (139.94)	5.15 (8.29)	1900	4.0	0.412 (0.250)	17.06 (3.36)	0.043 (0.026)	203 (95)	61 (16)	28.66 (97.05)
6th Gear										
434.61 (324.09)	28661 (127.49)	5.69 (9.16)	1900	3.1	0.409 (0.249)	17.19 (3.39)	0.043 (0.026)	203 (95)	62 (17)	28.67 (97.08)
7th Gear										
433.19 (323.03)	25982 (115.57)	6.25 (10.06)	1900	2.8	0.409 (0.249)	17.18 (3.38)	0.042 (0.025)	203 (95)	65 (18)	28.67 (97.08)
8th Gear										
435.16 (324.50)	23697 (105.41)	6.89 (11.09)	1899	2.5	0.408 (0.248)	17.23 (3.39)	0.042 (0.025)	203 (95)	67 (19)	28.66 (97.05)
9th Gear										
432.87 (322.79)	21409 (95.23)	7.58 (12.20)	1898	2.2	0.412 (0.250)	17.05 (3.36)	0.041 (0.025)	203 (95)	73 (23)	28.67 (97.08)
10th Gear										
430.62 (321.11)	19354 (86.09)	8.34 (13.42)	1900	2.0	0.415 (0.252)	16.93 (3.33)	0.041 (0.025)	203 (95)	73 (23)	28.67 (97.08)

## HYDRAULIC PERFORMANCE

CATEGORY: IVN

Quick Attach: yes

OECD Static test

Maximum force exerted through whole range: 21903 lbs (97.4 kN)

### Three outlet sets combined

	Standard pump	High flow pump
i) Sustained pressure of the open relief valve:	2877 psi (198 bar)	3042 psi (210 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	43.8 GPM (165.8 l/min)	59.0 GPM (223.4 l/min)
iii) Pump delivery rate at maximum hydraulic power:	43.3 GPM (163.7 l/min)	56.2 GPM (212.9 l/min)
Delivery pressure:	2526 psi (174 bar)	2649 psi (183 bar)
Power:	63.7 HP (47.5 kW)	86.9 Hp (64.8 kW)

### Single outlet set

ii) Pump delivery rate at minimum pressure and rated engine speed:	42.8 GPM (162.2 l/min)	48.4 GPM (183.4 l/min)
iii) Pump delivery rate at maximum hydraulic power:	42.7 GPM (161.6 l/min)	44.6 GPM (168.9 l/min)
Delivery pressure:	2024 psi (139 bar)	2091 psi (144 bar)
Power:	50.4 HP (37.6 kW)	54.4 Hp (40.6 kW)

## MegaFlow system

### Two outlet sets combined

	Standard pump	TwinFlow pump
i) Sustained pressure at compensator cutoff:	2877 psi (198 bar)	2855 psi (197 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	43.8 GPM (165.8 l/min)	57.3 GPM (217.0 l/min)
Combined flow:	101.1 GPM (382.8 l/min)	
iii) Pump delivery rate at maximum hydraulic power:	43.3 GPM (163.7 l/min)	56.4 GPM (213.6 l/min)
Delivery pressure:	2526 psi (174 bar)	2479 psi (171 bar)
Power:	63.7 HP (47.5 kW)	81.6 Hp (60.9 kW)


### Two outlet sets combined

	High flow pump	TwinFlow pump
i) Sustained pressure at compensator cutoff:	2993 psi (206 bar)	2855 psi (197 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	61.0 GPM (230.9 l/min)	57.3 GPM (217.0 l/min)
Combined flow:	118.3 GPM (447.9 l/min)	
iii) Pump delivery rate at maximum hydraulic power:	56.7 GPM (214.7 l/min)	56.4 GPM (213.6 l/min)
Delivery pressure:	2517 psi (174 bar)	2479 psi (171 bar)
Power:	83.3 HP (62.1 kW)	81.6 Hp (60.9 kW)

## HITCH DIMENSIONS AS TESTED - NO LOAD

	inch	mm
A	39.0	990
B	30.7	780
C	27.9	709
D	26.5	673
E	13.5	342
F	16.3	415
G	38.2	970
H	2.6	66
I	21.2	538
J	21.9	555
K	30.5	775
L	58.5	1487
*L'	65.8	1671
M	53.6	1361
N	43.0	1093
O	9.1	230
P	52.6	1335
Q	46.5	1181
R	39.4	1000

\*L' to Quick Attach ends



**NEW HOLLAND T9.530 Diesel**