

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

2004

Nebraska Summary: S458 New Holland TN75DA

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Nebraska Summary: S458 New Holland TN75DA" (2004). *Nebraska Tractor Tests*. 2883.

<https://digitalcommons.unl.edu/tractormuseumlit/2883>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TESTS 2131 and 2150—NEBRASKA SUMMARY 458 NEW HOLLAND TN75DA DIESEL 16 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed (PTO speed—564 rpm)					
63.4 (47.3)	2295	3.94 (14.91)	0.435 (0.264)	16.10 (3.17)	
Maximum Power (2 hours)					
64.4 (48.0)	2248	3.96 (15.00)	0.431 (0.262)	16.24 (3.20)	
Standard Power Take-off speed (539 rpm)					
63.4 (47.3)	2193	3.89 (14.74)	0.429 (0.261)	16.29 (3.21)	
VARYING POWER AND FUEL CONSUMPTION					
63.4 (47.3)	2295	3.94 (14.92)	0.435 (0.264)	16.10 (3.17)	Air temperature
55.5 (41.4)	2364	3.49 (13.23)	0.440 (0.268)	15.89 (3.13)	77°F (25°C)
42.4 (31.6)	2403	2.88 (10.90)	0.475 (0.289)	14.72 (2.90)	Relative humidity
28.7 (21.4)	2443	2.14 (8.11)	0.522 (0.317)	13.41 (2.64)	43%
14.6 (10.9)	2480	1.61 (6.09)	0.771 (0.469)	9.07 (1.79)	Barometer
--	2512	0.98 (3.70)	--	--	30.3" Hg (102.7 kPa)
Maximum Torque -202.2 lb.-ft. (274.2 Nm) at 1410 rpm Maximum Torque Rise -39.1% Torque rise at 1810 engine rpm -15%					

Location of tests: Alma Mater Studiorum, University Di Bologna, Via Gandolfi, 19-40057, Cadriano, Bologna, Italy

Dates of tests: October 2003 to April, 2004

Manufacturer: CNH America LLC, 700 State St. Racine, WI. 53404 USA

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.840 **Fuel weight** 6.99 lbs/gal (0.838 kg/l) **Oil SAE** 15W40 **API service classification** CF-4/SG **Oil consumption for 10 hours** 0.03 lb (15 gm) **Transmission and hydraulic lubricant** Ambra Multi G 15W40 **Front axle lubricant** Ambra Multi G

ENGINE: Make Iveco Diesel **Type** three cylinder vertical with turbocharger **Serial No.** 873941 **Crankshaft** lengthwise **Rated engine speed** 2300 **Bore and stroke** 4.094" x 4.528" (104.0 mm x 115.0 mm) **Compression ratio** 18.0 to 1 **Displacement** 179 cu in (2930 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: Type 2WD and front wheel assist **Serial No.** HJE297923 **Tread width** rear 48.5" (1232 mm) to 76.7" (1949 mm) front: 2WD - 56.7" (1439 mm) to 63.3" (1607 mm), FWA - 48.7" (1236 mm) to 76.6" (1945 mm) **Wheel base** 2WD - 83.9" (2130 mm) FWA - 81.3" (2065 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio **Nominal travel speeds (30 km/h transmission) mph (km/h)** first 0.39 (0.63) second 0.58 (0.93) third 0.85 (1.37) fourth 1.26 (2.03) fifth 1.63 (2.63) sixth 2.00 (3.22) seventh 2.43 (3.91) eighth 2.98 (4.79) ninth 3.57 (5.75) tenth 4.37 (7.04) eleventh 5.30 (8.53) twelfth 5.77 (9.28) thirteenth 6.49 (10.44) fourteenth 8.60 (13.84) fifteenth 12.64 (20.34) sixteenth 18.72 (30.13) reverse 0.38 (0.61), 0.56 (0.90), 0.83 (1.33), 1.22 (1.97), 1.58 (2.54), 1.93 (3.11), 2.36 (3.79), 2.88 (4.64), 3.46 (5.57), 4.24 (6.82), 5.13 (8.26), 5.59 (8.99), 6.28 (10.11), 8.33 (13.40), 12.24 (19.70), 18.14 (29.19) **Clutch** dual dry disc operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2196 engine rpm or 1000 rpm at 2260 engine rpm **Unladen tractor mass** 2WD - 5895 lb (2675 kg), FWA - 6450 lb (2925 kg)

DRAWBAR PERFORMANCE(40 km/h trans.)

BALLASTED - FRONT DRIVE ENGAGED FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
75% of Pull at Maximum Power—Five Hours 10th (3MHi) Gear									
44.0 (32.8)	2925 (13.02)	5.64 (9.07)	2364	3.7	0.534 (0.325)	13.10 (2.58)	198 (92)	48 (9)	30.1 (102.0)
MAXIMUM POWER IN SELECTED GEARS									
7th (2MLo) Gear									
48.0 (35.8)	6590 (29.31)	2.73 (4.40)	2335	14.9	0.514 (0.313)	13.60 (2.68)	196 (91)	54 (12)	30.0 (101.7)
8th (2MHi) Gear									
54.3 (40.5)	6065 (26.98)	3.36 (5.41)	2239	11.7	0.499 (0.303)	14.02 (2.76)	201 (94)	55 (13)	30.0 (101.7)
9th (3MLo) Gear									
54.0 (40.3)	4805 (21.38)	4.21 (6.78)	2245	6.6	0.497 (0.302)	14.07 (2.77)	208 (98)	57 (14)	30.0 (101.7)
10th (3MHi) Gear									
53.9 (40.2)	3885 (17.29)	5.20 (8.37)	2237	5.3	0.500 (0.304)	13.97 (2.75)	207 (97)	57 (14)	30.0 (101.7)
11th (4MLo) Gear									
54.2 (40.4)	3205 (14.25)	6.34 (10.20)	2230	3.8	0.501 (0.305)	13.96 (2.75)	205 (96)	55 (13)	30.0 (101.7)
12th (1Hi) Gear									
55.4 (41.3)	2930 (13.04)	7.09 (11.41)	2261	3.7	0.494 (0.301)	14.15 (2.79)	199 (93)	55 (13)	30.0 (101.7)
13th (4MHi) Gear									
54.9 (40.9)	2530 (11.26)	8.13 (13.09)	2247	3.4	0.494 (0.300)	14.15 (2.79)	201 (94)	54 (12)	30.0 (101.7)
14th (2Hi) Gear									
53.1 (39.6)	1875 (8.34)	10.62 (17.09)	2260	2.3	0.508 (0.309)	13.76 (2.71)	208 (98)	54 (12)	30.0 (101.7)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 5258 lbs (2385 kg) 3 point lift capacity. The performance results on this summary were taken from OECD tests conducted under the Code I Test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **2131** and **2150**, Nebraska Summary 458, August 29, 2005.

Leonard L. Bashford
Director

M.F. Kocher
V.I. Adamchuk
W.P. Campbell
Board of Tractor Test Engineers

TN75DA-FWA(40 km/h transmission)

TIRES, BALLAST AND WEIGHT		With Ballast	Without Ballast
Rear Tires	-No., size, ply & psi (kPa)	Two 16.9R30; **,20 (135)	Two 16.9R30; **,20 (135)
Ballast	-Liquid (total)	None	None
	-Cast Iron (total)	440 lb (200 kg)	None
Front Tires	-No., size, ply & psi (kPa)	Two 11.2R24; **,17 (120)	Two 11.2R24; **,17 (120)
Ballast	-Liquid (total)	None	None
	-Cast Iron (total)	640 lb (290 kg)	None
Height of Drawbar		20.1 in (510 mm)	20.1 in (510 mm)
Static Weight with Operator	- Rear	4595 lb (2085 kg)	4300 lb (1950 kg)
	- Front	3090 lb (1405 kg)	2315 lb (1050 kg)
	- Total	7695 lb (3490 kg)	6615 lb (3000 kg)

DRAWBAR PERFORMANCE(30 km/h trans.)

BALLASTED - 2WD

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp.°F cool- ing med	Temp.°C Air dry bulb	Barom. inch Hg (kPa)
75% of Pull at Maximum Power—Five Hours 10th (3 MHi) Gear									
43.0 (32.1)	3845 (17.11)	4.19 (6.75)	2339	7.0	0.514 (0.312)	13.61 (2.68)	181 (83)	55 (13)	30.3 (102.6)

MAXIMUM POWER IN SELECTED GEARS

9th (3M Lo) Gear									
44.1 (32.9)	5405 (24.04)	3.06 (4.93)	2283	15.0	0.602 (0.366)	11.62 (2.29)	183 (84)	63 (17)	30.3 (102.7)
10th(3M Hi) Gear									
51.5 (38.4)	5105 (22.72)	3.78 (6.08)	2241	13.0	0.506 (0.308)	13.81 (2.72)	183 (84)	63 (17)	30.3 (102.7)
11th (4 MLo) Gear									
53.8 (40.1)	4190 (18.63)	4.82 (7.76)	2254	8.9	0.499 (0.304)	14.01 (2.76)	181 (83)	61 (16)	30.3 (102.7)
12th (1 Hi) Gear									
54.6 (40.7)	3845 (17.10)	5.33 (8.57)	2253	7.3	0.488 (0.297)	14.31 (2.82)	181 (83)	61 (16)	30.3 (102.7)
13th(4M Hi) Gear									
54.9 (40.9)	3395 (15.09)	6.07 (9.77)	2245	5.2	0.487 (0.296)	14.37 (2.83)	181 (83)	61 (16)	30.3 (102.7)
14th(2 Hi) Gear									
53.1 (39.6)	2415 (10.75)	8.25 (13.27)	2251	3.3	0.496 (0.301)	14.11 (2.78)	181 (83)	61 (16)	30.2 (102.7)

TN75DA-2WD (30km/h transmission)

TIRES, BALLAST AND WEIGHT	With Ballast	Without Ballast
Rear Tires	-No., size, ply & psi (kPa) Two 16.9R30;**,20 (135)	Two 16.9R30;**,20 (135)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 440 lb (200 kg)	None
Front Tires	-No., size, ply & psi (kPa) Two 7.50-16; 8; 36 (250)	Two 7.50-16; 8; 36 (250)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 640 lb (290 kg)	None
Height of Drawbar	30.3 in (770 mm)	26.4 in (670 mm)
Static Weight with Operator	- Rear 4345 lb (1970 kg)	4080 lb (1850 kg)
	- Front 2800 lb (1270 kg)	1985 lb (900 kg)
	- Total 7145 lb (3240 kg)	6065 lb (2750 kg)

TRACTOR SOUND LEVEL WITH CAB	FWA dB(A)	2WD dB(A)
At no load in 9th (3M Lo) gear	79.8	78.9
Bystander in 16th (4 Hi) gear	83.9	83.0

CENTER OF GRAVITY - 2WD

Horizontal distance forward from centerline of rear wheels	27.4" (697 mm)
Vertical distance above roadway	31.9" (810 mm)
Horizontal distance from center of rear wheel tread	0.5" (13 mm) to the left

CENTER OF GRAVITY - FWA

Horizontal distance forward from centerline of rear wheels	28.5" (723 mm)
Vertical distance above roadway	31.9" (810 mm)
Horizontal distance from center of rear wheel tread	0.5" (13 mm) to the left

TURNING ON A CONCRETE SURFACE (2WD)

Turning radius—without brake right 141" (3.58 m) left 139" (3.53 m)
Turning space radius—without brake right 145" (3.68 m) left 143" (3.63 m)

TURNING ON A CONCRETE SURFACE (FWA)

Turning radius—without brake right 141" (3.58 m) left 141" (3.58 m)
Turning space radius—without brake right 146" (3.72 m) left 146" (3.72 m)

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum force exerted through whole range: 3865 lbs (17.2 kN)

i) Opening pressure of relief valve: NA

Sustained pressure with relief valve open: 2980 psi (205 bar)

ii) Pump delivery rate at minimum pressure: 17.2 GPM (65.0 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 15.7 GPM (59.5 l/min)

Delivery pressure: 2300 psi (158 bar)

Power: 21.1 hp (15.7 kW)

THREE POINT HITCH PERFORMANCE (SAE Static Test)

Observed maximum pressure psi.(bar) 2980 (205)

Location: hydraulic pump

Hydraulic oil temperature: °F(°C) 114 (45)

Location: hydraulic sump

Category: II

Quick attach: none

System pressure 2685 psi (185 Bar)

Hitch point distance to ground level in. (mm) 14.6 (370) 19.4 (492) 24.2 (614) 29.0 (736) 33.8 (858) 38.6 (980)

Lift force on frame lb 4810 5265 5230 4975 4665 4325

" " " " " " (kN) (21.4) (23.4) (23.3) (22.1) (20.8) (19.2)

HITCH DIMENSIONS AS TESTED—NO LOAD

	SAE TEST		OECD TEST	
	inch	mm	inch	mm
A	27.2	690	27.4	697
B	10.0	255	10.0	255
C	12.3	312	12.3	312
D	10.9	276	10.9	276
E	14.2	361	12.1	308
F	7.5	189	7.5	189
G	27.2	690	27.4	695
H	1.2	30	1.2	30
I	13.4	340	13.6	345
J	19.7	501	19.9	506
K	20.6	523	20.6	523
L	40.7	1035	40.7	1035
M	21.7	550	21.7	550
N	34.6	880	34.6	880
O	14.6	370	14.7	373
P	38.7	984	43.9	1116
Q	39.8	1010	39.8	1011
R	22.4	570	22.5	572

