

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

2008

## Nebraska Summary: S621A Case-IH Magnum 180

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S621A Case-IH Magnum 180" (2008). *Nebraska Tractor Tests*. 2922.

<https://digitalcommons.unl.edu/tractormuseumlit/2922>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2423-NEBRASKA SUMMARY 621A

## CASE IH PUMA 180 DIESEL

## ALSO CASE IH MAGNUM 180 DIESEL

## 19 SPEED

### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1022 rpm)</b>					
158.6 (118.3)	2200	9.77 (37.00)	0.427 (0.260)	16.23 (3.20)	
<b>Standard Power Take-off Speed (1000 rpm)</b>					
164.4 (122.6)	2153	9.81 (37.12)	0.413 (0.251)	16.76 (3.30)	
<b>Maximum Power (1 hour)</b>					
179.8 (134.1)	1900	10.01 (37.89)	0.386 (0.235)	17.96 (3.54)	

### VARYING POWER AND FUEL CONSUMPTION

158.6 (118.3)	2200	9.77 (37.00)	0.427 (0.260)	16.23 (3.20)	Air temperature
138.5 (103.3)	2260	9.30 (35.22)	0.466 (0.283)	14.89 (2.93)	72°F (22°C)
105.3 (78.5)	2290	7.46 (28.24)	0.491 (0.299)	14.11 (2.78)	Relative humidity
70.9 (52.9)	2315	5.63 (21.33)	0.551 (0.335)	12.61 (2.48)	47%
35.7 (26.6)	2330	3.85 (14.57)	0.746 (0.454)	9.29 (1.83)	Barometer
--	2348	2.20 (8.32)	--	--	29.5" Hg (100.0 kPa)

Maximum Torque - 572.4 lb.-ft. (776.2 Nm) at 1400 rpm  
 Maximum Torque rise - 51.1%  
 Torque rise at 1800 engine rpm - 36%

### DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged)

#### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—8th Gear</b>									
132.7 (98.9)	12525 (55.71)	3.97 (6.40)	2197	6.1	0.517 (0.315)	13.44 (2.65)	183 (84)	55 (13)	29.5 (99.9)
<b>75% of Pull at Maximum Power—8th Gear</b>									
102.7 (76.6)	9375 (41.70)	4.11 (6.61)	2254	5.3	0.585 (0.356)	11.88 (2.34)	181 (83)	55 (13)	29.5 (99.9)
<b>50% of Pull at Maximum Power—8th Gear</b>									
71.7 (53.5)	6260 (27.84)	4.30 (6.92)	2300	2.9	0.665 (0.404)	10.46 (2.06)	181 (83)	55 (13)	29.5 (99.9)
<b>75% of Pull at Reduced Engine Speed—9th Gear</b>									
106.4 (79.3)	9350 (41.60)	4.27 (6.87)	1955	5.7	0.513 (0.312)	13.55 (2.67)	176 (80)	55 (13)	29.5 (99.9)
<b>50% of Pull at Reduced Engine Speed—9th Gear</b>									
72.4 (54.0)	6230 (27.72)	4.36 (7.01)	1950	3.5	0.585 (0.356)	11.88 (2.34)	176 (80)	55 (13)	29.5 (99.9)

**Location of tests:** HBLFA Francisco Josephinum  
 BLT Biomass-Logistics-Technology,  
 Rottenhauser, StraBe, 1, AT, 3250, Wieselburg,  
 Austria

**Dates of tests:** June -September, 2007.

**Manufacturer:** CNH Osterreich GmbH  
 SteyrerstraBe, 32, 4300, St. Valentin, Austria

**FUEL and OIL:** Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.835  
**Fuel weight** 6.95 lbs/gal (0.833 kg/l) **Oil SAE** 10W30 **API service classification** CG-4  
**Transmission and hydraulic lubricant** Case IH Hytran Ultra fluid **Front axle lubricant** Case IH Hytran Ultra fluid

**ENGINE:** Make CNH Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler  
**Serial No.** 374056 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.094" x 5.197" (104.0 mm x 132.0 mm) **Compression ratio** 16.5 to 1 **Displacement** 410 cu in (6728 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** two paper canisters **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS:** **Type** front wheel assist **Serial No.** Z6BH01004 **Tread width** rear 60.2" (1530 mm) to 87.8" (2230 mm) front 61.4" (1560 mm) to 89.0" (2260 mm) **Wheelbase** 113.5" (2884 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with full range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.21 (1.94) second 1.45 (2.33) third 1.74 (2.80) fourth 2.09 (3.36) fifth 2.52 (4.05) sixth 3.03 (4.87) seventh 3.49 (5.62) eighth 4.20 (6.76) ninth 5.05 (8.12) tenth 6.06 (9.76) eleventh 7.30 (11.75) twelfth 8.78 (14.13) thirteenth 10.09 (16.24) fourteenth 12.13 (19.52) fifteenth 14.57 (23.45) sixteenth 17.52 (28.20) seventeenth 21.08 (33.92) eighteenth 25.35 (40.79) nineteenth 25.35 (40.80) (1700 engine rpm) reverse 2.67 (4.30), 3.21 (5.16), 3.85 (6.20), 4.63 (7.45), 5.57 (8.96), 6.70 (10.78) **Clutch** multiple wet disc electro-hydraulically operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1950 engine rpm or 1000 rpm at 2154 engine rpm **Unladen tractor mass** 17595 lb (7980 kg)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Engaged)**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp.°F(°C) cool- ing Air dry bulb	Barom. inch Hg (kPa)	
					<b>6th Gear</b>				
121.6 (90.7)	16805 (74.76)	2.71 (4.37)	2254	13.1	0.564 (0.343)	12.33 (2.43)	180 (82)	59 (15)	29.4 (99.7)
					<b>7th Gear</b>				
137.5 (102.5)	16680 (74.20)	3.09 (4.97)	2131	9.5	0.506 (0.308)	13.75 (2.71)	180 (82)	59 (15)	29.4 (99.7)
					<b>8th Gear</b>				
146.8 (109.5)	16625 (73.96)	3.31 (5.33)	1905	9.7	0.474 (0.288)	14.67 (2.89)	185 (85)	59 (15)	29.4 (99.7)
					<b>9th Gear</b>				
149.1 (111.2)	13635 (60.65)	4.10 (6.60)	1902	6.7	0.471 (0.286)	14.77 (2.91)	181 (83)	57 (14)	29.4 (99.7)
					<b>10th Gear</b>				
146.8 (109.5)	11010 (48.97)	5.00 (8.05)	1900	5.3	0.473 (0.289)	14.65 (2.89)	183 (84)	59 (15)	29.4 (99.7)
					<b>11th Gear</b>				
148.7 (110.9)	9215 (40.99)	6.05 (9.74)	1897	4.6	0.468 (0.285)	14.86 (2.93)	181 (83)	57 (14)	29.4 (99.7)
					<b>12th Gear</b>				
142.8 (106.5)	7325 (32.59)	7.31 (11.77)	1895	4.1	0.487 (0.296)	14.26 (2.81)	180 (82)	57 (14)	29.4 (99.7)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments.

**NOTE:** Report reissued, supplemental for Magnum 180 Diesel, November, 2009.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2423** Nebraska Summary 621A, November 27, 2009.

Roger M. Hoy  
 Director

M.F. Kocher  
 V.I. Adamchuk  
 J.A. Smith  
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 8th gear	70.0	70.0
Bystander	--	--

**TIRES, BALLAST AND WEIGHT**

**Rear Tires** - No., size, ply & psi(kPa)  
**Front Tires** - No., size, ply & psi(kPa)  
**Height of Drawbar**  
**Static Weight with operator** - Rear  
 - Front  
 - Total

**Tested without ballast**

Two 710/70R38; \*\*; 15(100)  
 Two 600/65R28; \*\*; 15(100)  
 24.0 in (610 mm)  
 10650 lb (4830 kg)  
 7110 lb (3225 kg)  
 17760 lb (8055 kg)

This vehicle is equipped with an electronically controlled engine Power management system that monitors and boosts engine power output in certain circumstances. This is achieved by electronically changing the characteristics of the engine power-speed curve. The engine Power management function ("boosted" power level) becomes active in the higher transmission gears (16th and above) and for road transport applications. The system is also activated when power transfer through the PTO exceeds a preset level (and forward speed exceeds 0.5 km/h), for mobile PTO driven implement applications. An override system is provided to enable PTO operations at the "boosted" power level while the vehicle is stationary for test purposes. The results of this PTO output test are presented below.

### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1022 rpm)</b>					
189.1 (141.0)	2200	11.27 (42.67)	0.413 (0.251)	16.77 (3.30)	
<b>Standard Power Take-off Speed - (1000 rpm)</b>					
195.0 (145.4)	2153	11.47 (43.44)	0.407 (0.248)	17.00 (3.35)	
<b>Maximum Power (1 hour)</b>					
213.6 (159.3)	1900	11.88 (44.95)	0.385 (0.234)	17.98 (3.54)	

### VARYING POWER AND FUEL CONSUMPTION

189.1 (141.0)	2200	11.27 (42.67)	0.413 (0.251)	16.77 (3.30)	Air temperature
164.0 (122.3)	2245	10.33 (39.12)	0.436 (0.266)	15.87 (3.13)	73°F (23°C)
124.6 (93.0)	2275	8.51 (32.19)	0.473 (0.288)	14.64 (2.88)	Relative humidity
84.2 (62.8)	2305	6.32 (23.91)	0.519 (0.316)	13.33 (2.63)	50%
42.5 (31.7)	2325	4.19 (15.87)	0.682 (0.415)	10.15 (2.00)	Barometer
--	2348	2.19 (8.28)	--	--	29.5"Hg (100.0kPa)

Maximum Torque 644.5 lb.-ft. (873.8 Nm) at 1600 rpm  
 Maximum Torque Rise - 42.8%  
 Torque rise at 1800 rpm - 38%

## HYDRAULIC PERFORMANCE

CATEGORY: IHN

Quick Attach: No

OECD Static test

	Lift cylinders
Maximum force exerted through whole range:	10275 lbs (45.7 kN) (2 x 90 mm) 13490 lbs (60.0 kN) (2 x 100 mm)
i) Sustained pressure at compensator cutoff:	3175 psi (219 bar) <b>two outlet sets combined</b>
ii) Pump delivery rate at minimum pressure:	39.1 GPM (148.1 l/min)
iii) Pump delivery rate at maximum	
hydraulic power:	35.6 GPM (134.5 l/min)
Delivery pressure:	2610 psi (180 bar)
Power:	54.1 HP (40.4 kW)
	<b>single outlet set</b>
ii) Pump delivery rate at minimum pressure:	26.2 GPM (99.2 l/min)
iii) Pump delivery rate at maximum	
hydraulic power:	25.7 GPM (97.4 l/min)
Delivery pressure:	2540 psi (175 bar)
Power:	38.1 HP (28.4 kW)

### THREE POINT HITCH PERFORMANCE (SAE Static test)

Observed Maximum Pressure psi. (bar)	3175 (219)				
Location:	lift cylinder				
Hydraulic oil temperature: °F (°C)	150 (65)				
Location:	hydraulic sump				
Category:	IHN				
Quick attach:	none				
System pressure 2865 psi (197 Bar) Lift cylinders - 2 x 90 mm					
Hitch point distance to ground level in. (mm)	19.7 (500)	21.9 (555)	25.8 (655)	33.7 (855)	45.3 (1150)
Lift force on frame lb	13195	13155	13195	13080	11690
" " " " " " (kN)	(58.7)	(58.5)	(58.7)	(58.2)	(52.0)
System pressure 2865 psi (197 Bar) Lift cylinders - 2 x 100 mm					
Hitch point distance to ground level in. (mm)	19.7 (500)	21.9 (555)	25.8 (655)	35.8 (910)	45.3 (1150)
Lift force on frame lb	14930	15015	15175	15150	14230
" " " " " " (kN)	(66.4)	(66.8)	(67.5)	(67.4)	(63.3)

### HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	31.9	810	31.5	800
B	17.9	454	17.9	454
C	15.1	383	15.1	383
D	14.6	372	14.6	372
E	10.9	277	10.9	277
F	10.6	270	10.6	270
G	36.4	925	36.4	925
H	2.4	60	2.4	60
I	19.7	440	19.7	440
J	25.8	655	25.8	655
K	26.9	682	26.9	682
L	48.2	1224	48.2	1224
M	23.1	587	23.1	587
N	38.3	974	38.3	974
O	9.0	230	19.7	500
P	52.8	1340	47.8	1214
Q	38.2	970	45.3	1150
R	40.2	1022	34.4	875

