

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

2009

Nebraska Summary: S711 Challenger MT445B

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S711 Challenger MT445B" (2009). *Nebraska Tractor Tests*. 3202.

<https://digitalcommons.unl.edu/tractormuseumlit/3202>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2515–NEBRASKA SUMMARY 711 CHALLENGER MT 445B DIESEL 16 SPEED

Tractor chassis S/N T177054 and higher

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1099 rpm)					
78.9 (58.8)	2199	5.12 (19.41)	0.461 (0.280)	15.40 (3.03)	
Standard Power Take-off Speed(1000 rpm)					
90.8 (67.7)	2000	5.49 (20.77)	0.429 (0.261)	16.54 (3.26)	
Maximum Power (1 hour)					
90.8 (67.7)	2000	5.49 (20.77)	0.429 (0.261)	16.54 (3.26)	

VARYING POWER AND FUEL CONSUMPTION

78.9 (58.8)	2199	5.12 (19.41)	0.461 (0.280)	15.40 (3.03)	Air temperature
67.3 (50.2)	2206	4.57 (17.31)	0.482 (0.293)	14.72 (2.90)	68°F (20°C)
50.6 (37.7)	2218	3.81 (14.41)	0.535 (0.325)	13.28 (2.62)	Relative humidity
34.1 (25.4)	2233	2.80 (10.61)	0.585 (0.356)	12.15 (2.39)	38%
17.0 (12.7)	2241	2.00 (7.56)	0.835 (0.508)	8.50 (1.67)	Barometer
--	2248	1.39 (5.25)	--	--	29.7" Hg(100.5 kPa)

Maximum torque - 300.2 lb.-ft.(407.0 Nm) at 1250 rpm

Maximum torque rise - 59.4%

Torque rise at 1750 engine rpm - 43%

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F (°C) cool- ing med	Barom. inch Hg (kPa)
Maximum Power—7th(2C) Gear							
56.6 (42.2)	4550 (20.2)	4.66 (7.50)	2199	3.3	0.585 (0.356)	12.13 (2.39)	180 (82)
75% of Pull at Maximum Power—7th(2C) Gear							
43.4 (32.4)	3435 (15.3)	4.74 (7.63)	2208	2.1	0.653 (0.397)	10.87 (2.14)	178 (81)
50% of Pull at Maximum Power—7th(2C) Gear							
29.0 (21.6)	2275 (10.1)	4.78 (7.69)	2214	1.6	0.760 (0.463)	9.34 (1.84)	176 (80)
75% of Pull at Reduced Engine Speed—8th(2D) Gear							
43.3 (32.3)	3415 (15.2)	4.76 (7.66)	1805	2.8	0.578 (0.351)	12.29 (2.42)	178 (81)
50% of Pull at Reduced Engine Speed—8th(2D) Gear							
29.2 (21.8)	2295 (10.2)	4.77 (7.67)	1800	2.0	0.640 (0.389)	11.09 (2.18)	174 (79)

Location of tests: Groupement d'Antony, Parc de Touvoie, BP 44 Antony, Cedex, France 92163

Dates of tests: December 2008 to March, 2009

Manufacturer: AGCOS.A. BP 307, Avenue Blaise Pascal, 60026 Beauvais, France

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.853 **Fuel weight** 7.10 lbs/gal (0.851 kg/l) **Oil SAE** 15W40 **API service classification** CH4 **Transmission and hydraulic lubricant** BP Terrac Tractan 9 fluid **Front axle lubricant** API GL5 - SAE 85W140

ENGINE: Make Perkins Diesel **Type** four cylinder vertical with turbocharger and air to air intercooler **Serial No.** U021737S **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.134" x 5.000" (105.0 mm x 127.0 mm) **Compression ratio** 16.2 to 1 **Displacement** 268 cu in (4400 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.** T239091 **Tread width** rear 59.8" (1518 mm) to 67.0" (1703 mm) front 55.7" (1415 mm) to 64.8" (1646 mm) **Wheelbase** 97.0" (2464 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with partial (4) range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.32 (2.12) second 1.62 (2.60) third 1.97 (3.17) fourth 2.43 (3.91) fifth 3.11 (5.01) sixth 3.83 (6.17) seventh 4.68 (7.53) eighth 5.75 (9.26) ninth 6.33 (10.19) tenth 7.79 (12.53) eleventh 9.50 (15.29) twelfth 11.68 (18.80) thirteenth 13.54 (21.79) fourteenth 16.65 (26.80) fifteenth 20.31 (32.69) sixteenth 24.99 (40.21) reverse 1.32 (2.12), 1.62 (2.60), 1.97 (3.17), 2.43 (3.91), 3.11 (5.01), 3.83 (6.17), 4.68 (7.53), 5.75 (9.26), 6.33 (10.19), 7.79 (12.53), 9.50 (15.29), 11.68 (18.80), 13.54 (21.79), 16.65 (26.80), 20.31 (32.69), 24.99 (40.21) **Clutch** multiple wet disc operated by foot pedal **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1980 engine rpm or 1000 rpm at 2000 engine rpm **Unladen tractor mass** 9720 lb (4410 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
4th(1D)Gear									
48.9 (36.5)	8700 (38.7)	2.11 (3.39)	2192	15.2	0.683 (0.416)	10.40 (2.05)	178 (81)	43 (6)	30.2 (102.4)
5th(2A)Gear									
60.5 (45.1)	8475 (37.7)	2.68 (4.31)	2050	10.6	0.564 (0.343)	12.59 (2.48)	172 (78)	43 (6)	30.2 (102.4)
6th(2B)Gear									
64.6 (48.2)	7195 (32.0)	3.37 (5.42)	2002	6.8	0.542 (0.330)	13.10 (2.58)	178 (81)	43 (6)	30.2 (102.4)
7th(2C)Gear									
65.7 (49.0)	5855 (26.1)	4.21 (6.77)	1997	4.4	0.524 (0.318)	13.56 (2.67)	176 (80)	45 (7)	30.2 (102.4)
8th(2D)Gear									
65.2 (48.6)	4685 (20.8)	5.22 (8.39)	1999	3.3	0.530 (0.322)	13.40 (2.64)	178 (81)	45 (7)	30.2 (102.4)
9th(3A)Gear									
76.3 (56.9)	5005 (22.3)	5.72 (9.20)	2006	4.2	0.509 (0.309)	13.96 (2.75)	178 (81)	45 (7)	30.2 (102.4)
10th(3B)Gear									
75.8 (56.5)	4005 (17.8)	7.09 (11.41)	1999	3.4	0.522 (0.317)	13.61 (2.68)	180 (82)	45 (7)	30.2 (102.4)
*11th(3C)Gear									
74.8 (55.8)	3245 (14.4)	8.64 (13.90)	2000	3.4	0.532 (0.323)	13.36 (2.63)	189 (87)	45 (7)	30.2 (102.4)

*Front Drive Disengaged

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

NOTE 1: The engine on this tractor is electronically controlled to give 2 power levels. A "boosted" level is available when the PTO is engaged, tractor stationary, and when the tractor is operated in ranges 3 and 4.

NOTE 2: The data on this summary was obtained from OECD report 2515 conducted on the Massey Ferguson 5445 Diesel.

NOTE 3: The performance figures on this report apply to tractors with chassis S/N T177054 and higher.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 26 GPM (100 lpm) hydraulic flow at the remote outlets. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **2515**, Nebraska Summary 711, September 8, 2010.

Roger M. Hoy
 Director

M.F. Kocher
 D.R. Keshwani
 J.A. Smith
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 7th (2C) gear	75.0	74.0
Bystander	--	--

TRACTOR SOUND LEVEL WITHOUT CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 7th (2C) gear	85.0	85.0
Bystander	--	--

TIRES AND WEIGHT

Rear tires - No., size, ply & psi(kPa)
Front tires - No., size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator- Rear
 - Front
 - Total

Tested without ballast

Two 18.4R38; **;15(100)
 Two 14.9R28; **;15(100)
 19.7 in (500 mm)
 6065 lb (2750 kg)
 3845 lb (1745 kg)
 9910 lb (4495 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Disengaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
5th(2A) Gear									
51.8 (38.6)	7095 (31.5)	2.74 (4.40)	2197	15.2	0.627 (0.381)	11.33 (2.23)	180 (82)	50 (10)	30.2 (102.3)
6th(2B) Gear									
59.9 (44.7)	6985 (31.1)	3.22 (5.18)	2036	12.3	0.579 (0.352)	12.24 (2.41)	172 (78)	50 (10)	30.2 (102.3)
7th(2C) Gear									
64.4 (48.0)	5980 (26.6)	4.04 (6.50)	1996	8.2	0.540 (0.328)	13.16 (2.59)	174 (79)	50 (10)	30.2 (102.3)
8th(2D) Gear									
64.4 (48.0)	4745 (21.1)	5.09 (8.19)	2001	6.0	0.553 (0.336)	12.84 (2.53)	176 (80)	50 (10)	30.2 (102.3)
9th(3A) Gear									
74.8 (55.8)	5050 (22.5)	5.56 (8.94)	2001	6.2	0.531 (0.323)	13.37 (2.63)	176 (80)	50 (10)	30.2 (102.3)
10th(3B) Gear									
74.6 (55.6)	4025 (17.9)	6.95 (11.19)	2000	5.2	0.532 (0.323)	13.36 (2.63)	178 (81)	50 (10)	30.2 (102.3)
11th(3C) Gear									
74.0 (55.2)	3270 (14.5)	8.49 (13.67)	2000	5.0	0.540 (0.328)	13.16 (2.59)	178 (81)	50 (10)	30.2 (102.3)

TIRES AND WEIGHT

Rear tires - No.,size, ply & psi(kPa)

Front tires - No.,size, ply & psi(kPa)

Height of Drawbar

Static Weight with operator-Rear

- Front

- Total

Tested without ballast

Two 18.4R38; **,15(100)

Two 14.9R28; **,15(100)

31.5 in (800 mm)

6065 lb (2750 kg)

3845 lb (1745 kg)

9910 lb (4495 kg)

HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 7817 lbs (34.8 kN) (66 mm lift cylinders)

9189 lbs (40.9 kN) (75 mm lift cylinders)

Open center system

100 l/min pump 57 l/min pump

Closed center system

110 l/min pump

i) Sustained pressure of the open relief valve: 3136 psi (216 bar) 2785 psi (192 bar) 2848 psi (196 bar)

ii) Pump delivery rate at minimum pressure: 24.1 GPM(91.2 l/min) 16.1 GPM(61.0 l/min) 29.8 GPM (112.7 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 22.4 GPM(84.8 l/min) 14.7 GPM(55.5 l/min) 24.2 GPM(91.6 l/min)

Delivery pressure: 2338 psi (161 bar) 2580 psi (178 bar) 2708 psi (187 bar)

Power: 30.6 HP (22.8 kW) 22.1 Hp (16.5 kW) 38.2 hp (28.5 kW)

THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi.(bar)	2770(191)
Location:	lift cylinder
Hydraulic oil temperature: °F(°C)	152(67)
Location:	hydraulic valve
Category:	II
Quick attach:	none

66 mm cylinders

SAE Static Test—System pressure 2490 psi (172 Bar)

Hitch point distance to ground level in.(mm)	9.9(251)	15.0(381)	22.0(559)	29.0(737)	36.0(914)
Lift force on frame lb	15561	12897	11745	10314	9126
" " " " " " (kN)	(69.2)	(57.4)	(51.0)	(45.9)	(40.6)

75 mm cylinders

SAE Static Test—System pressure 2490 psi (172 Bar)

Hitch point distance to ground level in.(mm)	10.2(259)	15.0(381)	22.0(559)	29.0(737)	36.0(914)
Lift force on frame lb	18747	15849	14310	12789	11421
" " " " " " (kN)	(83.4)	(70.5)	(63.7)	(56.9)	(50.8)

HITCH DIMENSIONS AS TESTED—NO LOAD

	SAE test		OECD test	
	inch	mm	inch	mm
A	24.8	629	24.8	629
B	11.6	295	11.6	295
C	13.9	353	13.9	353
D	13.0	330	13.0	330
E	7.9	200	7.9	200
F	10.2	260	10.2	260
G	30.3	770	30.3	770
H	1.4	35	1.4	35
I	16.2	413	16.2	413
J	20.1	510	20.1	510
K	24.2	615	24.2	615
L	41.2	1046	41.2	1046
M	23.5	596	23.5	596
N	37.2	946	37.2	946
O	8.0	203	8.0	203
P	40.2	1020	44.1	1120
Q	33.5	850	33.5	850
R	29.0	737	29.0	737

