

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

2009

Nebraska Summary: S746 Massey Ferguson 8680 IEGR

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Nebraska Summary: S746 Massey Ferguson 8680 IEGR" (2009). *Nebraska Tractor Tests*. 3276.

<https://digitalcommons.unl.edu/tractormuseumlit/3276>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2559-NEBRASKA SUMMARY 746

MASSEY FERGUSON 8680 IEGR DIESEL

DYNA VT TRANSMISSION

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1081 rpm)					
282.7 (210.8)	2200	17.19 (65.07)	0.425 (0.258)	16.45 (3.24)	
Standard Power Take-off Speed(1000 rpm)					
305.6 (227.9)	2035	17.26 (65.34)	0.395 (0.240)	17.71 (3.49)	
Maximum Power (1 hour)					
322.6 (240.6)	1850	17.97 (68.04)	0.389 (0.237)	17.95 (3.54)	

VARYING POWER AND FUEL CONSUMPTION

282.7 (210.8)	2200	17.19 (65.07)	0.425 (0.258)	16.45 (3.24)	Air temperature
242.6 (180.9)	2221	15.11 (57.18)	0.436 (0.265)	16.06 (3.16)	68°F (20°C)
182.8 (136.3)	2231	12.04 (45.58)	0.460 (0.280)	15.18 (2.99)	Relative humidity
122.4 (91.3)	2243	8.58 (32.49)	0.490 (0.298)	14.26 (2.81)	51%
61.4 (45.8)	2252	5.23 (19.80)	0.596 (0.362)	11.73 (2.31)	Barometer
--	2258	2.55 (9.64)	--	--	29.2" Hg(98.8 kPa)

Maximum Torque - 1037 lb.-ft. (1406 Nm) at 1500 rpm
 Maximum Torque Rise - 53.7%
 Torque rise at 1800 engine rpm - 38%
 Power increase at 1850 engine rpm - 14.1%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle 9									
236.3 (176.2)	15900 (70.72)	5.57 (8.97)	2200	2.4	0.509 (0.310)	13.73 (2.71)	165 (74)	61 (16)	29.4 (99.4)
75% of Pull at Maximum Power—Turtle 9									
181.7 (135.5)	11925 (53.05)	5.71 (9.19)	2218	1.7	0.546 (0.332)	12.84 (2.53)	165 (74)	63 (17)	29.4 (99.4)
50% of Pull at Maximum Power—Turtle 9									
123.1 (91.8)	7920 (35.24)	5.83 (9.38)	2233	1.1	0.601 (0.366)	11.62 (2.29)	165 (74)	61 (16)	29.4 (99.4)
75% of Pull at Reduced Engine Speed—Turtle 11									
182.2 (135.9)	11930 (53.06)	5.73 (9.22)	1788	1.6	0.476 (0.290)	14.67 (2.89)	165 (74)	63 (17)	29.4 (99.4)
50% of Pull at Reduced Engine Speed—Turtle 11									
123.0 (91.7)	7930 (35.27)	5.82 (9.36)	1793	1.1	0.505 (0.307)	13.82 (2.72)	165 (74)	63 (17)	29.4 (99.4)

Location of tests: DLG - Test Centre, Technology and Farm inputs, Max-Eyth-Weg 1, D-64823 Gross-Umstadt, Germany

Dates of tests: October 2009 - March 2010.

Manufacturer: AGCO S.A. ZA n2 BP 60307, Avenue Blaise Pascal, 60026 Beauvais, France

FUEL and OIL: Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.839 Fuel weight 6.99 lbs/gal (0.8373 kg/l) Oil SAE 10W40 API service classification CI4 Transmission and hydraulic lubricant BP STOU 10W/40 Front axle lubricant SAE 85W90 API GL5

ENGINE: Make Sisu Diesel Type six cylinder vertical with turbocharger, air to air intercooler and IEGR technology Serial No. 21340 Crankshaft lengthwise Rated engine speed 2200 Bore and stroke 4.370" x 5.709" (111.0 mm x 145.0 mm) Compression ratio 16.7 to 1 Displacement 513 cu in (8419 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler vertical Cooling medium temperature control thermostat and variable speed fan

CHASSIS: Type front wheel assist with duals Serial No. T073991 Tread width rear 60.0" (1525 mm) to 101.8" (2585 mm) front 60.8" (1545 mm) to 89.2" (2265 mm) Wheelbase 122.2" (3105 mm) Hydraulic control system direct engine drive Transmission CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. Nominal travel speeds mph (km/h) forward: Low range 0-18 (0-30), high range 0-25 (0-40) reverse: Low range 0-12 (0-19), high range 0-12 (0-19) Clutch a foot pedal controls the hydrostatic oil flow Brakes multiple wet disc hydraulically operated by two foot pedals that can be locked together Steering hydrostatic Power take-off 540 rpm at 2038 engine rpm or 1000 rpm at 2033 engine rpm Unladen tractor mass 25840 lb (11720 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER AT SELECTED SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Turtle 6									
224.5 (167.4)	26725 (118.88)	3.15 (5.07)	2013	15.1	0.542 (0.330)	12.89 (2.54)	163 (73)	59 (15)	29.4 (99.5)
Turtle 7.5									
258.5 (192.8)	25525 (113.54)	3.80 (6.11)	1855	7.2	0.488 (0.297)	14.31 (2.82)	162 (72)	57 (14)	29.4 (99.5)
Turtle 9									
265.1 (197.7)	21440 (95.36)	4.64 (7.46)	1850	3.9	0.475 (0.289)	14.72 (2.90)	165 (74)	57 (14)	29.4 (99.5)
Turtle 11									
265.5 (198.0)	17375 (77.29)	5.73 (9.22)	1851	2.6	0.475 (0.289)	14.72 (2.90)	162 (72)	57 (14)	29.4 (99.4)
Turtle 13									
263.2 (196.3)	14685 (65.33)	6.72 (10.81)	1850	2.0	0.478 (0.291)	14.57 (2.87)	167 (75)	57 (14)	29.4 (99.5)
Turtle 15									
258.7 (192.9)	12710 (56.54)	7.63 (12.28)	1851	1.7	0.488 (0.297)	14.32 (2.82)	169 (76)	57 (14)	29.4 (99.5)
Turtle 17									
257.6 (192.1)	11030 (49.07)	8.76 (14.09)	1853	1.3	0.490 (0.298)	14.26 (2.81)	169 (76)	55 (13)	29.4 (99.5)
Rabbit 11									
257.5 (192.0)	17375 (77.28)	5.56 (8.94)	1852	2.8	0.490 (0.298)	14.26 (2.81)	165 (74)	59 (15)	29.4 (99.5)
Rabbit 13									
261.2 (194.8)	14835 (66.00)	6.60 (10.63)	1852	2.3	0.481 (0.293)	14.52 (2.86)	169 (76)	57 (14)	29.4 (99.5)
Rabbit 15									
264.0 (196.9)	12880 (57.30)	7.69 (12.37)	1850	1.9	0.477 (0.290)	14.63 (2.88)	171 (77)	57 (14)	29.4 (99.5)
Rabbit 17									
263.5 (196.5)	11420 (50.81)	8.65 (13.92)	1854	1.6	0.480 (0.292)	14.57 (2.87)	171 (77)	57 (14)	29.4 (99.5)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claims of 54% torque rise, 15% power bulge nor remote hydraulic flow claim of 26.4 GPM (100 l/min) from one outlet set. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2559**, Nebraska summary 746, October 26, 2010.

Roger M. Hoy
Director

M.F. Kocher
D.R. Keshwani
J.A. Smith
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	dB(A)
At no load in Turtle - 4.6mph (7.5 km/h) - no load	71.0
Bystander	---

TIRES, BALLAST AND WEIGHT	With Ballast	Without Ballast
Rear Tires - No., size, ply & psi(kPa)	Six 480/80R46;***;9(60)	Four 480/80R46;***;9(60)
Ballast - Triples (total)	2955 lb(1340 kg)	None
- Cast Iron (total)	2255 lb(1023 kg)	None
Front Tires - No., size, ply & psi(kPa)	Four 420/90R30;***;9(60)	Two 420/90R30;***;9(60)
Ballast - Duals (total)	1170 lb (530 kg)	None
- Cast Iron (total)	2485 lb (1127 kg)	None
Height of Drawbar	19.5 in (500 mm)	19.5 in (500 mm)
Static Weight with operator - Rear	20280 lb (9200 kg)	15320 lb (6950 kg)
- Front	14585 lb (6615 kg)	10680 lb (4845 kg)
- Total	34865 lb(15815 kg)	26000 lb(11795 kg)

DRAWBAR PERFORMANCE
(Ballasted - Front Drive Engaged)
FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle 7.5								
242.4 (180.8)	19545 (86.93)	4.65 (7.49)	2201	1.8	0.499 (0.303)	14.03 (2.76)	158 (70)	52 (11) 29.7 (100.6)
75% of Pull at Maximum Power—Turtle 7.5								
187.2 (139.6)	14660 (65.20)	4.79 (7.71)	2216	1.1	0.522 (0.318)	13.40 (2.64)	158 (70)	52 (11) 29.7 (100.6)
50% of Pull at Maximum Power—Turtle 7.5								
127.4 (95.0)	9755 (43.40)	4.90 (7.88)	2234	0.6	0.570 (0.347)	12.27 (2.42)	158 (70)	50 (10) 29.7 (100.6)
75% of Pull at Reduced Engine Speed—Turtle 9								
186.3 (138.9)	14640 (65.12)	4.77 (7.68)	1810	1.1	0.461 (0.280)	15.18 (2.99)	156 (69)	50 (10) 29.7 (100.6)
50% of Pull at Reduced Engine Speed—Turtle 9								
126.9 (94.6)	9765 (43.44)	4.87 (7.84)	1823	0.7	0.490 (0.298)	14.26 (2.81)	156 (69)	50 (10) 29.7 (100.6)
MAXIMUM POWER AT SELECTED SPEEDS								
Turtle 5								
226.0 (168.5)	33685 (149.84)	2.52 (4.05)	2025	15.1	0.540 (0.328)	12.94 (2.55)	153 (67)	50 (10) 29.7 (100.6)
Turtle 6								
252.9 (188.6)	32545 (144.77)	2.91 (4.69)	1851	9.7	0.499 (0.304)	14.01 (2.76)	147 (64)	50 (10) 29.7 (100.5)
Turtle 7.5								
272.0 (202.8)	26695 (118.74)	3.82 (6.15)	1851	3.8	0.466 (0.283)	15.02 (2.96)	149 (65)	52 (11) 29.7 (100.5)
Turtle 9								
273.4 (203.9)	22205 (98.77)	4.62 (7.43)	1851	2.3	0.462 (0.281)	15.13 (2.98)	149 (65)	50 (10) 29.7 (100.5)
Turtle 11								
270.9 (202.0)	17720 (78.82)	5.73 (9.23)	1852	1.7	0.467 (0.284)	14.97 (2.95)	140 (60)	41 (5) 29.5 (99.9)
Turtle 13								
268.6 (200.3)	15175 (67.50)	6.64 (10.68)	1854	1.5	0.470 (0.286)	14.87 (2.93)	145 (63)	41 (5) 29.5 (99.9)
Turtle 15								
261.4 (194.9)	12700 (56.50)	7.72 (12.42)	1854	1.3	0.482 (0.293)	14.52 (2.86)	153 (68)	41 (5) 29.5 (100.0)
Turtle 17								
258.7 (192.9)	11410 (50.76)	8.50 (13.68)	1854	1.0	0.489 (0.297)	14.31 (2.82)	149 (65)	48 (9) 29.7 (100.5)
Rabbit 11								
264.0 (196.9)	17865 (79.46)	5.54 (8.92)	1852	1.7	0.480 (0.292)	14.58 (2.87)	156 (69)	52 (11) 29.7 (100.6)
Rabbit 13								
267.4 (199.4)	15325 (68.16)	6.54 (10.53)	1852	1.4	0.472 (0.287)	14.82 (2.92)	158 (70)	50 (10) 29.7 (100.6)
Rabbit 15								
268.7 (200.4)	13235 (58.87)	7.62 (12.26)	1852	1.2	0.469 (0.286)	14.90 (2.94)	160 (71)	50 (10) 29.7 (100.6)
Rabbit 17								
266.6 (198.8)	11485 (51.08)	8.71 (14.01)	1854	1.0	0.472 (0.287)	14.82 (2.92)	160 (71)	50 (10) 29.7 (100.6)

HYDRAULIC PERFORMANCE

CATEGORY: IVN

Quick Attach: No

OECD Static test

Maximum force exerted through whole range: 24590 lbs (109.4 kN)

i) Sustained pressure at compensator cutoff: 3190 psi (220 bar)
three outlet sets combined

ii) Pump delivery rate at minimum pressure and rated engine speed: 49.5 GPM (187.4 l/min)

iii) Pump delivery rate at maximum hydraulic power: 44.6 GPM (169.0 l/min)
Delivery pressure: 2205 psi (152 bar)
Power: 57.4 HP (42.8 kW)
single outlet set

ii) Pump delivery rate at minimum pressure and rated engine speed: 25.3 GPM (95.6 l/min)

iii) Pump delivery rate at maximum hydraulic power: 23.8 GPM (90.1 l/min)
Delivery pressure: 2510 psi (173 bar)
Power: 34.9 HP (26.0 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	35.8	910
B	14.6	370
C	19.1	484
D	15.9	405
E	15.6	395
F	13.0	330
G	36.4	925
H	2.0	50
I	16.5	420
J	23.4	595
K	28.7	730
L	52.4	1330
M	29.8	757
N	42.9	1090
O	9.1	230
P	50.4	1280
Q	38.7	983
R	37.0	940

