

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

2010

## Nebraska Summary: S774 Massey Ferguson 6480

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S774 Massey Ferguson 6480" (2010). *Nebraska Tractor Tests*. 3256.

<https://digitalcommons.unl.edu/tractormuseumlit/3256>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2412-NEBRASKA SUMMARY 774

## MASSEY FERGUSON 6480 DIESEL

### 24 SPEED

### SISU Engine

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1084 rpm)</b>					
127.8 (95.3)	2200	7.86 (29.76)	0.438 (0.266)	16.25 (3.20)	
<b>Standard Power Take-off Speed(1000 rpm)</b>					
143.9 (107.3)	2030	8.25 (31.22)	0.408 (0.248)	17.45 (3.44)	
<b>Maximum Power (1 hour)</b>					
147.2 (109.8)	1900	8.05 (30.49)	0.389 (0.237)	18.28 (3.60)	

#### VARYING POWER AND FUEL CONSUMPTION

127.8 (95.3)	2200	7.86 (29.76)	0.438 (0.266)	16.25 (3.20)	Air temperature
109.5 (81.7)	2217	7.09 (26.82)	0.461 (0.280)	15.44 (3.04)	73°F (23°C)
82.3 (61.4)	2223	5.87 (22.24)	0.508 (0.309)	14.01 (2.76)	Relative humidity
55.2 (41.2)	2232	4.49 (16.98)	0.579 (0.352)	12.29 (2.42)	38%
27.6 (20.6)	2242	3.09 (11.68)	0.794 (0.483)	8.96 (1.77)	Barometer
--	2250	2.03 (7.67)	--	--	30.5" Hg (103.3 kPa)

Maximum Torque - 478.3 lb.-ft. (648.5 Nm) at 1400 rpm  
 Maximum Torque Rise - 56.8%  
 Torque rise at 1750 engine rpm - 43%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—12th(3A) Gear</b>									
97.1 (72.4)	6750 (30.0)	5.39 (8.68)	2201	3.2	0.502 (0.305)	14.18 (2.79)	180 (82)	43 (6)	30.4 (103.1)
<b>75% of Pull at Maximum Power—12th(3A) Gear</b>									
73.6 (54.9)	5060 (22.5)	5.46 (8.78)	2208	2.8	0.550 (0.334)	12.95 (2.55)	178 (81)	43 (6)	30.4 (103.1)
<b>50% of Pull at Maximum Power—12th(3A) Gear</b>									
50.0 (37.3)	3390 (15.1)	5.53 (8.90)	2218	1.7	0.635 (0.386)	11.22 (2.21)	178 (81)	43 (6)	30.4 (103.1)
<b>75% of Pull at Reduced Engine Speed—14th(3B) Gear</b>									
73.5 (54.8)	5060 (22.5)	5.45 (8.77)	1835	3.0	0.475 (0.289)	14.97 (2.95)	176 (80)	41 (5)	30.4 (103.2)
<b>50% of Pull at Reduced Engine Speed—14th(3B) Gear</b>									
50.0 (37.3)	3395 (15.1)	5.52 (8.89)	1839	1.9	0.538 (0.327)	13.25 (2.61)	176 (80)	41 (5)	30.4 (103.1)

**Location of tests:** Groupement d'Antony, Parc de Touvoie, BP 44 Antony, France 92163

**Dates of tests:** November 2007 - January 2008  
 Cab sound tests - March 31, 2010

**Manufacturer:** AGCO S.A. BP 307, Avenue Blaise Pascal, 60026 Beauvais, France

**FUEL and OIL:** Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.855  
**Fuel weight** 7.12 lbs/gal (0.853 kg/l) **Oil SAE** 15W40 **API service classification** CH4  
**Transmission and hydraulic lubricant** BP Terrac Tractan 9 10W/40 **Front axle lubricant** BP Terrac Tractan 9 10W/40

**ENGINE: Make** Sisu Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler  
**Serial No.** T09020 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.252" x 4.724" (108.0 mm x 120.0 mm) **Compression ratio** 18.5 to 1 **Displacement** 402 cu in (6596 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS: Type** front wheel assist **Serial No.** S127019 **Tread width** rear 54.1" (1375 mm) to 86.8" (2205 mm) front 62.9" (1597 mm) to 80.0" (2033 mm) **Wheelbase** 109.4" (2780 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with partial (6) range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.01 (1.62) second 1.21 (1.95) third 1.42 (2.29) fourth 1.71 (2.75) fifth 2.01 (3.24) sixth 2.42 (3.90) seventh 2.73 (4.39) eighth 3.27 (5.27) ninth 3.85 (6.19) tenth 4.63 (7.45) eleventh 5.44 (8.76) twelfth 5.54 (8.91) thirteenth 6.55 (10.54) fourteenth 6.66 (10.71) fifteenth 7.81 (12.57) sixteenth 9.40 (15.13) seventeenth 11.05 (17.79) eighteenth 12.77 (20.55) nineteenth 13.30 (21.41) twentieth 15.35 (24.70) twenty-first 18.02 (29.00) twenty-second 21.68 (34.89) twenty-third 24.86 (40.00) twenty-fourth 24.86 (40.00) reverse 1.01 (1.62), 1.21 (1.95), 1.42 (2.29), 1.71 (2.75), 2.01 (3.24), 2.42 (3.90), 2.73 (4.39), 3.27 (5.27), 3.85 (6.19), 4.63 (7.45), 5.44 (8.76), 5.54 (8.91), 6.55 (10.54), 6.66 (10.71), 7.81 (12.57), 9.40 (15.13), 11.05 (17.79), 12.77 (20.55), 13.30 (21.41), 15.35 (24.70), 18.02 (29.00), 21.68 (34.89), 24.86 (40.00), 24.86 (40.00)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Engaged)**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crankshaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cooling med	Air dry bulb	Barom. inch Hg (kPa)
4th(1D) Gear									
53.4 (39.8)	13265 (59.0)	1.51 (2.43)	2208	15.1	0.674 (0.410)	10.56 (2.08)	178 (81)	39 (4)	30.5 (103.2)
5th(1E) Gear									
63.2 (47.1)	13055 (58.0)	1.82 (2.92)	2205	12.9	0.638 (0.388)	11.17 (2.20)	180 (82)	39 (4)	30.5 (103.2)
6th(1F) Gear									
76.2 (56.8)	12970 (57.7)	2.20 (3.54)	2201	12.2	0.587 (0.357)	12.13 (2.39)	180 (82)	39 (4)	30.5 (103.2)
7th(2A) Gear									
85.6 (63.8)	12970 (57.7)	2.47 (3.98)	2195	12.1	0.556 (0.338)	12.79 (2.52)	180 (82)	41 (5)	30.5 (103.2)
8th(2B) Gear									
101.0 (75.3)	12750 (56.7)	2.97 (4.78)	2191	12.0	0.519 (0.316)	13.71 (2.70)	180 (82)	41 (5)	30.5 (103.2)
9th(2C) Gear									
107.6 (80.2)	12020 (53.5)	3.36 (5.40)	2058	9.7	0.494 (0.300)	14.42 (2.84)	180 (82)	41 (5)	30.5 (103.2)
10th(2D) Gear									
111.7 (83.3)	10370 (46.1)	4.04 (6.50)	2012	6.7	0.461 (0.281)	15.43 (3.04)	178 (81)	43 (6)	30.4 (103.1)
11th(2E) Gear									
111.4 (83.1)	9240 (41.1)	4.52 (7.28)	1916	5.9	0.437 (0.266)	16.29 (3.21)	180 (82)	43 (6)	30.4 (103.1)
12th(3A) Gear									
128.9 (96.1)	10635 (47.3)	4.55 (7.32)	1910	6.6	0.436 (0.265)	16.29 (3.21)	180 (82)	43 (6)	30.4 (103.1)
13th(2F) Gear									
111.6 (83.2)	7620 (33.9)	5.49 (8.83)	1903	4.6	0.433 (0.264)	16.43 (3.24)	180 (82)	43 (6)	30.4 (103.1)
14th(3B) Gear									
129.9 (96.9)	8815 (39.2)	5.53 (8.90)	1900	5.0	0.433 (0.263)	16.45 (3.24)	180 (82)	41 (5)	30.4 (103.1)
15th(3C) Gear									
130.9 (97.6)	7530 (33.5)	6.52 (10.50)	1901	4.9	0.427 (0.260)	16.64 (3.28)	181 (83)	41 (5)	30.4 (103.1)
*16th(3D) Gear									
128.8 (96.1)	6260 (27.8)	7.72 (12.41)	1901	5.0	0.436 (0.265)	16.34 (3.22)	183 (84)	41 (5)	30.4 (103.1)
*17th(3E) Gear									
124.6 (92.9)	5075 (22.6)	9.21 (14.82)	1903	3.0	0.450 (0.274)	15.83 (3.12)	183 (84)	41 (5)	30.4 (103.1)

\* Front Drive Disengaged

**Clutch** multiple wet disc operated by foot pedal  
**Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together  
**Steering** hydrostatic **Power take-off** 540 rpm at 1976 engine rpm or 1000 rpm at 2030 engine rpm **Unladen tractor mass** 14725 lb (6680 kg)

**NOTE 1:** The data on this summary was obtained from OECD report 2412 conducted on the AGCO RT120A Diesel.

**NOTE 2:** The engine on this tractor is electronically controlled to give 2 power levels. A "boosted" level is available when the PTO is engaged, tractor stationary, and when the tractor is operated in ranges 3 and 4.

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2412**, Nebraska Summary 774, July 6, 2011.

Roger M. Hoy  
 Director

M.F. Kocher  
 D.R. Keshwani  
 P.J. Jasa  
 Board of Tractor Test Engineers

**TIRES, BALLAST AND WEIGHT**

**Rear Tires** - No., size, ply & psi(kPa)  
**Front Tires** - No., size, ply & psi(kPa)  
**Height of Drawbar**  
**Static Weight with operator** - Rear  
 - Front  
 - Total

**Tested without ballast**

Two 480/80R42;\*\*,14(100)  
 Two 16.9R28;\*\*,16 (110)  
 23.6 in (600 mm)  
 8915 lb (4045 kg)  
 5975 lb (2710 kg)  
 14890 lb (6755 kg)

TRACTOR SOUND LEVEL WITH CAB	Front wheel drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in 10th (2D) gear	68.8	68.2
Bystander		--

### HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

Maximum force exerted through whole range:	9105 lbs (40.5 kN)
i) Sustained pressure of the open relief valve:	2840 psi (196 bar)
ii) Pump delivery rate at minimum pressure:	29.5 GPM (111.7 l/min)
iii) Pump delivery rate at maximum	
hydraulic power:	27.2 GPM (102.8 l/min)
Delivery pressure:	2265 psi (156 bar)
Power:	35.9 HP (26.7 kW)

### HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	28.9	735	28.1	713
B	11.6	295	11.6	295
C	13.9	354	13.9	354
D	13.0	330	13.0	330
E	7.9	200	11.4	290
F	10.2	260	10.2	260
G	34.4	875	34.4	875
H	3.9	98	3.9	98
I	15.3	389	15.3	389
J	24.2	615	24.2	615
K	24.9	633	24.9	633
L	41.7	1060	41.7	1060
M	23.0	585	23.0	585
N	37.8	960	37.8	960
O	8.0	204	10.2	258
P	48.2	1225	43.2	1098
Q	37.0	941	37.5	952
R	29.9	760	28.7	730

### THREE POINT HITCH PERFORMANCE

Observed maximum pressure psi. (bar)	2830 (195)
Location:	lift cylinder
Hydraulic oil temperature: °F (°C)	157 (69)
Location:	hydraulic sump
Category:	II
Quick attach:	None

SAE Static Test—System pressure 2545 psi (176 bar)

Hitch point distance to ground level in. (mm)	10.2 (258)	16.3 (414)	22.0 (560)	28.3 (718)	33.9 (861)	37.5 (952)
Lift force on frame lb	11825	11555	11330	11040	10455	9915
" " " " " (kN)	(52.6)	(51.4)	(50.4)	(49.1)	(46.5)	(44.1)

