

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

2011

## Nebraska Summary: S795 Massey Ferguson 5465

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

---

Nebraska Tractor Test Lab, "Nebraska Summary: S795 Massey Ferguson 5465" (2011). *Nebraska Tractor Tests*. 3251.

<https://digitalcommons.unl.edu/tractormuseumlit/3251>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# SUMMARY OF OECD TEST 2625-NEBRASKA SUMMARY 795

## MASSEY FERGUSON 5465 DIESEL

### 16 SPEED

### SISU Engine

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1084 rpm)</b>					
105.8 (78.9)	2200	6.95 (26.29)	0.467 (0.284)	15.23 (3.00)	
<b>Standard Power Take-off Speed(1000 rpm)</b>					
122.8 (91.6)	2031	7.28 (27.36)	0.422 (0.257)	16.88 (3.33)	
<b>Maximum Power (1 hour)</b>					
123.7 (92.3)	2000	7.28 (27.55)	0.419 (0.255)	17.00 (3.35)	

#### VARYING POWER AND FUEL CONSUMPTION

105.8 (78.9)	2200	6.95 (26.29)	0.467 (0.284)	15.23 (3.00)	Air temperature
90.2 (67.3)	2207	6.16 (23.32)	0.487 (0.296)	14.64 (2.88)	75°F (24°C)
67.5 (50.3)	2215	5.28 (19.99)	0.557 (0.339)	12.79 (2.52)	Relative humidity
45.6 (34.0)	2224	4.29 (16.24)	0.671 (0.408)	10.63 (2.09)	40%
22.8 (17.0)	2234	3.23 (12.24)	1.009 (0.614)	7.06 (1.39)	Barometer
--	2239	2.25 (8.52)	--	--	30.2" Hg (102.2 kPa)

Maximum torque - 405.3 lb.-ft. (549.5 Nm) at 1200 rpm  
 Maximum torque rise - 60.4%  
 Torque rise at 1750 engine rpm - 41%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged)

#### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—7th(2C) Gear</b>									
87.0 (64.9)	6990 (31.1)	4.66 (7.50)	2201	4.6	0.526 (0.320)	13.54 (2.67)	181 (83)	63 (17)	30.1 (102.0)
<b>75% of Pull at Maximum Power—7th(2C) Gear</b>									
66.5 (49.6)	5260 (23.4)	4.74 (7.63)	2208	3.7	0.580 (0.353)	12.27 (2.42)	179 (82)	64 (18)	30.1 (102.0)
<b>50% of Pull at Maximum Power—7th(2C) Gear</b>									
45.1 (33.7)	3515 (15.6)	4.81 (7.74)	2222	2.9	0.710 (0.432)	10.03 (1.98)	179 (82)	64 (18)	30.1 (102.0)
<b>75% of Pull at Reduced Engine Speed—8th(2D) Gear</b>									
66.0 (49.2)	5235 (23.3)	4.73 (7.61)	1793	3.7	0.506 (0.308)	14.06 (2.77)	178 (81)	64 (18)	30.1 (102.0)
<b>50% of Pull at Reduced Engine Speed—8th(2D) Gear</b>									
45.2 (33.7)	3515 (15.6)	4.82 (7.76)	1800	2.4	0.575 (0.350)	12.39 (2.44)	178 (81)	64 (18)	30.1 (102.0)

**Location of tests:** Groupement d'Antony, 1, rue Pierre-Gilles de Gennes, CS 10030 Antony, Cedex, France 92761

**Dates of tests:** June to July, 2011

**Manufacturer:** AGCO S.A. BP 307, Avenue Blaise Pascal, 60026 Beauvais, France

**FUEL and OIL:** Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.855 **Fuel weight** 7.12 lbs/gal (0.853 kg/l) **Oil SAE** 15W40 **API service classification** CH4 **Transmission and hydraulic lubricant** BPTerrac Tractan 9 fluid **Front axle lubricant** API GL5 - SAE 85W140

**ENGINE:** Make Sisu Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler **Serial No.** X10895 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.251" x 4.724" (108.0 mm x 120.0 mm) **Compression ratio** 17.4 to 1 **Displacement** 402 cu in (6596 ml) **Starting system** 12 volt **Lubrication pressure** **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS:** **Type** front wheel assist **Serial No.** B133041 **Tread width** rear 66.9" (1700 mm) to 84.4" (2144 mm) front 63.7" (1619 mm) to 85.6" (2174 mm) **Wheelbase** 113.1" (2874 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with partial (4) range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.35 (2.17) second 1.65 (2.66) third 2.02 (3.25) fourth 2.48 (3.99) fifth 3.19 (5.14) sixth 3.93 (6.32) seventh 4.78 (7.70) eighth 5.89 (9.48) ninth 6.48 (10.43) tenth 7.97 (12.83) eleventh 9.72 (15.65) twelfth 11.96 (19.25) thirteenth 13.86 (22.31) fourteenth 17.05 (27.44) fifteenth 20.80 (33.47) sixteenth 25.58 (41.16) reverse 1.35 (2.17), 1.65 (2.66), 2.02 (3.25), 2.48 (3.99), 3.19 (5.14), 3.93 (6.32), 4.78 (7.70), 5.89 (9.48), 6.48 (10.43), 7.97 (12.83), 9.72 (15.65), 11.96 (19.25), 13.86 (22.31), 17.05 (27.44), 20.80 (33.47), 25.58 (41.16) **Clutch** multiple wet disc operated by foot pedal **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1976 engine rpm or 1000 rpm at 2030 engine rpm **Unladen tractor mass** 12500 lb (5670 kg)

**DRAWBAR PERFORMANCE**  
**(Unballasted - Front Drive Engaged)**  
**MAXIMUM POWER IN SELECTED GEARS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
65.6 (48.9)	11535 (51.3)	2.13 (3.43)	2201	13.8	0.649 (0.395)	10.96 (2.16)	180 (82)	61 (16)	30.1 (102.0)
84.4 (62.9)	11410 (50.8)	2.77 (4.46)	2168	12.4	0.539 (0.328)	13.20 (2.60)	180 (82)	61 (16)	30.1 (102.0)
94.5 (70.5)	10300 (45.8)	3.44 (5.54)	2037	7.4	0.503 (0.306)	14.16 (2.79)	180 (82)	63 (17)	30.1 (102.0)
98.4 (73.4)	8740 (38.9)	4.22 (6.80)	2004	5.6	0.483 (0.294)	14.72 (2.90)	181 (83)	63 (17)	30.1 (102.0)
97.1 (72.4)	6935 (30.8)	5.25 (8.45)	2006	4.1	0.486 (0.296)	14.65 (2.89)	181 (83)	64 (18)	30.1 (102.0)
102.9 (76.7)	6610 (29.4)	5.84 (9.39)	2006	3.8	0.480 (0.292)	14.82 (2.92)	181 (83)	72 (22)	30.1 (102.0)
101.1 (75.4)	5305 (23.6)	7.15 (11.51)	1998	3.5	0.492 (0.299)	14.47 (2.85)	183 (84)	72 (22)	30.1 (102.0)
100.6 (75.0)	4265 (19.0)	8.84 (14.23)	2010	5.0	0.489 (0.298)	14.56 (2.87)	183 (84)	70 (21)	30.1 (102.0)
98.5 (73.5)	3475 (15.5)	10.63 (17.11)	2006	4.2	0.497 (0.302)	14.31 (2.82)	183 (84)	70 (21)	30.1 (102.0)

\*Front Drive Disengaged

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 7th (2C) gear	74.0	74.0
Bystander	--	--

**TIRES AND WEIGHT**

**Rear tires** - No., size, ply & psi (kPa)  
**Front tires** - No., size, ply & psi (kPa)  
**Height of Drawbar**  
**Static Weight with operator**- Rear  
- Front  
- Total

**Tested without ballast**

Two 460/85R38; \*\*,15(100)  
Two 380/85R28; \*\*,15(100)  
18.9 in (480 mm)  
6945 lb (3150 kg)  
5720 lb (2595 kg)  
12665 lb (5745 kg)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**NOTE 1:** The engine on this tractor is electronically controlled to give 2 power levels. A "boosted" level is available when the PTO is engaged, tractor stationary, and when the tractor is operated in ranges 3 and 4.

**NOTE 2:** The performance figures on this report apply to tractors equipped with a Sisu engine.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The manufacturer's remote hydraulic flow claim of 26 GPM (100 lpm) was not verified. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2625**, Nebraska Summary 795, November 21, 2011.

Roger M. Hoy  
Director

M.F. Kocher  
D.R. Keshwani  
P.J. Jasa  
Board of Tractor Test Engineers

## HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 9189 lbs (40.9 kN) (75 mm lift cylinders)

### two outlet sets combined

	57 l/min pump	110 l/min pump
i) Sustained pressure of the open relief valve:	2830 psi (195 bar)	2755 psi (190 bar)
ii) Pump delivery rate at minimum pressure:	15.8 GPM (59.8 l/min)	30.0 GPM (113.4 l/min)
iii) Pump delivery rate at maximum		
hydraulic power:	14.7 GPM (55.6 l/min)	26.0 GPM (98.5 l/min)
Delivery pressure:	2425 psi (167 bar)	2220 psi (153 bar)
Power:	20.8 Hp (15.5 kW)	33.7 hp (25.1 kW)

### single outlet set

ii) Pump delivery rate at minimum pressure:	15.6 GPM (58.9 l/min)	29.6 GPM (112.2 l/min)
iii) Pump delivery rate at maximum		
hydraulic power:	14.6 GPM (55.3 l/min)	25.7 GPM (97.4 l/min)
Delivery pressure:	2395 psi (165 bar)	1915 psi (132 bar)
Power:	20.4 Hp (15.2 kW)	28.7 hp (21.4 kW)

### HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	24.8	629
B	11.6	295
C	13.9	353
D	13.0	330
E	7.9	200
F	10.2	260
G	30.3	770
H	1.4	35
I	16.2	413
J	20.1	510
K	24.2	615
L	41.2	1046
M	23.5	596
N	37.2	946
O	8.0	203
P	44.1	1120
Q	33.5	850
R	29.0	737

