

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

2011

Nebraska Summary: S806 New Holland T7.250

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S806 New Holland T7.250" (2011). *Nebraska Tractor Tests*. 3242.

<https://digitalcommons.unl.edu/tractormuseumlit/3242>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2614–NEBRASKA SUMMARY 806

NEW HOLLAND T7.250 DIESEL

19 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/ltr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1162 rpm)					
177.0 (132.0)	2200	9.70 (36.72)	0.381 (0.232)	18.25 (3.59)	
Standard Power Take-off Speed (1000 rpm)					
198.5 (148.0)	1893	10.44 (39.51)	0.365 (0.222)	19.01 (3.75)	
Maximum Power (1 hour)					
198.7 (148.2)	1800	10.16 (38.47)	0.355 (0.216)	19.55 (3.85)	

VARYING POWER AND FUEL CONSUMPTION

177.0 (132.0)	2200	9.70 (36.72)	0.381 (0.232)	18.25 (3.59)	Air temperature
155.4 (115.9)	2272	8.83 (33.42)	0.394 (0.240)	17.61 (3.47)	68°F (20°C)
117.3 (87.5)	2289	7.30 (27.63)	0.432 (0.263)	16.08 (3.17)	Relative humidity
78.7 (58.7)	2300	5.65 (21.40)	0.499 (0.304)	13.92 (2.74)	46%
39.7 (29.6)	2313	4.03 (15.25)	0.705 (0.429)	9.85 (1.94)	Barometer
--	2330	2.54 (9.63)	--	--	29.3" Hg (99.1 kPa)

Maximum Torque - 641.8 lb.-ft. (870.2 Nm) at 1400 rpm
 Maximum Torque rise - 51.8%
 Torque rise at 1800 engine rpm - 37%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—10th Gear									
155.2 (115.7)	10675 (47.48)	5.45 (8.77)	2100	5.5	0.449 (0.273)	15.53 (3.06)	176 (80)	57 (14)	29.6 (100.1)
75% of Pull at Maximum Power—10th Gear									
121.2 (90.4)	8005 (35.60)	5.68 (9.14)	2135	3.7	0.469 (0.285)	14.87 (2.93)	176 (80)	57 (14)	29.6 (100.1)
50% of Pull at Maximum Power—10th Gear									
82.6 (61.6)	5340 (23.75)	5.80 (9.34)	2165	3.0	0.528 (0.321)	13.24 (2.61)	176 (80)	57 (14)	29.6 (100.1)
75% of Pull at Reduced Engine Speed—11th Gear									
123.6 (92.2)	8055 (35.84)	5.75 (9.26)	1825	3.9	0.441 (0.268)	15.79 (3.11)	172 (78)	57 (14)	29.6 (100.1)
50% of Pull at Reduced Engine Speed—11th Gear									
83.3 (62.1)	5330 (23.71)	5.86 (9.43)	1840	2.8	0.492 (0.299)	14.16 (2.79)	172 (78)	57 (14)	29.6 (100.1)

Location of tests: HBLFA Francisco Josephinum
 BLT Biomass-Logistics-Technology,
 Rottenhauser, Strasse, 1, AT, 3250, Wieselburg,
 Austria

Dates of tests: October, 2010 to April, 2011.

Manufacturer: CNH UK Limited Basildon, Essex
 SS14 3AD United Kingdom

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.837
Fuel weight 6.97 lbs/gal (0.835 kg/l) **Oil SAE**
 10W30 **API service classification** CG-4
Transmission and hydraulic lubricant NH 410B
fluid Front axle lubricant NH 410B fluid

ENGINE: Make F.P.T. Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler and D.E.F. (diesel exhaust fluid) exhaust treatment. **Serial No.** 518516 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.094" x 5.197" (104.0 mm x 132.0 mm) **Compression ratio** 17.0 to 1 **Displacement** 410 cu in (6728 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** two paper canisters **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.** ZABZ41804 **Tread width** rear 60.2" (1530 mm) to 87.8" (2230 mm) front 61.4" (1560 mm) to 89.0" (2260 mm) **Wheelbase** 113.5" (2884 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with full range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.17 (1.89) second 1.40 (2.25) third 1.68 (2.71) fourth 2.01 (3.24) fifth 2.39 (3.85) sixth 2.86 (4.60) seventh 3.40 (5.47) eighth 4.06 (6.54) ninth 4.88 (7.86) tenth 5.83 (9.39) eleventh 6.95 (11.18) twelfth 8.30 (13.35) thirteenth 9.82 (15.80) fourteenth 11.74 (18.89) fifteenth 14.11 (22.70) sixteenth 16.86 (27.13) seventeenth 20.06 (32.29) eighteenth 25.10 (40.39) nineteenth 31.01 (49.90) reverse 2.59 (4.17), 3.10 (4.99), 3.73 (6.00), 4.45 (7.16), 5.30 (8.53), 6.33 (10.18) **Clutch** multiple wet disc electro-hydraulically operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1950 engine rpm or 1000 rpm at 1893 engine rpm **Unladen tractor mass** 18940 lb (8590 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp.°F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
124.7 (93.0)	16045 (71.38)	2.91 (4.69)	2130	15.0	7th Gear 0.497 (0.302)	14.02 (2.76)	180 (82)	55 (13)	29.6 (100.1)
149.8 (111.7)	15575 (69.28)	3.61 (5.81)	2080	10.4	8th Gear 0.458 (0.279)	15.22 (3.00)	178 (81)	55 (13)	29.6 (100.1)
158.0 (117.8)	16015 (71.23)	3.70 (5.95)	1800	11.3	9th Gear 0.445 (0.271)	15.63 (3.08)	178 (81)	55 (13)	29.6 (100.1)
162.9 (121.5)	13250 (58.93)	4.61 (7.42)	1800	6.5	10th Gear 0.425 (0.259)	16.40 (3.23)	176 (80)	57 (14)	29.6 (100.1)
167.0 (124.5)	11260 (50.09)	5.56 (8.95)	1800	5.6	11th Gear 0.420 (0.255)	16.60 (3.27)	176 (80)	55 (13)	29.6 (100.1)
164.4 (122.6)	9100 (40.48)	6.77 (10.90)	1800	4.4	12th Gear 0.425 (0.259)	16.40 (3.23)	176 (80)	54 (12)	29.6 (100.1)
170.0 (126.8)	7945 (35.35)	8.02 (12.91)	1800	4.0	13th Gear 0.412 (0.251)	16.90 (3.33)	176 (80)	54 (12)	29.6 (100.1)
168.8 (125.9)	6520 (29.00)	9.71 (15.63)	1800	3.4	14th Gear 0.418 (0.255)	16.65 (3.28)	176 (80)	54 (12)	29.6 (100.1)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's implement pump flow claim of 32 GPM (121 lpm). The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2614** Nebraska Summary 806, January 26, 2012.

Roger M. Hoy
Director

M.F. Kocher
D.R. Keshwani
P.J. Jasa
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 9th gear	67.0	67.0
Bystander	--	--

TIRES, BALLAST AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)
Front Tires - No., size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator - Rear
- Front
- Total

Tested without ballast

Two 710/70R38;**,16(110)
Two 600/65R28;**,16(110)
18.1 in (460 mm)
10880 lb (4935 kg)
8225 lb (3730 kg)
19105 lb (8665 kg)

This vehicle is equipped with an electronically controlled engine Power management system that monitors and boosts engine power output in certain circumstances. This is achieved by electronically changing the characteristics of the engine power-speed curve. The engine Power management function ("boosted" power level) becomes active in the higher transmission gears (16th and above) and for road transport applications. The system is also activated when power transfer through the PTO and hydraulic pump exceeds a preset level (and forward speed exceeds 0.5 km/h), for mobile PTO driven implement applications. An override system is provided to enable PTO operations at the "boosted" power level while the vehicle is stationary for test purposes. The results of this PTO output test are presented below.

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1162 rpm)					
207.3 (154.6)	2200	10.92 (41.32)	0.367 (0.223)	18.98 (3.74)	
Standard Power Take-off Speed - (1000 rpm)					
226.6 (169.0)	1893	11.76 (44.32)	0.361 (0.220)	19.29 (3.80)	
Maximum Power (1 hour)					
228.2 (170.2)	1800	11.75 (44.46)	0.358 (0.218)	19.44 (3.83)	

VARYING POWER AND FUEL CONSUMPTION

207.3 (154.6)	2200	10.92 (41.32)	0.367 (0.223)	18.98 (3.74)	Air temperature
181.2 (135.1)	2262	9.97 (37.74)	0.383 (0.233)	18.17 (3.58)	68°F (20°C)
136.9 (102.1)	2280	8.28 (31.33)	0.421 (0.256)	16.55 (3.26)	Relative humidity
92.0 (68.6)	2296	6.31 (23.89)	0.478 (0.290)	14.59 (2.87)	47%
46.4 (34.6)	2314	4.34 (16.41)	0.650 (0.395)	10.72 (2.11)	Barometer
-- --	2330	2.46 (9.30)	-- --	-- --	29.2"Hg (99.0 kPa)

Maximum Torque 725.5 lb.-ft. (983.7 Nm) at 1500 rpm
Maximum Torque Rise - 46.6%
Torque rise at 1800 rpm - 34%

HYDRAULIC PERFORMANCE

CATEGORY: III

Quick Attach: No

OECD Static test

Lift cylinders:

2 x 100 mm

Maximum force exerted through whole range: 12500 lbs (55.6 kN)

- i) Sustained pressure at compensator cutoff: 2900 psi (200 bar)
two outlet sets combined
- ii) Pump delivery rate at minimum pressure: 29.7 GPM (112.3 l/min)
- iii) Pump delivery rate at maximum
 hydraulic power: 26.1 GPM (98.7 l/min)
 Delivery pressure: 2610 psi (180 bar)
 Power: 39.7 HP (29.6 kW)

- single outlet set**
- ii) Pump delivery rate at minimum pressure: 29.5 GPM (111.5 l/min)
- iii) Pump delivery rate at maximum
 hydraulic power: 24.2 GPM (91.7 l/min)
 Delivery pressure: 2465 psi (170 bar)
 Power: 34.9 HP (26.0 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	32.1	815
B	15.0	380
C	15.1	383
D	14.6	372
E	10.8	275
F	10.6	270
G	36.4	925
H	2.4	60
I	17.7	450
J	25.8	655
K	26.9	682
L	48.2	1224
M	23.1	587
N	38.3	974
O	9.0	230
P	52.8	1340
Q	37.2	945
R	40.2	1020

