

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

2006 Bird Strike Committee USA/Canada, 8th
Annual Meeting, St. Louis, MO

Bird Strike Committee Proceedings

August 2006

OVERHEAD GRID LINE SYSTEMS TO EXCLUDE WATERFOWL FROM LARGE BODIES OF WATER

Tony Duffiney

USDA, Wildlife Services, Okemos, MI

Follow this and additional works at: <http://digitalcommons.unl.edu/birdstrike2006>



Part of the [Environmental Health and Protection Commons](#)

Duffiney, Tony, "OVERHEAD GRID LINE SYSTEMS TO EXCLUDE WATERFOWL FROM LARGE BODIES OF WATER" (2006). 2006 Bird Strike Committee USA/Canada, 8th Annual Meeting, St. Louis, MO. 20.

<http://digitalcommons.unl.edu/birdstrike2006/20>

This Article is brought to you for free and open access by the Bird Strike Committee Proceedings at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in 2006 Bird Strike Committee USA/Canada, 8th Annual Meeting, St. Louis, MO by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

From *Abstracts of the Proceedings of the 8th Bird Strike Committee USA/Canada Annual Meeting*, 21-24 August 2006, St. Louis, Missouri USA (www.birdstrike.org)

**(19) OVERHEAD GRID LINE SYSTEMS TO EXCLUDE WATERFOWL FROM
LARGE BODIES OF WATER**

Tony Duffiney, *USDA, Wildlife Services, 2803 Jolly Road, Suite 100, Okemos, MI 48864 USA*

The presence of birds at retention/detention basins on or adjacent to an airport increases the probability of experiencing a wildlife strike. Overhead gridline systems have proven effective for reducing the presence of birds on small water bodies. While there are several grid materials available to address bird hazards associated with small basins, the list of options decreases quickly as the distance to be spanned increases. The Michigan Wildlife Services program (WS) tested five types of grid material on three large detention basins to determine which materials could span up to 675 meters (2214.5 feet) without center supports. Additionally, the line material could not sag substantially, because of water fluctuations of up to 1.5 meters (5 feet) depending on the frequency and duration of rain events. If a line would touch the surface of the water, the surface tension would hold it in place until freeze-up. The material found to be superior in our tests, was a braided fishing line made of Spectra® called PowerPro. Grid lines were suspended in two directions on 30-meter (100 foot) spacing. Preliminary results show a notable reduction in bird usage by waterfowl and gulls.