

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Architectural Engineering -- Faculty Publications

Architectural Engineering and Construction,
Durham School of


2015

Air change rate vs airflow pathway: bioaerosol containment and removal in patient rooms

Kevin R. Grosskopf

University of Nebraska-Lincoln, kevin.grosskopf@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/archengfacpub>

 Part of the [Architectural Engineering Commons](#), [Construction Engineering Commons](#), [Environmental Design Commons](#), and the [Other Engineering Commons](#)

Grosskopf, Kevin R., "Air change rate vs airflow pathway: bioaerosol containment and removal in patient rooms" (2015). *Architectural Engineering -- Faculty Publications*. 93.

<http://digitalcommons.unl.edu/archengfacpub/93>

This Article is brought to you for free and open access by the Architectural Engineering and Construction, Durham School of at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Architectural Engineering -- Faculty Publications by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

POSTER PRESENTATION

Open Access

Air change rate vs airflow pathway: bioaerosol containment and removal in patient rooms

K Grosskopf

From 3rd International Conference on Prevention and Infection Control (ICPIC 2015)
Geneva, Switzerland. 16-19 June 2015

Introduction

Recent studies have shown that higher air change rates may have the unintended consequence of creating turbulent airflows that entrain high concentrations of infectious particles within the breathing zone, and possibly, breakdown pressure relationships necessary to contain the spread of infectious particles to other clinical spaces.

Objectives

A series of experimental and numerical tests were conducted in an actual hospital to observe the containment and removal of respirable aerosols (0.5-10 μ m) with respect to ventilation rate and directional airflow in a general patient room, and, an airborne infectious isolation room (AIIR).

Methods

A total of four experimental tests were conducted; two each in a general patient room and an infectious isolation room. A synthetic oil (polyaliphatic olefin) was continuously aerosolized at a rate of 15mg/0.4L of air per second to generate an aerosol (0.5 μ m - 10 μ m) at the approximate height of a patient lying at rest (0.8m). Particle size distribution samples were drawn at 30 sec intervals at 30 sampling locations in the test rooms over 4 hours. Computational analyses were used to validate the experimental results, and, to further quantify the particle transport phenomena.

Results

Increasing mechanical ventilation from 2.5 to 5.5 ACH reduced aerosol concentrations only 30% on average. However, particle concentrations were more than 40% higher in pathways between the source and exhaust as was the suspension and migration of larger particles (3 - 10 μ m) throughout the patient room(s). Higher ventilation rates

did not appear to affect directional airflow relationships between corridors and patient rooms having anterooms and a pressure differential of ≥ 2.5 Pa.

Conclusion

Higher ventilation rates were not found to be *proportionately* effective in reducing aerosol concentrations. Airflow pathways, not air change rates, were found to be the dominant environmental factor for bioaerosol migration and potential cross-infection.

Disclosure of interest

None declared.

Published: 16 June 2015

References

1. Grosskopf K, Mousavi E: Ventilation and Transport Bioaerosols in Health-Care Environments. *ASHRAE Journal* 2014, **56**:8:22.
2. Memarzadeh F, Xu W: Role of air changes per hour (ACH) in possible transmission of airborne infections. *Building Simulation* 2012, **5**(1):15-28.

doi:10.1186/2047-2994-4-S1-P94

Cite this article as: Grosskopf: Air change rate vs airflow pathway: bioaerosol containment and removal in patient rooms. *Antimicrobial Resistance and Infection Control* 2015 **4**(Suppl 1):P94.

Submit your next manuscript to BioMed Central and take full advantage of:

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

Submit your manuscript at
www.biomedcentral.com/submit



Engineering, University of Nebraska, Lincoln, NE, USA



© 2015 Grosskopf; licensee BioMed Central Ltd. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited. The Creative Commons Public Domain Dedication waiver (<http://creativecommons.org/publicdomain/zero/1.0/>) applies to the data made available in this article, unless otherwise stated.