

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 1931

Test 198: McCormick-Deering Farmall "F-30"

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 198: McCormick-Deering Farmall "F-30" (1931). *Nebraska Tractor Tests*. 806.
<http://digitalcommons.unl.edu/tractormuseumlit/806>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

UNIVERSITY OF NEBRASKA. - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Corrected Copy of Report of Official Tractor Test No. 198

Dates of test: October 9 to 23, 1931.

Name and model of tractor: McCORMICK-DEERING FARMALL "F 30"

Manufacturer: International Harvester Co., Chicago, Ill.

Manufacturer's rating: NOT RATED.

Highest rating permissible under the recommendations of the A.S.A.E. and
 S.A.E. Tractor Rating Codes: Drawbar - 20.27 H.P. Belt - 30.29 H.P.

One carburetor setting (97% of maximum) was used thruout this test.

B R A K E H O R S E P O W E R T E S T S

H. P.	:Crank : :shaft :	Fuel Consumption	: Water Consumption :	Temp. :	: Barometer
:speed :	:Gals. :	:H. P. :	:Lbs. per :	Cool- : In :	:Cool-: :Inches of
:R.P.M.:	:per :	:hrs. per:	H. P. :	ing : fuel : Total :	:ing : Air :Mercury
:	:hour :	:gal. :	:hour :	: : : : : :	:med. : : :

OPERATING MAXIMUM LOAD TEST. ONE HOUR

32.80 : 1150 : 3.414 : 9.61 : 0.704 : 0.00 : 0.00 : 0.00 : 182 : 76 : 28.820

RATED LOAD TEST. ONE HOUR

30.31 : 1150 : 3.327 : 9.11 : 0.742 : 0.00 : 0.00 : 0.00 : 191 : 75 : 28.785

*VARYING LOAD TEST. TWO HOURS

30.21 : 1150 : 3.182 : 9.49 : 0.712 : -- : -- : -- : 184 : 70 : --

0.73 : 1313 : 1.558 : 0.47 : 14.425 : -- : -- : -- : 178 : 71 : --

16.44 : 1244 : 2.601 : 6.32 : 1.069 : -- : -- : -- : 180 : 72 : --

33.92 : 1140 : 3.484 : 9.74 : 0.694 : -- : -- : -- : 178 : 72 : --

8.63 : 1288 : 2.104 : 4.10 : 1.648 : -- : -- : -- : 181 : 74 : --

23.11 : 1197 : 2.929 : 7.89 : 0.857 : -- : -- : -- : 181 : 73 : --

19.52 : 1222 : 2.643 : 7.39 : 0.915 : 0.00 : 0.00 : 0.00 : 180 : 72 : 28.975

*20 minute runs. Last line is average for two hours.

D R A W B A R H O R S E P O W E R T E S T S

H. P.	: Draw : Speed :	Crank : Slip :	Fuel Consumption	:Water:	Temp. :	:Barometer
: bar :	: Miles :	: shaft : on :	:H. P. :	:Lbs. :	:used :	:Inches of
: pull :	: per :	: speed : drive:	Gal.:	:hour :	:per :	:Cool-: :Mercury
:pounds:	:hour :	:R.P.M.:	:wheels:	:per :	:H.P. :	:ing :Air:
:	:	:	% :	:hour :	:gal. :	:hour :

RATED LOAD TEST. TEN HOURS. Second GEAR

20.88 : 2520 : 3.11 : 1150 : 3.44 : 3.152 : 6.62 : 1.024 : 0.053 : 175 : 69 : 28.580

MAXIMUM LOAD TEST

24.85 : 4157 : 2.24 : 1152 : 9.70 : ----- : Not Recorded : ----- : 175 : 58 : 28.720

23.93 : 2953 : 3.04 : 1151 : 6.54 : ----- : " " : ----- : 168 : 67 : 28.600

23.04 : 2327 : 3.71 : 1151 : 5.23 : ----- : " " : ----- : 175 : 68 : 28.600

22.00 : 1849 : 4.46 : 1145 : 4.34 : ----- : " " : ----- : 174 : 68 : 28.600

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
AGRICULTURAL COLLEGE, LINCOLN

Corrected Copy of Report of Official Tractor Test No. 198

BRIEF SPECIFICATIONS

MOTOR: Make Own Serial No. A A 518 Type 4 cylinder, vertical
Head I Mounting Lengthwise
Bore and stroke: 4 1/4" x 5" Rated R.P.M. 1150
Port Dia. Valves: Inlet 1.697" Exhaust 1.479"
Belt pulley: Diam. 14 5/8" Face 7" R.P.M. 682
Magneto: Own Model E 4 A
Carburetor: Zenith Model K 5 Size 1 1/4"
Governor: Own No. None Type Centrifugal
Air Cleaner: Own Type Oil-washed wire filter
Lubrication: Splash with circulating pump

CHASSIS: Type 4 wheels Serial No. F B 517 Drive Enclosed gear
Clutch: Own Type Single plate-dry Operated by foot
Advertised speeds, miles per hour: First 2 Second 2 3/4
Third 3 1/4 Fourth 3 3/4 Reverse 2 1/2
Drive wheels: Diameter 42" Face 12"
Lugs: Type Spade No. per wheel 24 Size 5" high x 3 1/2" face
Extension rims: Width 6" Lugs: 12 per rim Size 5" high x 3 1/2" face
Seat: Pressed steel
Total weight as tested (with operator) 5990 pounds.

FUEL AND OIL: 6.76 pounds on brake tests
Fuel: Kerosene Weight per gallon 6.78 pounds on rated drawbar tests
Oil: S.A.E. Viscosity No. 30 The oil was drained to the middle cock and refilled to top cock after approximately each 10 hours of operation. After 55 hours, all the oil was drained. Again at the end of the test all the oil was drained.
Total oil to motor 6.949 gallons
Total drained from motor 7.825 gallons
Total time motor was operated 66 hours

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 198

REPAIRS AND ADJUSTMENTS

The pin, which holds the splined end of the steering rod in the splined sleeve, sheared off twice, once during the limber up run and again during the rated load drawbar test. Each time the pin was replaced by another.

REMARKS

The tests herein reported were conducted with one carburetor setting which remained unchanged thruout the tests. This condition should be recognized when comparing this test with any Nebraska test conducted prior to 1928.

The drive wheels were equipped with spade lugs and extension rims and lugs as listed on Page 2 of this report.

In the advertising literature submitted with the specifications and application for test of this tractor we find no claims and statements which, in our opinion, are unreasonable or excessive.

We, the undersigned, certify that the above is a true and correct report of official tractor test No. 198.

Carlton L. Zink
Engineer-in-charge

E. E. Brackett

C. W. Smith

E. B. Lewis
Board of Tractor Test Engineers