

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 1948

Test 392: Ferguson Model TE-20

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 392: Ferguson Model TE-20" (1948). *Nebraska Tractor Tests*. 969.
<http://digitalcommons.unl.edu/tractormuseumlit/969>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 392

Dates of test: April 26, 1948 to May 10, 1948
 Name and model of tractor: FERGUSON TE-20**
 Manufacturer: HARRY FERGUSON, ltd., Coventry, England
 Manufacturer's rating: None

HORSEPOWER SUMMARY

	Drawbar	Belt
1. Sea level (calculated maximum horsepower) (based on 60° F. and 29.92" Hg.)	21.77	26.50
2. Observed maximum horsepower (tests F & B)	20.70	25.41
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (formerly ASAE and SAE ratings)	16.33	22.53

REMARKS

During test "B" a decrease in horsepower occurred. The head was removed and combustion chamber cleaned; improved performance resulted.

Fan belt was replaced with a new one during preliminary belt run.

FUEL, OIL, and TIME

Fuel Gasoline Octane 74* Weight per gallon 6.082
Oil SAE No. 20 To motor 2.225 gal. Drained from motor 1.594 gal.
Total time motor was operated 67 1/2 hours

*Octane rating taken from oil company's typical inspection data.

**Also designated as TO-20

We, the undersigned, certify that this is a true and correct report of official tractor test No. 392.

L. F. Larsen
 Engineer in Charge

C. W. Smith

F. D. Yung

L. W. Hurlbut
 BOARD OF TRACTOR TEST ENGINEERS

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 392

All results shown on pages 2 and 3 of this report were determined from observed data and without allowances, additions, or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, and J were made with an operating setting of the carburetor (selected by the manufacturer) of 94.2% of maximum belt horsepower.

B E L T H O R S E P O W E R T E S T S

Horsepower	Crank shaft speed rpm	Fuel Consumption			Water used gal. per hr.	Temperature		Barometer Inches of Mercury
		Gal per hr.	hp-hr per gal.	lb per hp-hr		cooling med ^o F.	Air ^o F	

TEST B - 100% MAXIMUM LOAD - TWO HOURS

25.41	1998	2.525	10.06	0.604	0.00	172	62	28.750
-------	------	-------	-------	-------	------	-----	----	--------

TEST C - OPERATING MAXIMUM LOAD - ONE HOUR

24.02	2005	2.272	10.57	0.575	0.00	170	58	28.750
-------	------	-------	-------	-------	------	-----	----	--------

*TEST D - ONE HOUR

22.59	2000	2.184	10.34	0.588	0.00	170	56	28.775
-------	------	-------	-------	-------	------	-----	----	--------

TEST E - VARYING LOAD - TWO HOURS (20 minute runs; last line average)

22.57	1999	2.180	10.35	0.588	----	171	58	-----
1.90	2239	1.159	1.64	3.711	----	164	57	-----
12.23	2160	1.638	7.47	0.814	----	166	57	-----
23.07	1884	2.161	10.68	0.570	----	171	58	-----
6.40	2201	1.332	4.80	1.266	----	165	59	-----
17.95	2100	1.939	9.26	0.657	----	169	59	-----
14.02	2097	1.735	8.08	0.752	0.00	168	58	28.790

*Formerly called RATED LOAD: see HORSEPOWER SUMMARY 3, page 1.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 392

D R A W B A R H O R S E P O W E R T E S T S

Horse Power	Draw bar pull lb.	Speed mph	Crank shaft speed rpm	Slip on drive wheels %	Fuel Consumption			Water used gal per hr.	Temperature		Barometer Inches of Mercury
					gal. per hr	hp-hr per gal	lb per hp-hr		Cool- ing med °F.	Air °F.	

Rear wheels, tires, and added weight used in Tests F, G, and H; Steel Disc Wheels; 10-28, 4 ply tires and 754 lb. added weight per wheel.

TEST F - 100% MAXIMUM LOAD - 2nd GEAR

20.70	2146	3.62	1751	6.35	-----Not Recorded -----			174	71	28.750
-------	------	------	------	------	-------------------------	--	--	-----	----	--------

TEST G - OPERATING MAXIMUM LOAD

18.34	2650	2.60	1751	7.46	----- Not Recorded -----			165	56	29.045
19.69	2028	3.64	1753	5.82	"	"		174	73	28.769
19.70	1445	5.11	1746	3.47	"	"		171	67	28.750
18.24	623	10.98	1758	1.40	"	"		171	70	28.700

*TEST H - TEN HOURS - 2nd GEAR

16.35	1666	3.68	1746	4.42	1.819	8.99	0.676	0.00	164	54	28.778
-------	------	------	------	------	-------	------	-------	------	-----	----	--------

TEST J - OPERATING MAXIMUM LOAD - 2nd GEAR

Same wheels and tires as used in Tests F, G, and H. All added weight removed from tractor (liquid, cast iron, or any other added forms).

16.90	1808	3.50	1750	10.91	----- Not Recorded -----			167	58	29.030
-------	------	------	------	-------	--------------------------	--	--	-----	----	--------

*Formerly called RATED LOAD; see HORSEPOWER SUMMARY 3, page 1.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 392.

TIRES, WHEELS, and WEIGHT

	Tests F, G, & H	Test J
Rear Wheel: Type (each)	Steel Disc	Steel Disc
Liquid Ballast	226 lb.	None
Added Cast Iron	528 lb	None
Rear Tires: No. Size & Ply	2 10-28 4 ply	2 10-28 4 ply
Type of Tread	All traction	All traction
Make	Goodyear	Goodyear
Air Pressure	12 lb	12 lb
Front Wheel: Type (each)	Pressed Steel	Pressed Steel
Liquid Ballast	26 lb	None
Added Cast Iron	97 lb	None
Front Tires: No. Size & ply	2 4.00-19 4 ply	2 4.00-19 4 ply
Type of tread	Guide Grip	Guide Grip
Make	Firestone	Firestone
Air Pressure	28 lb	28 lb
Height of Drawbar	12 inches	15 inches
Static Weight: Rear End	3098 lb	1590 lb
Front End	1212 lb	970 lb
Total Weight as Tested (with Operator)	4510 lb	2760 lb

