

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

January 2004

Nebraska Summary 491: Fendt 817 Vario Diesel

Nebraska Tractor Test Lab

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Nebraska Tractor Test Lab, "Nebraska Summary 491: Fendt 817 Vario Diesel" (2004). *Nebraska Tractor Tests*. 2153.

<https://digitalcommons.unl.edu/tractormuseumlit/2153>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2262—NEBRASKA SUMMARY 491

FENDT 817 VARIO DIESEL

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed (PTO speed-1104 rpm)					
146.6 (109.3)	2100	9.25 (35.00)	0.436 (0.265)	15.84 (3.12)	
Standard Power Take-off Speed (1000 rpm)					
156.0 (116.3)	1903	9.23 (34.93)	0.408 (0.248)	16.90 (3.33)	
Maximum Power (2 hours)					
158.9 (118.5)	1798	9.12 (34.51)	0.396 (0.241)	17.42 (3.43)	

VARYING POWER AND FUEL CONSUMPTION

146.6 (109.3)	2100	9.25 (35.00)	0.436 (0.265)	15.84 (3.12)	Air temperature
126.1 (94.0)	2123	8.27 (31.29)	0.453 (0.275)	15.24 (3.00)	66°F (19°C)
95.8 (71.4)	2146	6.47 (24.49)	0.466 (0.284)	14.80 (2.92)	Relative humidity
64.1 (47.8)	2167	4.82 (18.24)	0.518 (0.315)	13.31 (2.62)	30%
32.3 (24.1)	2186	3.39 (12.83)	0.723 (0.440)	9.54 (1.88)	Barometer
--	2203	1.86 (7.07)	--	--	29.7" Hg (100.7 kPa)
Maximum torque - 560 lb.-ft. (759 Nm) at 1301 rpm					
Maximum torque rise - 52.7%					
Torque rise at 1700 engine rpm - 31%					

DRAWBAR PERFORMANCE (Unballasted—Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F cool- ing med	°C Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Low Range									
125.1 (93.3)	8395 (37.35)	5.59 (9.00)	2099	2.0	0.511 (0.311)	13.70 (2.70)	153 (67)	70 (21)	29.7 (100.6)
75% of Pull at Maximum Power—Low Range									
96.0 (71.5)	6265 (27.86)	5.75 (9.25)	2133	1.5	0.545 (0.332)	12.83 (2.53)	151 (66)	72 (22)	29.7 (100.6)
50% of Pull at Maximum Power—Low Range									
64.9 (48.4)	4155 (18.49)	5.86 (9.43)	2156	1.1	0.618 (0.376)	11.32 (2.23)	144 (62)	72 (22)	29.7 (100.6)
75% of Pull at Reduced Engine Speed—Low Range									
96.5 (72.0)	6280 (27.94)	5.76 (9.27)	1759	1.5	0.473 (0.288)	14.77 (2.91)	153 (67)	72 (22)	29.7 (100.6)
50% of Pull at Reduced Engine Speed—Low Range									
65.2 (48.6)	4175 (18.57)	5.85 (9.42)	1765	0.8	0.516 (0.314)	13.55 (2.67)	149 (65)	72 (22)	29.7 (100.6)

Location of tests: DLG Testing Station for Agricultural Machinery Max - Eyth - Weg 1, D-64823, Gros-Umstadt, Germany

Dates of tests: March to May, 2004

Manufacturer: AGCO GmbH & Co. D-87616 Marktoberdorf, Germany

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60° F (15°/15°C)** 0.829 **Fuel weight** 6.90 lbs/gal (0.8269 kg/l) **Oil SAE 10W40 API service classification** CD **Transmission lubricant** SAE 10W40 **Hydraulic lubricant** SAE 10W40 **Front axle lubricant** 85W/90 gear oil, API GL-5

ENGINE: Make Deutz Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler **Serial No.** 00000860836 **Crankshaft** lengthwise **Rated engine speed** 2100 **Bore and stroke** 3.858" x 4.961" (98.0 mm x 126.0 mm) **Compression ratio** 18.0 to 1 **Displacement** 348 cu in (5702 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Fuel cooler** radiator for pump return fuel **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.** 718/22/0018 **Tread width** rear 60.0" (1524 mm) to 120.0" (3048 mm) front 60.0" (1524 mm) to 88.0" (2235 mm) **Wheel base** 106.3" (2700 mm) **Hydraulic control system** direct engine drive **Transmission** Fendt Vario. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. **Nominal travel speeds mph (km/h)** forward: Low range 0-17 (0-28), high range 0-31 (0-50) reverse: Low range 0-11 (0-17), high range 0-25 (0-40) **Clutch** a foot pedal controls the hydrostatic oil flow **Brakes** wet disc hydraulically operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1931 engine rpm or 1000 rpm at 1903 engine rpm. **Unladen tractor mass** 15960 lb (7240 kg)

DRAWBAR PERFORMANCE
(Unballasted–Front Drive Engaged)
MAXIMUM POWER AT SELECTED TRAVEL SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
115.6 (86.2)	17150 (76.29)	2.53 (4.07)	1869	14.8	Low Range 0.545 (0.331)	12.84 (2.53)	158 (70)	63 (17)	29.5 (99.8)
129.8 (96.8)	15635 (69.55)	3.11 (5.01)	1801	5.6	Low Range 0.483 (0.294)	14.47 (2.85)	162 (72)	64 (18)	29.5 (99.8)
134.1 (100.0)	12845 (57.15)	3.91 (6.30)	1801	3.4	Low Range 0.469 (0.285)	14.92 (2.94)	160 (71)	61 (16)	29.5 (99.8)
134.2 (100.1)	10620 (47.24)	4.74 (7.63)	1802	2.6	Low Range 0.470 (0.286)	14.87 (2.93)	160 (71)	61 (16)	29.5 (99.8)
133.4 (99.5)	9200 (40.93)	5.44 (8.75)	1801	2.1	Low Range 0.471 (0.286)	14.85 (2.92)	158 (70)	61 (16)	29.5 (99.8)
132.9 (99.1)	8040 (35.76)	6.20 (9.98)	1801	1.9	Low Range 0.474 (0.288)	14.75 (2.90)	160 (71)	61 (16)	29.5 (99.8)
131.2 (97.8)	6605 (29.39)	7.45 (11.98)	1802	1.4	Low Range 0.480 (0.292)	14.57 (2.87)	162 (72)	61 (16)	29.5 (99.8)
130.9 (97.6)	6400 (28.48)	7.67 (12.34)	1802	1.3	Low Range 0.480 (0.292)	14.57 (2.87)	163 (73)	61 (16)	29.5 (99.8)
124.6 (92.9)	10170 (45.24)	4.59 (7.39)	1801	2.6	High Range 0.505 (0.307)	13.86 (2.73)	163 (73)	61 (16)	29.5 (99.8)
130.5 (97.3)	8675 (38.59)	5.64 (9.08)	1801	2.0	High Range 0.483 (0.294)	14.47 (2.85)	162 (72)	59 (15)	29.5 (99.8)
133.0 (99.2)	7335 (32.64)	6.80 (10.94)	1801	1.7	High Range 0.475 (0.289)	14.72 (2.90)	160 (71)	59 (15)	29.5 (99.8)
133.3 (99.4)	6350 (28.24)	7.87 (12.67)	1801	1.3	High Range 0.473 (0.288)	14.77 (2.91)	160 (71)	59 (15)	29.5 (99.8)
132.6 (98.9)	5520 (24.56)	9.01 (14.50)	1804	1.3	High Range 0.475 (0.289)	14.72 (2.90)	160 (71)	57 (14)	29.5 (99.8)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE: The performance figures on this report are the result of replacing the electronic engine control module of the Fendt 818 with the 817 module.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance results on this summary were taken from OECD tests conducted under the Code II Test Code procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2262**, Nebraska Summary 491, December 15, 2005.

Leonard L. Bashford
Director

M.F. Kocher
V.I. Adamchuk
J.A. Smith
Board of Tractor Test Engineers

TIRES AND WEIGHT

Rear Tires–No., size, ply & psi (kPa)
Front Tires–No., size, ply & psi (kPa)
Height of Drawbar
Static Weight with operator–Rear
– Front
– Total

Tested Without Ballast

Two 650/65R42;**, 12 (80)
Two 540/65R30;**, 12 (80)
19.7 in (500 mm)
9765 lb (4430 kg)
6360 lb (2885 kg)
16125 lb (7315 kg)

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Engaged dB(A)	Disengaged dB(A)
Maximum Sound level	76.0	75.0
Sound level at 4.6 mph (7.5 km/h) - no load	68.0	68.0
Bystander	--	--

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: III

Quick Attach: Walterscheid lower links

Maximum force exerted through whole range: 13250 lbs (58.9 kN)

i) Opening pressure of relief valve:

NA

Sustained pressure of the open relief valve:

one outlet set

two outlet sets combined

2900 psi (200 bar)

2900 psi (200 bar)

ii) Pump delivery rate at minimum pressure:

20.9 GPM (79.1 l/min)

29.5 GPM (111.5 l/min)

iii) Pump delivery rate at maximum

hydraulic power:

20.5 GPM (77.5 l/min)

26.3 GPM (99.6 l/min)

Delivery pressure:

2465 psi (170 bar)

2685 psi (185 bar)

Power:

29.4 HP (21.9 kW)

41.2 Hp (30.7 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	29.1	740
B	13.8	350
C	19.3	390
D	15.4	315
E	9.4	240
F	10.0	255
G	35.6	905
H	2.2	55
I	16.1	410
J	25.6	650
K	26.2	665
L	45.1	1145
M	25.0	635
N	39.4	1000
O	9.1	230
P	52.6	1335
Q	38.6	980
R	30.5	775

